

	REVISION HISTORY	
REV.	DESCRIPTION	DATE
02	REVISED PER P10021	2012-04-10
Α	INITIAL RELEASE PER P10021	2012-04-27
В	REVISE PER	2014-02-28

15'[4572] CORD W/DUAL SWITCH LIGHTER ADAPTER

SPECIFICATIONS

CERTIFICATIONS: SAE J845 (Dec 2007) (SEE CHART);

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

2. FLASH MODE: SINGLE FAST: 120 ± 5 FLASHES PER MINUTE

DOUBLE: 80 ± 5 FLASHES PER MINUTE DOUBLE FAST: 120 ± 5 FLASHES PER MINUTE

3. VOLTAGE (NOMINAL): 12 to 24 VDC

4. VOLTAGE (EXTREME): 9.0 to 32 VDC

5. CURRENT (PEAK): 3.6A (@ 12 VDC NOMINAL)

6. POWER (MAXIMUM): 46.1W (@ 12 VDC NOMINAL)

7. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)

CONNECTION: 15' CORD W/DUAL SWITCH LIGHTER **ADAPTER**

9. MOUNTING: VACUUM/MAGNET MOUNT

10. BASE MATERIAL: ALUMINUM

DATE

11. LENS MATERIAL: POLYCARBONATE

12. PRODUCT WEIGHT: 3.1 LBS (1.4 Kg)

7.6[192.6]		

ODUCT CHA	.RT
COLOR	SAE J845
AMBER	CLASS 1
BLUE	CLASS 2
CLEAR	CLASS 1
GREEN	N/A
RED	N/A
	COLOR AMBER BLUE CLEAR GREEN

NOTES:

- ROHS COMPLIANT
- DIMENSIONS IN INCHES[MILLIMETERS(FOR REFERENCE)]

NON DISCLOSURE AGREEMENT	SURE AGREEMENT	DISCLOSURE AGREEMENT
--------------------------	----------------	----------------------

THIS DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ECCU AND IS SAUEL IN CONTINUED FRACTOR AS A WHOLE ONLY. THE DRAWING AND / OR DESIGN MAY NOT BE USED, COPIED, REPRODUCED, OR OTHERWISE DISCLOSED IN PART OR AS A WHOLE USED FOR ANY OTHER PURPOSE WITHOUT THE PROOF WRITHER CONSTITUTES ACCEPTANCE OF THESE TERMS. © 2012 ECCO

		GENERATED DRA		DRAWN BY	BND	2014-02-20		
		OT MANUALLY UF DEL REFERENCED		CHECKED	MDH	2014-02-28		
	TOLERANCES	ARE IN INCHES, AND TOLERANCES ARE:	MILLIMETERS	MECH. ENG.	JLA	2014-02-20		
	MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES ± 0.5°	ELEC. ENG.	TJT	2014-02-20	LED	BEACON
	XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04	FRACTIONS	TEST ENG.	JRT	2014-02-20	CUSTOMER PAR	
		X.XXX ± 0.02 RD ANGLE PROJECTION	± 1/64	SALES.	WNH	2014-02-20	SEE CH	1AKI
OR.		ANGLE PROJECTION	1				SIZE: A	DWG. NO.
N	(D		Electroni	ically Contro	olled Use Latest Copy	SHEET 1 OF 1	Project: P10021
								•

SCALE 1:3

APPROVALS

|--|

LED BEACON,360°,6",SWITC,12-24V,VM

Date Created: 2012-04-05

В

PRODUCT SERIES: CUSTOMER PART NO. JRT 2014-02-20 SEE CHART 2014-02-20 WNH DWG. NO. SIZE: 7970X-VM REV.