

| | REVISION HISTORY | | |
|------|----------------------------|------------|--|
| REV. | DESCRIPTION | DATE | |
| 02 | REVISED PER P10021 | 2012-04-10 | |
| Α | INITIAL RELEASE PER P10021 | 2012-04-27 | |
| В | REVISE PER | 2014-02-28 | |

15'[4572] CORD W/DUAL SWITCH LIGHTER ADAPTER

SPECIFICATIONS

1. CERTIFICATIONS: SAE J845 (Dec 2007) (SEE CHART); Note: Unique components, accessories, and hardware kits are

not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the

base product model configuration.

2. FLASH MODE: SINGLE FAST : 120 ± 5 FLASHES PER MINUTE

DOUBLE: 80 ± 5 FLASHES PER MINUTE

DOUBLE FAST: 120 ± 5 FLASHES PER MINUTE

3. VOLTAGE (NOMINAL): 12 to 24 VDC

4. VOLTAGE (EXTREME): 9.0 to 32 VDC

5. CURRENT (PEAK): 3.6A (@ 12 VDC NOMINAL)

6. POWER (MAXIMUM): 46.1W (@ 12 VDC NOMINAL)

7. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)

8. CONNECTION: 15' CORD W/DUAL SWITCH LIGHTER ADAPTER


9. MOUNTING: VACUUM/MAGNET MOUNT

10. BASE MATERIAL: ALUMINUM

11. LENS MATERIAL: POLYCARBONATE

12. PRODUCT WEIGHT: 3.1 LBS (1.4 Kg)

| 7.6[192.6] | |
|--------------|--|
| | |
| | |
| | |
| | |
| | |



SCALE 1:3

| | FGS PRODUCT CHART | | | |
|--|-------------------|-------|----------|--|
| | FGS. NO. | COLOR | SAE J845 | |
| | 7970A-VM | AMBER | CLASS 1 | |
| | 7970B-VM | BLUE | CLASS 2 | |
| | 7970C-VM | CLEAR | CLASS 1 | |
| | 7970G-VM | GREEN | N/A | |
| | 7970R-VM | RED | N/A | |
| | | | | |

NOTES:

- 1. ROHS COMPLIANT
- 2. DIMENSIONS IN INCHES[MILLIMETERS(FOR REFERENCE)]

NON DISCLOSURE AGREEMENT

THE DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ECCO. AND IS ISSUED IN CONTRIBUTE FOR ENGINEERINGINFORMATION.

NITH DRAWING AND / OR DESIGN MAY NOT BE USED, CAPIED REPRODUCED. OR OTHERWISE DESIC CORD. IN PART OR AS A WHOLE TO QUISDERS O
USED FOR ANY OTHER PURPOSE WHOLITHE PRIOR WRITTEN CONSENT OF ECCO. THE DRAWING IS SUBJECTED OF RECALL AT ANY TIME, YOUR POSSESSION.

| CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED:A+ | | | DRAWN BY | BND | 2014-02-20 |
|---|-----------------------------------|------------------|------------|-----|------------|
| | | | CHECKED | MDH | 2014-02-28 |
| TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES ARE: | | | MECH. ENG. | JLA | 2014-02-20 |
| ILLIMETERS DECIMALS | INCHES DECIMALS | ANGLES ± 0.5° | ELEC. ENG. | TJT | 2014-02-20 |
| XX. ± 1.0mm XX.X ± 0.5mm | X.X ± 0.1 X.XX ± 0.04 | FRACTIONS | TEST ENG. | JRT | 2014-02-20 |
| THI | X.XXX ± 0.02 RD ANGLE PROJECTION | ± 1/64 ON | SALES. | WNH | 2014-02-20 |
| (h) | | | | | |
| | | | | | |

APPROVALS

| LED BEACON,360°,6",SWITC,12-24V,VM | | | |
|------------------------------------|-----------------|--|--|
| CUSTOMER PART NO. | PRODUCT SERIES: | | |

SALES. WNH 2014-02-20 SEE CHART 7900

SIZE: A DWG, NO. 7970X-VM

Electronically Controlled Use Latest Copy SHEET 1 OF 1 Project: P10021 Date Created: 2012-04-05