



CAMERA SYSTEMS

CAMERAS

					
	EC2014-C	EC2014-WC	C2013B	EC2024-C	EC2023-C
approvals	IP69K, FCC, CE, R10 C-Tick, RoHS	IP69K, FCC, CE, R10, RoHS	IP69K, FCC, CE, RoHS	IP69K, FCC, CE, R10 RoHS	IP69K, FCC, CE, R10, RoHS
color	Yes	Yes	Yes	Yes	Yes
power consumption (W)	3	.25	1	2.5	1.3
microphone	Yes	Yes	-	Yes	Yes
day / night light sensor	Yes	Yes	Yes	Yes	Yes
dimensions	2.87" x 2.99" x 2.60"	2.87" x 2.99" x 2.98"	2.92" x 3.01" x 2.62"	3.6" x 2.7" x 2.5"	2.3" x 2.6" x 2.1"
weight	0.74 lbs	0.89 lbs	0.6 lbs	0.82 lbs	0.51 lbs
temperature (F°)	-22 to +158	-4 to +158	-22 to +158	-22 to +158	-22 to +158
lens angle	120°	120°	120°	120°	120°
lens size	1/3"	1/3"	1/4"	1/10"	1/10"
infrared LEDs	11	11	18	18	6
mechanical vibration	10G	10G	8G	10G	10G
4 pin camera connection	Yes*	-	Yes*	Yes*	Yes*

*threaded connection



CAMERA SYSTEMS

CAMERAS

approvals



EC2022-C

IP69K, FCC, CE, R10, C-Tick, RoHS



EC2015-C

IP67, FCC, CE, RoHS



EC2020-C

IP69, RoHS



EC2021-C

IP69, RoHS

	EC2022-C	EC2015-C	EC2020-C	EC2021-C
color	Yes	Yes	Yes	Yes
power consumption (W)	1.3	<1	2	2
microphone	-	No	-	-
day / night light sensor	Yes	Yes	-	-
dimensions	12.3" x 6.3" x 1.2"	1.69" x 1.24" x 1.1"	0.9" x 0.9" x 0.9"	0.6" diameter
weight	0.73 lbs	0.14 lbs	0.11 lbs	0.09 lbs
temperature (F°)	-22 to +158	-22 to +158	-22 to +158	-22 to +158
lens angle	150°	120°	170°	170°
lens size	3/5"	-	3/5"	3/5"
infrared LEDs	4	10	-	18
mechanical vibration	10G	-	10G	10G
4 pin camera connection	Yes*	Yes*	Yes*	Yes*

*threaded connection



BEACONS | MINIBARS | LIGHTBARS | DIRECTIONALS | WORKLAMPS | UTILITY BARS | INTERIOR LIGHTING | BACK-UP ALARMS

CAMERA SYSTEMS

EC5603-K 5.6" LCD Color System

Comprising a feature-packed 5.6" LCD high-resolution touch screen color monitor and CMOS color infrared camera, the EC5603-K delivers excellent picture quality even in low-light conditions. The compact monitor allows for unobtrusive installation without compromising viewable screen area. System is expandable up to 3 cameras.

FEATURES & BENEFITS

- Touchscreen menu control
- CMOS 11 LED infrared camera
- Includes monitor sunshade
- Three camera expandable
- One year warranty

COMPONENTS

- EC5603-M
- EC2014-C
- ECTC20-4

EXPANSION OPTIONS

- Any current ECCO camera
- ECTC5-4 (5m/16'), ECTC10-4 (10m/32'), ECTC20-4 (20m/65')

ACCESSORIES & REPLACEMENT PARTS

PC1.8Y-4 Wire Harness



EC5603-M

approvals	FCC, CE, R10, C-Tick, RoHS
internal controller	Yes
color	Yes
voltage	12-24
power consumption (W)	5
audio	Yes
day / night light sensor	Yes
dimensions	6.32" x 4.52" x 1.06"
weight	2.67 lbs
temperature (F°)	-4 to +158
screen size	5.6"
mirror image	Yes
remote control	Yes
sunshade	Yes
max cameras	3
4 pin camera connection	Yes



EC2014-C

approvals	IP69K, FCC, CE, R10, C-Tick, RoHS
color	Yes
power consumption (W)	3
microphone	Yes
day / night light sensor	Yes
dimensions	2.87" x 2.99" x 2.60"
weight	0.74 lbs
temperature (F°)	-22 to +158
lens angle	120°
lens size	1/3"
infrared LEDs	11
mechanical vibration	10G
4 pin camera connection	Yes (threaded connection)



ECTC20-4
20m/65' (4 pin)



BEACONS | MINIBARS | LIGHTBARS | DIRECTIONALS | WORKLAMPS | UTILITY BARS | INTERIOR LIGHTING | BACK-UP ALARMS

CAMERA SYSTEMS

EC7003-K 7.0" LCD Color System

The 7.0" LCD high-resolution touchscreen color monitor included with this system provides the optimal viewing area for mobile CCTV applications. Excellent picture quality is assured even in low-light conditions using ECCO's CMOS color infrared camera. The flat, widescreen monitor allows unobtrusive mounting with a large, easily viewable screen area. Expandable up to 3 cameras.

FEATURES & BENEFITS

- Touchscreen menu control
- CMOS 11 LED infrared camera
- Includes monitor sunshade
- Three camera expandable
- One year warranty

COMPONENTS

- EC7003-M
- EC2014-C
- ECTC20-4

EXPANSION OPTIONS

- Any current ECCO camera
- ECTC5-4 (5m/16'), ECTC10-4 (10m/32'), ECTC20-4 (20m/65')

ACCESSORIES & REPLACEMENT PARTS

PC1.8Y-4 Wire Harness



EC7003-M

approvals	FCC, CE, R10, C-Tick, RoHS
internal controller	Yes
color	Yes
voltage	12-24
power consumption (W)	6
audio	Yes
day / night light sensor	Yes
dimensions	8.4" x 6" x 2.8"
weight	3.3 lbs
temperature	-4 to +158
screen size	7.0"
mirror image	Yes
remote control	Yes
sunshade	Yes
max cameras	3
4 pin camera connection	Yes



EC2014-C

approvals	IP69K, FCC, CE, R10, C-Tick, RoHS
color	Yes
power consumption (W)	3
microphone	Yes
day / night light sensor	Yes
dimensions	2.87" x 2.99" x 2.60"
weight	0.74 lbs
temperature	-22 to +158
lens angle	120°
lens size	1/3"
infrared LEDs	11
mechanical vibration	10G
4 pin camera connection	Yes (threaded connection)



ECTC20-4
20m/65' (4 pin)