



CAMERA SYSTEMS

CAMERAS



EC2014-C



EC2014-WC



C2013B



EC2024-C



EC2023-C

approvals	IP69K, FCC, CE, R10 C-Tick, RoHS	IP69K, FCC, CE, R10, RoHS	IP69K, FCC, CE, RoHS	IP69K, FCC, CE, R10 RoHS	IP69K, FCC, CE, R10, RoHS
color	Yes	Yes	Yes	Yes	Yes
power consumption (W)	3	.25	1	2.5	1.3
microphone	Yes	Yes	-	Yes	Yes
day / night light sensor	Yes	Yes	Yes	Yes	Yes
dimensions	2.87" x 2.99" x 2.60"	2.87" x 2.99" x 2.98"	2.92" x 3.01" x 2.62"	3.6" x 2.7" x 2.5"	2.3" x 2.6" x 2.1"
weight	0.74 lbs	0.89 lbs	0.6 lbs	0.82 lbs	0.51 lbs
temperature (F°)	-22 to +158	-4 to +158	-22 to +158	-22 to +158	-22 to +158
lens angle	120°	120°	120°	120°	120°
lens size	1/3"	1/3"	1/4"	1/10"	1/10"
infrared LEDs	11	11	18	18	6
mechanical vibration	10G	10G	8G	10G	10G
4 pin camera connection	Yes*	-	Yes*	Yes*	Yes*

*threaded connection



CAMERA SYSTEMS

CAMERAS



EC2022-C



EC2015-C



EC2020-C



EC2021-C

approvals	IP69K, FCC, CE, R10, C-Tick, RoHS	IP67, FCC, CE, RoHS	IP69, RoHS	IP69, RoHS
color	Yes	Yes	Yes	Yes
power consumption (W)	1.3	<1	2	2
microphone	-	No	-	-
day / night light sensor	Yes	Yes	-	-
dimensions	12.3" x 6.3" x 1.2"	1.69" x 1.24" x 1.1"	0.9" x 0.9" x 0.9"	0.6" diameter
weight	0.73 lbs	0.14 lbs	0.11 lbs	0.09 lbs
temperature (F°)	-22 to +158	-22 to +158	-22 to +158	-22 to +158
lens angle	150°	120°	170°	170°
lens size	3/5"	-	3/5"	3/5"
infrared LEDs	4	10	-	18
mechanical vibration	10G	-	10G	10G
4 pin camera connection	Yes*	Yes*	Yes*	Yes*

*threaded connection