



# CAMERA SYSTEMS

## EC7003-K 7.0" LCD Color System

The 7.0" LCD high-resolution touchscreen color monitor included with this system provides the optimal viewing area for mobile CCTV applications. Excellent picture quality is assured even in low-light conditions using ECCO's CMOS color infrared camera. The flat, widescreen monitor allows unobtrusive mounting with a large, easily viewable screen area. Expandable up to 3 cameras.

### FEATURES & BENEFITS

- Touchscreen menu control
- CMOS 11 LED infrared camera
- Includes monitor sunshade
- Three camera expandable
- One year warranty


### COMPONENTS


 EC7003-M

 EC2014-C

 ECTC20-4

### EXPANSION OPTIONS

 Any current ECCO camera

 ECTC5-4 (5m/16'), ECTC10-4 (10m/32'), ECTC20-4 (20m/65')

### ACCESSORIES & REPLACEMENT PARTS

PC1.8Y-4 Wire Harness



**EC7003-M**

|                          |                            |
|--------------------------|----------------------------|
| approvals                | FCC, CE, R10, C-Tick, RoHS |
| internal controller      | Yes                        |
| color                    | Yes                        |
| voltage                  | 12-24                      |
| power consumption (W)    | 6                          |
| audio                    | Yes                        |
| day / night light sensor | Yes                        |
| dimensions               | 8.4" x 6" x 2.8"           |
| weight                   | 3.3 lbs                    |
| temperature              | -4 to +158                 |
| screen size              | 7.0"                       |
| mirror image             | Yes                        |
| remote control           | Yes                        |
| sunshade                 | Yes                        |
| max cameras              | 3                          |
| 4 pin camera connection  | Yes                        |



**EC2014-C**

|                          |                                   |
|--------------------------|-----------------------------------|
| approvals                | IP69K, FCC, CE, R10, C-Tick, RoHS |
| color                    | Yes                               |
| power consumption (W)    | 3                                 |
| microphone               | Yes                               |
| day / night light sensor | Yes                               |
| dimensions               | 2.87" x 2.99" x 2.60"             |
| weight                   | 0.74 lbs                          |
| temperature              | -22 to +158                       |
| lens angle               | 120°                              |
| lens size                | 1/3"                              |
| infrared LEDs            | 11                                |
| mechanical vibration     | 10G                               |
| 4 pin camera connection  | Yes<br>(threaded connection)      |



**ECTC20-4**  
20m/65' (4 pin)