

Safety   
**Director**<sup>™</sup>  
 Arrow



BEACONS | MINIBARS | LIGHTBARS | WORKLAMPS | UTILITY BARS | INTERIOR LIGHTING | BACK-UP ALARMS | CAMERA SYSTEMS

## DIRECTIONALS

### ED3307 SERIES SAE Class I LED Safety Director

The ED3307 LED Safety Director™ is a high output directional warning with the added benefits of low amp draw, maintenance free, and long-life LED light source. Features 35 flash pattern selectable via in-cab controller. The LED Safety Arrow is the definitive traffic direction lighting solution.

#### Models

PART NO.	VOLTAGE	MAX AMPS	TYPE	CABLE LENGTH	
ED3307A	12-24	2.8	Single Unit	35'	
ED3307SA	12-24	2.8	Split Arrow	35'	

#### Features and Benefits

- Extruded aluminum housing with polycarbonate lens
- 16 high-powered 3811 LED modules
- SAE J595 Class I, CE, R10
- Temperature Range: -22°F to +122°F (-30°C to +50°C)
- Warranty: 3 years

#### System Components

- Controller: ED3307CB
- Split Arrow Repl. Cable: R3307SACBL
- Cable: 15' 3410-15  
35' 3410-35  
55' 3410-55

#### Replacement Parts

- ED3307 Series are offered in Amber only; however, replacement color modules are available.
- ER3300X - Replace 'X' with A=Amber, B=Blue, C=Clear, R=Red

