









MOUNTING DISCLAIMER

MOUNTING MEASUREMENT IS FOR REFERENCE ONLY. MEASURE BEFORE DRILLING.

- 1. 142" CIGARETTE PLUG CABLE NOT SHOWN FOR CLARITY 2. ROHS COMPLIANT
- 3. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

	REVISION HISTORY						
REV.	DESCRIPTION						
03	REVISED PER EL0180	2020-12-14					
Α	INITIAL RELEASE PER EL0180	2021-02-15					
В	REVISED PER EL0180	2021-05-03					

SPECIFICATIONS

CERTIFICATIONS: ECE R10; AMECA/SAE J595 (MAR 2014) CLASS 1;, (SEE CHART); CA Title 13 (SEE CHART);

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

2. FLASH MODE: SINGLE: 75 ± 5 FLASHES PER MINUTE DOUBLE: 75 ± 5 FLASHES PER MINUTE QUAD: 75 ± 5 FLASHES PER MINUTE

3. VOLTAGE (NOMINAL): 12-24 VDC

4. VOLTAGE (EXTREME): 10-30 VDC

5. CURRENT (PEAK): SEE CHART (@ 12 VDC NOMINAL)

6. POWER (MAXIMUM): SEE CHART (@ 12 VDC NOMINAL)

7. TEMPERATURE RANGE: -40°F (-40°C) TO 149°F (65°C)

8. CONNECTION: CIG PLUG W/ON-OFF SWITCH

9. MOUNTING: ADHESIVE, SUCTION CUP OR 2 SCREWS

10. BASE MATERIAL: POLYCARBONATE

11. LENS MATERIAL: POLYCARBONATE

12. PRODUCT WEIGHT: 1.7 LBS (0.77 Kg)

1										
FGS. PRODUCT CHART										
	FGS. NO.	COLOR	CURRENT (PEAK) A	POWER (MAX) W	SAE J595	CA T13				
	ED5051VDL2-AW	AMB/WHT	1.7	21.1	CLASS 1; AMB, WHT	CLASS B; AMB				
	ED5051VDL2-BW	BLU/WHT	1.6	20.7	CLASS 1; BLU, WHT	CLASS B; BLU				
	ED5051VDL2-RW	RED/WHT	1.6	21.0	CLASS 1; RED, WHT	CLASS B; RED				
	ED5051VDL2-RWBW	RED/WHT/BLU/WHT	1.6	20.0	CLASS 1; WHT	-				

DISCLAIMER

DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. ECCO ENGINEERING DOES NOT MAINITAIN FORMAL DESIGN CONTROL OF THIS PRODUCT.

	SCALE 1:3		APF	PROVALS	DATE	12	3					
	CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: 01		DRAWN BY	JW	2021-04-26		\$	EC				
			CHECKED	BTK	2021-04-26	X	X					
	TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:		MECH. ENG.									
	MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES ± 0.5°	ELEC. ENG.			DI	REC	TIONAL,\	/ISOR,D	ECK,DASH,2 LIC	SHTS
	XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS	TEST ENG.	BAK	2021-05-03	CUSTON					
	TI-	IRD ANGLE PROJECTI	SALES			SEE CHART						
<u> </u>							SIZE:	В	DWG. NO.	ED50)51VDL2-XX	REV.
AD HIN				Electronically Controlled Use Latest Copy			SHEET 1	OF 1	Project: EL0180		Date Created: 2020-11-16	В

PROPRIETARY AND CONFIDENTIAL INFORMATION THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIA'
MAY NOT BE USED, COPIED, REPRODUCED OR OTHERWISE DISCLOSED IN PART OR IN WHOLE TO THIRD PARTIES OR USED FOR ANY OTHER PURPOSE WITHOUT PRIOR ECCO WRITTEN CO.