



**NOTES:**

- CABLE NOT SHOWN FOR CLARITY:  
6-20 AWG CONDUCTOR CABLE  
BLACK- GROUND(-)  
RED - POSITIVE(+)  
GREEN - CENTER WORKLIGHT(+)  
WHITE - WARNING LIGHT(+)  
BLUE - FLASH PATTERN SELECT(-), DIM ON WARNING PATTERN ONLY(+)  
YELLOW - SYNC
- CABLE DIMENSION IS 30.50 ± 1.00 [775 ± 25] FROM CABLE EXIT TO END OF WIRES
- ROHS COMPLIANT
- DIMENSIONS IN INCHES [MILLIMETERS (FOR REFERENCE)]

**DISCLAIMER**

DIMENSIONS, ILLUSTRATIONS, SPECIFICATIONS AND CERTIFICATIONS CONTAINED IN THIS DOCUMENT ARE TYPICAL OF THE ACTUAL PRODUCT AND ARE SUBJECT TO CHANGE. ECCO ENGINEERING DOES NOT MAINTAIN FORMAL DESIGN CONTROL OF THIS PRODUCT.

REVISION HISTORY		
REV.	DESCRIPTION	DATE
03	REVISED PER ELO157	2019-11-26
A	INITIAL RELEASE PER ELO157	2020-02-07
B	REVISED PER ELO157	2020-02-18

**SPECIFICATIONS**

- CERTIFICATIONS: SAE PENDING; IP67  
Note: Unique components, accessories, and hardware kits are not typically included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.
- FLASH MODE: SINGLE : 75 ± 5 FLASHES PER MINUTE  
SINGLE : 375 ± 5 FLASHES PER MINUTE  
DOUBLE : 75 ± 5 FLASHES PER MINUTE
- VOLTAGE (NOMINAL): 12-24 VDC
- VOLTAGE (EXTREME): 9.0-32 VDC
- CURRENT (PEAK): 3.26A (@ 12 VDC NOMINAL)
- POWER (MAXIMUM): 41.7W (@ 12 VDC NOMINAL)
- TEMPERATURE RANGE: -40°F (-40°C) TO 158°F (70°C)
- CONNECTION: 6-20 AWG CABLE
- MOUNTING: BRACKET MOUNT
- BASE MATERIAL: ALUMINUM
- LENS MATERIAL: POLYCARBONATE, UV STABILIZED
- PRODUCT WEIGHT: 4.12 LBS (1.85 Kg)

COLOR CHART	
FGS. NO.	COLOR
ED9215AW	AMBER/WHITE
ED9215BW	BLUE/WHITE
ED9215RB	RED/BLUE
ED9215RW	RED/WHITE

PROPRIETARY AND CONFIDENTIAL INFORMATION

THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES ("ECCO") AND IS ISSUED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HEREIN MAY NOT BE USED, COPIED, REPRODUCED OR OTHERWISE DISCLOSED IN PART OR IN WHOLE TO THIRD PARTIES OR USED FOR ANY OTHER PURPOSE WITHOUT PRIOR ECCO WRITTEN CONSENT. ECCO RESERVES ALL PATENT, COPYRIGHT, TRADEMARK AND OTHER PROPRIETARY RIGHTS TO THIS DOCUMENT, INCLUDING ALL DESIGN, MANUFACTURING, REPRODUCTION, USE AND SALES RIGHTS THEREOF. THIS DRAWING IS SUBJECT TO RECALL BY ECCO AT ANY TIME, AND YOUR POSSESSION AND/OR USE CONSTITUTES ACCEPTANCE OF THESE TERMS. ©2019 ELECTRONIC CONTROLS COMPANY

SCALE 1:4		APPROVALS	DATE
CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: 01		DRAWN BY ART	2020-02-07
TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:		CHECKED MDH	2020-02-10
MILLIMETERS DECIMALS XX ± 1.0mm XX.X ± 0.5mm	INCHES DECIMALS X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	MECH. ENG.	
ANGLES ± 0.5°		ELEC. ENG.	
FRACTIONS ± 1/64		TEST ENG.	
THIRD ANGLE PROJECTION		SALES MD	2020-02-10
Electronically Controlled Use Latest Copy			



**135 DEG WARN-WORK LIGHT COMBO, 12-24V**

CUSTOMER PART NO. <b>SEE CHART</b>			
SIZE: A	DWG. NO. ED9215XX	REV. B	
SHEET 1 OF 1	Project: ELO157	Date Created: 2019-10-04	