



REVISION HISTORY					
REV.	DESCRIPTION	DATE			
01	PRELIMINARY RELEASE PER LM13214	2013-10-28			
02	REVISED PER LM13214	2013-11-04			
Α	INITIAL RELEASE PER LM13214	2013-12-12			

## **SPECIFICATIONS**

**CERTIFICATIONS:** 

Note: Unique components, accessories, and hardware kits are not typically Included in the Product Certification Test Protocols. Unless otherwise Specified, the Product Certifications referred to herein are predicated upon the base product model configuration.

- 2. LUMINOUS FLUX: 3600 lumens
- 3. ILLUMINANCE: lux
- 4. PEAK BEAM INTENSITY: Candela
- 5. EFFICACY: 50.1 lm/W
- 6. CORRELATED COLOR TEMPERATURE: K
- 7. VOLTAGE (NOMINAL): 12 to 24 VDC
- 8. VOLTAGE (EXTREME): 10 to 30 VDC
- 9. CURRENT (PEAK): 5.2A (@ 12 VDC NOMINAL)
- 10. POWER (MAXIMUM): 71.8W (@ 12 VDC NOMINAL)
- 11. TEMPERATURE RANGE: -22°F (-30°C) TO 122°F (50°C)
- 12. CONNECTION: 2 CONDUCTOR CABLE
- 13. MOUNTING: BRACKET MOUNT
- 14. HOUSING MATERIAL: ALUMINUM
- 15. LENS MATERIAL: POLYCARBONATE
- 16. PRODUCT WEIGHT: 4.7 LBS (2.12 Kg)

1. DIMENSIONS IN INCHES[MILLIMETERS (FOR REFERENCE)]

THIS DRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROPERTY OF ECCO. AND IS ISSUED IN CONDIDENCE FOR ENGINEERING INFORMATION. DIVINITY THE DRAWING AND A OR DESIGN MAN YIGH EURO DUISIDERS OF OUR DIVINITY OF THE ORDER OR THE ORDER OF T

	SCALE 1:2		APP	ROVALS	DAIE
	GENERATED DRA		DRAWN BY	BND	2013-11-04
	OT MANUALLY UF DEL REFERENCEI		CHECKED	MDH	2013-11-05
TOLERANCE	S ARE IN INCHES, AND TOLERANCES ARE:	MILLIMETERS	MECH. ENG.	JLA	2013-11-04
MILLIMETERS DECIMALS	X.X ± 0.1 X.XX ± 0.04 FRACTI	ANGLES ± 0.5°	ELEC. ENG.	TJT	2013-11-06
XX. ± 1.0mm XX.X ± 0.5mm			TEST ENG.	JRT	2013-11-05
THI		± 1/64	SALES.	WNH	2013-11-05
$\mathcal{L}_{\mathcal{L}}$		1			
(		_	Electronically Controlled Use Lates		

+ DDDO0\/+\C

COALE 1.0



LED WORKLAMP, 4.5", SQUARE, 12-24 VDC, FLOOD

-11-06 PRODUCT SERIES: EW2311 CUSTOMER PART NO. -11-05 EW2311 -11-05

SIZE: DWG. NO. EW2311 REV. Date Created: 2013-10-28 e Latest Copy SHEET 1 OF 1 Project: LM13214