



UTILITY BARS



EW3100 SERIES

Single Row

ECCO's single row utility bars offer long, maintenance-free life expectancy, low amp draw, and extremely bright white light output. Available in three lengths, each with a choice of two mounting options. These bars are an ideal choice for both commercial and recreational applications. Features include 12-24 VDC operation, 5-watt LEDs, flood or combination flood/spot beam patterns, aluminum housing, polycarbonate lens, and a 5-year warranty.

Models

| PART NO. | TYPE | LENGTH | LUMENS (RAW) | AMPS |
|----------|------------------|--------|--------------|------|
| EW3109 | Flood | 9" | 875 | 0.8 |
| EW3120 | Flood/Spot Combo | 20" | 2,175 | 1.8 |
| EW3132 | Flood/Spot Combo | 32" | 3,475 | 3.0 |

Design Features

- 12-24 VDC
- Includes Deutsch DT04-2P 2 position built-in connector receptacle housing on light. Mates with Deutsch DT06-2S 2 position plug (provided in the box with light)
- Built-in vent to prevent fogging
- High-intensity beam
- Flood or combination flood/spot beams
- Adjustable end or extrusion mount
- Aluminum heatsink housing and polycarbonate lens
- Temperature range: -40°F to 158°F (-40°C to 70°C)

