



New—Eibach 16" XT Barrel Spring

XT Barrel | Performance Race Springs

New Eibach 16" XT Barrel Springs for the dirt and pavement circle track market. With the XT "Extreme Travel" Barrel design the ends actually nest inside the barrel portion slightly along with utilizing the highest tensile strength wire, we were able to use fewer coils per spring giving you the lightest and highest traveling spring in its class. This spring series utilizes the same highest tensile strength wire technology that is used in our Platinum series rear springs for the NASCAR Sprint Cup series. This technology delivers where you need it most: reduced unsprung weight, maximum travel and race-winning performance that lasts.



Team Eibach 2012: 649+ Wins, 37+ Championships and 8 Rookies of the year. Don't get left behind—make the switch to Eibach now! Eibach—The Will to Win.

EIBACH 16" XT BARREL SPRING

- Ultra Lightweight for Reduced Unsprung Mass
- Maximum Travel in Combination with the Smallest Block Heights
- Lowest Side Loads with Load Center Ideally Located Relative to the Spring Axis
- Precision Tolerances—The Tightest in the Industry
- Each Spring Individually Tested and Rated
- Eibach Springs Lifetime Warranty



Continued

NEW-EIBACH 16" XT BARREL SPRING :

APPLICATIONS

| Part Number | Length | Inside Diameter | Rate |
|--|--------|-----------------|----------|
| | inch | inch | lbs/inch |
| 10.00 (length in inches) XT Barrel (Extreme Travel) | | | |
| 1000.2530.0225 | 10.00 | 2.50 / 3.00 | 225 |
| 1000.2530.0250 | 10.00 | 2.50 / 3.00 | 250 |
| 1000.2530.0275 | 10.00 | 2.50 / 3.00 | 275 |
| 1000.2530.0300 | 10.00 | 2.50 / 3.00 | 300 |
| 1000.2530.0325 | 10.00 | 2.50 / 3.00 | 325 |
| 1000.2530.0350 | 10.00 | 2.50 / 3.00 | 350 |
| 1000.2530.0375 | 10.00 | 2.50 / 3.00 | 375 |
| 1000.2530.0400 | 10.00 | 2.50 / 3.00 | 400 |
| 1000.2530.0425 | 10.00 | 2.50 / 3.00 | 425 |
| 1000.2530.0450 | 10.00 | 2.50 / 3.00 | 450 |
| 1000.2530.0475 | 10.00 | 2.50 / 3.00 | 475 |
| 1000.2530.0500 | 10.00 | 2.50 / 3.00 | 500 |
| 1000.2530.0525 | 10.00 | 2.50 / 3.00 | 525 |
| 1000.2530.0550 | 10.00 | 2.50 / 3.00 | 550 |
| 1000.2530.0575 | 10.00 | 2.50 / 3.00 | 575 |
| 12.00 (length in inches) XT Barrel (Extreme Travel) | | | |
| 1200.2530.0100 | 12.00 | 2.50 / 3.00 | 100 |
| 1200.2530.0125 | 12.00 | 2.50 / 3.00 | 125 |
| 1200.2530.0150 | 12.00 | 2.50 / 3.00 | 150 |
| 1200.2530.0175 | 12.00 | 2.50 / 3.00 | 175 |
| 1200.2530.0200 | 12.00 | 2.50 / 3.00 | 200 |
| 1200.2530.0225 | 12.00 | 2.50 / 3.00 | 225 |
| 1200.2530.0250 | 12.00 | 2.50 / 3.00 | 250 |
| 1200.2530.0275 | 12.00 | 2.50 / 3.00 | 275 |
| 1200.2530.0300 | 12.00 | 2.50 / 3.00 | 300 |
| 1200.2530.0325 | 12.00 | 2.50 / 3.00 | 325 |
| 1200.2530.0350 | 12.00 | 2.50 / 3.00 | 350 |
| 1200.2530.0375 | 12.00 | 2.50 / 3.00 | 375 |
| 1200.2530.0400 | 12.00 | 2.50 / 3.00 | 400 |
| 1200.2530.0425 | 12.00 | 2.50 / 3.00 | 425 |
| 14.00 (length in inches) XT Barrel (Extreme Travel) | | | |
| 1400.2530.0100 | 14.00 | 2.50 / 3.00 | 100 |
| 1400.2530.0125 | 14.00 | 2.50 / 3.00 | 125 |
| 1400.2530.0150 | 14.00 | 2.50 / 3.00 | 150 |
| 1400.2530.0175 | 14.00 | 2.50 / 3.00 | 175 |
| 1400.2530.0200 | 14.00 | 2.50 / 3.00 | 200 |
| 1400.2530.0225 | 14.00 | 2.50 / 3.00 | 225 |
| 1400.2530.0250 | 14.00 | 2.50 / 3.00 | 250 |
| 16.00 (length in inches) XT Barrel (Extreme Travel) | | | |
| New! 1600.2530.0100 | 16.00 | 2.50 / 3.00 | 100 |
| New! 1600.2530.0125 | 16.00 | 2.50 / 3.00 | 125 |
| New! 1600.2530.0150 | 16.00 | 2.50 / 3.00 | 150 |
| New! 1600.2530.0175 | 16.00 | 2.50 / 3.00 | 175 |
| Torsion Release Bearing | | | |
| TRB250 | | 2.50 | |

