



# New—Eibach 16" XT Barrel Spring

XT Barrel | Performance Race Springs

New Eibach 16" XT Barrel Springs for the dirt and pavement circle track market. With the XT "Extreme Travel" Barrel design the ends actually nest inside the barrel portion slightly along with utilizing the highest tensile strength wire, we were able to use fewer coils per spring giving you the lightest and highest traveling spring in its class. This spring series utilizes the same highest tensile strength wire technology that is used in our Platinum series rear springs for the NASCAR Sprint Cup series. This technology delivers where you need it most: reduced unsprung weight, maximum travel and race-winning performance that lasts.



Team Eibach 2012: 649+ Wins, 37+ Championships and 8 Rookies of the year. Don't get left behind—make the switch to Eibach now! Eibach—The Will to Win.

## EIBACH 16" XT BARREL SPRING

- Ultra Lightweight for Reduced Unsprung Mass
- Maximum Travel in Combination with the Smallest Block Heights
- Lowest Side Loads with Load Center Ideally Located Relative to the Spring Axis
- Precision Tolerances—The Tightest in the Industry
- Each Spring Individually Tested and Rated  
Eibach Springs Lifetime Warranty



Continued

# NEW-EIBACH 16" XT BARREL SPRING :

## APPLICATIONS

Part Number	Length	Inside Diameter	Rate
	inch	inch	lbs/inch
<b>10.00 (length in inches) XT Barrel (Extreme Travel)</b>			
1000.2530.0225	10.00	2.50 / 3.00	225
1000.2530.0250	10.00	2.50 / 3.00	250
1000.2530.0275	10.00	2.50 / 3.00	275
1000.2530.0300	10.00	2.50 / 3.00	300
1000.2530.0325	10.00	2.50 / 3.00	325
1000.2530.0350	10.00	2.50 / 3.00	350
1000.2530.0375	10.00	2.50 / 3.00	375
1000.2530.0400	10.00	2.50 / 3.00	400
1000.2530.0425	10.00	2.50 / 3.00	425
1000.2530.0450	10.00	2.50 / 3.00	450
1000.2530.0475	10.00	2.50 / 3.00	475
1000.2530.0500	10.00	2.50 / 3.00	500
1000.2530.0525	10.00	2.50 / 3.00	525
1000.2530.0550	10.00	2.50 / 3.00	550
1000.2530.0575	10.00	2.50 / 3.00	575
<b>12.00 (length in inches) XT Barrel (Extreme Travel)</b>			
1200.2530.0100	12.00	2.50 / 3.00	100
1200.2530.0125	12.00	2.50 / 3.00	125
1200.2530.0150	12.00	2.50 / 3.00	150
1200.2530.0175	12.00	2.50 / 3.00	175
1200.2530.0200	12.00	2.50 / 3.00	200
1200.2530.0225	12.00	2.50 / 3.00	225
1200.2530.0250	12.00	2.50 / 3.00	250
1200.2530.0275	12.00	2.50 / 3.00	275
1200.2530.0300	12.00	2.50 / 3.00	300
1200.2530.0325	12.00	2.50 / 3.00	325
1200.2530.0350	12.00	2.50 / 3.00	350
1200.2530.0375	12.00	2.50 / 3.00	375
1200.2530.0400	12.00	2.50 / 3.00	400
1200.2530.0425	12.00	2.50 / 3.00	425
<b>14.00 (length in inches) XT Barrel (Extreme Travel)</b>			
1400.2530.0100	14.00	2.50 / 3.00	100
1400.2530.0125	14.00	2.50 / 3.00	125
1400.2530.0150	14.00	2.50 / 3.00	150
1400.2530.0175	14.00	2.50 / 3.00	175
1400.2530.0200	14.00	2.50 / 3.00	200
1400.2530.0225	14.00	2.50 / 3.00	225
1400.2530.0250	14.00	2.50 / 3.00	250
<b>16.00 (length in inches) XT Barrel (Extreme Travel)</b>			
New! 1600.2530.0100	16.00	2.50 / 3.00	100
New! 1600.2530.0125	16.00	2.50 / 3.00	125
New! 1600.2530.0150	16.00	2.50 / 3.00	150
New! 1600.2530.0175	16.00	2.50 / 3.00	175
<b>Torsion Release Bearing</b>			
TRB250		2.50	

