



# EIBACH PLATINUM SERIES PERFORMANCE SPRINGS



## Full Line of Platinum Fronts and Rears Now Available

Building on six decades of spring technology, Eibach introduces our most advanced ERS System. Designed specifically for the Dirt Modified Racer, the PLATINUM SERIES springs are engineered using our proprietary ultra-high tensile alloy to deliver increased travel, maximum rate linearity, lightest physical weights and legendary durability.

This is more than just a series of individual coils, the PLATINUM SERIES Springs are designed as a system. With the help of series Champions, we have engineered this system to work in harmony from front to rear, giving the driver increased control by way of the precise weight transfer characteristics of the system. On track—quickly free up the car on entry and keep the front pinned to make the pass—then put the power to the ground to make it stick!

Eibach PLATINUM SERIES Springs Deliver Maximum Control and Performance Wrapped Into an Ultra-Light Weight Package, Engineered to Put You and Your Team at the Top of the Podium.

- More Travel—Increased Travel Reduces Shear Loads and Stores More Energy, Which Equals Increased Grip In and Off The Corner.
- Ultra-Light Weight—For Increased Vehicle Response and More Usable Power to the Ground.
- Individually Tested—Each Platinum Spring is Wound to Exact Tolerances and Dyno Tested with Graph Results Included.
- Legendary Quality—Maximum Amounts of Travel, Rate Linearity and Block Resistance while Withstanding the Punishment of the Track.
- Built To Race—Engineered On the Track, for the Track. Made in the USA by Eibach.



## PLATINUM FRONT | COIL BIND

Part Number	Length		Outside Diameter		Rate @ 1200lbs & 1"	Height @ 1200lbs	Rate @ 1500lbs & 1"	Height @ 1500lbs	Block Height	Travel - 1500lbs to Block	Weight	
	inch	mm	inch	mm	lbs/inch	inch	lbs/inch	inch	inch	inch	lbs	kgs
Platinum Front   Coil Bind												
EF360.350-3345	8.75	222	5.75	146	360	5.536	350	4.712	2.190	2.522	4.87	2.21
EF370.355-3410	8.75	222	5.75	146	370	5.696	365	4.865	2.170	2.695	4.81	2.18
EF400.380-3720	8.75	222	5.75	146	400	5.849	380	5.094	2.130	2.964	4.73	2.15
EF425.415-3925	8.75	222	5.75	146	425	6.106	415	5.404	2.180	3.224	4.71	2.14
EF450.440-3990	8.75	222	5.75	146	450	6.261	440	5.587	2.270	3.317	4.74	2.15

**PLATINUM MODIFIED | FRONT SPRINGS**

Part Number	Length		Outside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kgs
Platinum Front Short Track - 5.00" O.D.														
PF0950.500.0500	9.50	241	5.00	127	500	88	3.15	80	6.38	162	3180	14144	4.87	2.21
PF0950.500.0525	9.50	241	5.00	127	525	92	3.27	83	6.26	159	3280	14589	4.78	2.17
PF0950.500.0550	9.50	241	5.00	127	550	96	3.27	83	6.26	159	3438	15292	4.95	2.25
PF0950.500.0575	9.50	241	5.00	127	575	101	3.11	79	6.42	163	3679	16366	5.10	2.31
PF0950.500.0600	9.50	241	5.00	127	600	105	3.58	91	5.91	150	3539	15743	5.24	2.38
PF0950.500.0625	9.50	241	5.00	127	625	109	3.66	93	5.84	148	3651	16241	5.14	2.33
PF0950.500.0650	9.50	241	5.00	127	650	114	3.54	90	5.94	151	3664	17187	5.08	2.30

**PLATINUM | REAR SPRINGS**

Part Number	Length		Outside Diameter		Rate		Block Height		Travel		Load at Block Height		Weight	
	inch	mm	inch	mm	lbs/inch	N/mm	inch	mm	inch	mm	lbs	N	lbs	kgs
Rear Platinum Springs - 5.00" O.D.														
ER16.0075	16.00	406	5.00	127	75	13	2.47	63	13.53	344	1015	4515	3.13	1.42
ER16.0085	16.00	406	5.00	127	85	15	2.57	65	13.43	341	1142	5080	3.64	1.65
ER16.0100	16.00	406	5.00	127	100	18	2.92	74	13.08	332	1308	5818	3.90	1.77
ER16.0125	16.00	406	5.00	127	125	22	3.07	78	12.93	328	1616	7188	4.60	2.09
ER16.0150	16.00	406	5.00	127	150	26	3.55	90	12.45	316	1868	8309	5.10	2.31
ER16.0175	16.00	406	5.00	127	175	31	3.78	96	12.19	310	2132	9483	5.87	2.66
ER16.0200	16.00	406	5.00	127	200	35	4.06	103	11.89	302	2379	10581	6.50	2.96
ER16.0225	16.00	406	5.00	127	225	39	4.25	108	11.73	298	2636	11725	6.94	3.15
ER15.0150	15.00	381	5.00	127	15	26	3.26	83	11.74	298	1761	7834	4.72	2.14
ER15.0175	15.00	381	5.00	127	175	31	3.44	87	11.56	294	2023	8998	5.18	2.35
ER15.0200	15.00	381	5.00	127	200	35	3.54	90	11.45	291	2291	10190	5.60	2.54
ER15.0225	15.00	381	5.00	127	225	39	4.08	104	10.92	277	2457	10929	6.19	2.81
ER15.0250	15.00	381	5.00	127	250	44	4.29	109	10.71	272	2678	11912	6.90	3.13
ER14.0100	14.00	356	5.00	127	100	18	2.48	63	11.54	293	1154	5132	3.20	1.45
ER14.0125	14.00	356	5.00	127	125	22	2.80	71	11.23	285	1404	6245	3.84	1.74
ER14.0150	14.00	356	5.00	127	150	26	2.91	74	11.11	282	1667	7413	4.17	1.89
ER14.0275	14.00	356	5.00	127	275	48	4.01	102	9.99	254	2747	12219	6.20	2.81
ER14.0325	14.00	356	5.00	127	325	57	4.29	109	9.71	247	3156	14039	7.20	3.27
ER14.0375	14.00	356	5.00	127	375	66	4.46	113	9.54	242	3578	15916	7.67	3.48
ER14.0400	14.00	356	5.00	127	400	70	4.74	120	9.26	235	3704	16476	8.45	3.83
ER135.0350	13.50	343	5.00	127	350	61	4.01	102	9.49	241	3322	14777	7.47	3.39
ER13.0300	13.00	330	5.00	127	300	53	3.70	94	9.30	236	2790	12410	6.44	2.92
ER13.0325	13.00	330	5.00	127	325	57	3.75	95	9.25	235	3006	13317	6.59	2.99
ER13.0475	13.00	330	5.00	127	475	83	4.86	123	8.14	207	3867	17201	8.55	3.88
ER13.0500	13.00	330	5.00	127	500	88	4.71	120	8.29	211	4145	18438	8.55	3.88
ER125.0175	12.50	318	5.00	127	175	31	3.23	82	9.27	235	1622	7214	4.10	1.86
ER125.0200	12.50	318	5.00	127	200	35	3.27	83	9.22	234	1845	8208	5.05	2.29
ER125.0225	12.50	318	5.00	127	225	39	3.21	82	9.29	236	2090	9299	5.05	2.29
ER125.0250	12.50	318	5.00	127	250	44	3.50	89	8.98	228	2245	9988	5.71	2.59
ER125.0275	12.50	318	5.00	127	275	48	3.50	89	9.00	229	2475	11009	5.77	2.62
ER125.0300	12.50	318	5.00	127	300	53	3.56	90	8.94	227	2681	11927	5.95	2.70
ER125.0400	12.50	318	5.00	127	400	70	4.41	112	8.09	205	3234	14387	7.47	3.39
ER1225.0325	12.25	311	5.00	127	325	57	3.86	98	8.38	213	2724	12119	6.70	3.04
ER1225.0350	12.25	311	5.00	127	350	61	3.93	100	8.32	211	2911	12950	6.92	3.14
ER1225.0375	12.25	311	5.00	127	375	66	4.00	102	8.24	209	3090	13743	7.15	3.25
ER12.0400	12.00	305	5.00	127	400	70	4.12	105	7.89	200	3152	14021	7.43	3.37
ER12.0425	12.00	305	5.00	127	425	74	3.82	97	8.18	208	3477	15466	6.99	3.17
ER12.0450	12.00	305	5.00	127	450	79	3.90	99	8.10	206	3645	16214	7.26	3.29
ER12.0475	12.00	305	5.00	127	475	83	4.05	103	7.95	202	3776	16796	7.61	3.45
ER12.0500	12.00	305	5.00	127	500	88	3.94	100	8.06	205	4030	17926	7.48	3.39
ER12.0525	12.00	305	5.00	127	525	92	4.16	106	7.84	199	4116	18309	7.75	3.52
ER12.0550	12.00	305	5.00	127	550	96	4.05	103	7.95	202	4373	19452	7.70	3.49
ER12.0600	12.00	305	5.00	127	600	105	4.10	104	7.90	201	4740	21084	8.00	3.63
ER12.0650	12.00	305	5.00	127	650	114	4.62	117	7.38	187	4797	21338	8.80	3.99

ER115.0700	11.50	292	5.00	127	700	123	4.43	113	7.07	180	4949	22014	8.30	3.76
ER115.0750	11.50	292	5.00	127	750	131	4.62	117	6.88	175	5160	22953	9.05	4.11
ER115.0800	11.50	292	5.00	127	800	140	4.79	122	6.71	170	5368	23878	9.35	4.24
ER115.0850	11.50	292	5.00	127	850	149	4.74	120	6.76	172	5746	25559	9.65	4.38
ER115.0900	11.50	292	5.00	127	900	158	5.03	128	6.47	164	5823	25902	10.10	4.58
ER115.0950	11.50	292	5.00	127	950	166	5.11	130	6.39	162	6071	27005	10.45	4.74
ER115.1000	11.50	292	5.00	127	1000	175	4.92	125	6.58	167	6580	29269	9.85	4.47
ER1125.0500	11.25	286	5.00	127	500	88	3.74	95	7.48	190	3732	16600	6.81	3.09
ER1125.0550	11.25	286	5.00	127	550	96	3.98	101	7.28	185	3998	14747	7.43	3.37
ER1125.0600	11.25	286	5.00	127	600	105	3.98	101	7.24	184	4335	19285	7.56	3.43
ER11625.0100	11.625	295	5.00	127	100	18	9.06	230	2.57	65	904	4020	2.40	1.09
ER11625.0125	11.625	295	5.00	127	125	22	8.94	227	2.69	68	1119	4976	2.62	1.19
ER11625.0150	11.625	295	5.00	127	150	26	8.70	221	2.93	74	5819	2.95	2.95	1.34