



PASSENGER | PERFORMANCE | SUV/LIGHT TRUCK

CONSUMER TIRE CATALOG 2025



PASSENGER | PERFORMANCE | SUV/LIGHT TRUCK

Since 1966, Eldorado® has been a leader in the replacement tire market and a key supplier to independent tire dealers throughout North America. The company's guiding principles of Performance, Engineering, Quality and Value continue to drive Eldorado® to remain a cornerstone of reliability and quality for our customers.

In addition to Eldorado® passenger and SUV/LT tires, our dealers have access to a comprehensive range of high-quality Commercial, Agricultural and Specialty tires, as well as supplemental products such as steel wheels, wheel weights, valve stems and tire equipment. We support all of our programs with informative point-of-sale material, attractive signage and superior customer service.

At Eldorado®, our goal is to be your complete line supplier, with the products and programs you need and the service and support you deserve.

TABLE OF CONTENTS

Tourmax GFT II

Touring All-Season 2

HTX Sport II

Highway SUV/LT 6

Sport Fury AT4S

All-Terrain SUV/LT 12

Mud Claw Comp MTX

Mud Traction LT 16

Performer CXV-C

Highway All-Season 20

CUSTOM 428 A/S

Passenger All-Season 22

Every effort has been made to verify the accuracy of the listed specifications. TBC Corporation and TBC Brands cannot be held responsible for any discrepancies, and as such, the information should be considered as approximate.



ELDORADO TOURMAX GFT II

The new **TOURMAX GFT II** is an all-season touring tire that delivers better durability and longevity compared to the previous generation. Developed for family sedans and minivans, the **TOURMAX GFT II** combines attractive pricing, long wear, year-round traction, dependable performance, a quiet, comfortable ride with an impressive size coverage.

TOURING ALL-SEASON

Warranty

- 60,000-mile/97,000-km limited treadwear warranty for H, T, V, W-Rated Tires



Features & Benefits

- Technology-driven tread design for superior all-weather performance
- Four wide grooves help evacuate water and slush to enhance traction in wet conditions
- Optimized tire profile evenly distributes weight over the tire's contact patch promoting even wear
- Reinforced large shoulder block area provides confident cornering capability and handling

Sizes

Available in 15" - 20" rim sizes



ELDORADO TOURMAX GFT II

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAMETER	SINGLE MAX. LOAD LBS @ PSI	DUAL MAX. LOAD LBS @ PSI	SHIP WEIGHT (LBS.)
*TBC-GPT10	175/65R15	84H	SL	480 A A	10	BSW	5.0	6.89	23.98	1102 @ 44	-	17
ELDO-ETM25	185/65R15	88H	SL	480 A A	10	BSW	5.5	7.28	24.45	1235 @ 44	-	19
*TBC-GPT73	185/60R15	84T	SL	460 A B	10	BSW	5.5	7.28	23.74	1102 @ 44	-	18
*TBC-GPT98	185/55R15	82H	SL	480 A A	10	BSW	6.0	7.28	23.03	1047 @ 44	-	17
ELDO-ETM28	195/65R15	91H	SL	480 A A	10	BSW	6.0	7.68	25.00	1356 @ 44	-	20
ELDO-ETM41	195/60R15	88H	SL	480 A A	10	BSW	6.0	7.68	24.21	1235 @ 44	-	19
*TBC-GPT29	205/70R15	96T	SL	500 A B	10	BSW	6.0	8.07	26.34	1565 @ 44	-	22
ELDO-ETM30	205/65R15	94T	SL	500 A B	10	BSW	6.0	8.07	25.47	1477 @ 44	-	21
ELDO-ETM33	215/70R15	98T	SL	500 A B	10	BSW	6.5	8.46	26.89	1653 @ 44	-	24
*TBC-GPT81	195/55R16	87H	SL	480 A A	10	BSW	6.0	7.68	24.41	1201 @ 44	-	19
ELDO-ETM54	205/65R16	95H	SL	480 A A	10	BSW	6.0	8.07	26.46	1521 @ 44	-	23
ELDO-ETM18	205/60R16	92H	SL	480 A A	10	BSW	6.0	8.07	25.67	1389 @ 44	-	20
ELDO-ETM42	205/55R16	91H	SL	480 A A	10	BSW	6.5	8.07	24.88	1356 @ 44	-	20
ELDO-ETM10	215/65R16	98T	SL	480 A A	10	BSW	6.5	8.46	27.01	1653 @ 44	-	24
ELDO-ETM48	215/60R16	95H	SL	480 A A	10	BSW	6.5	8.46	26.14	1521 @ 44	-	23
ELDO-ETM57	215/55R16	97H	XL	480 A A	10	BSW	7.0	8.46	25.28	1609 @ 50	-	23
ELDO-ETM83	225/65R16	100T	SL	500 A B	10	BSW	6.5	8.86	27.48	1764 @ 44	-	25
ELDO-ETM52	225/60R16	98H	SL	480 A A	10	BSW	6.5	8.86	26.61	1653 @ 44	-	25
*TBC-GPT99	235/65R16	103T	SL	500 A B	10	BSW	7.0	9.25	28.03	1929 @ 44	-	28
ELDO-ETM12	205/50R17	93V	XL	480 A A	10	BSW	6.5	8.07	25.12	1433 @ 50	-	21
*TBC-GPT61	215/65R17	99T	SL	480 A A	10	BSW	6.5	8.46	28.03	1709 @ 44	-	25
ELDO-ETM79	215/60R17	96H	SL	480 A A	10	BSW	6.5	8.46	27.17	1565 @ 44	-	24
ELDO-ETM08	215/55R17	94V	SL	480 A A	10	BSW	7.0	8.46	26.30	1477 @ 44	-	24

ELDORADO TOURMAX GFT II

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAMETER	SINGLE MAX. LOAD LBS @ PSI	DUAL MAX. LOAD LBS @ PSI	SHIP WEIGHT (LBS.)
ELDO-ETM58	215/50R17	95V	XL	480 A A	10	BSW	7.0	8.46	25.51	1521 @ 50	-	22
ELDO-ETM53	215/45R17	91V	XL	480 A A	10	BSW	7.0	8.46	24.65	1356 @ 50	-	20
ELDO-ETM76	225/65R17	102T	SL	480 A A	10	BSW	6.5	8.86	28.50	1874 @ 44	-	27
ELDO-ETM55	225/60R17	99H	SL	480 A A	10	BSW	6.5	8.86	27.64	1709 @ 44	-	26
ELDO-ETM88	225/55R17	97V	SL	480 A A	10	BSW	7.0	8.86	26.77	1609 @ 44	-	26
ELDO-ETM66	225/50R17	94V	SL	480 A A	10	BSW	7.0	8.86	25.91	1477 @ 44	-	24
ELDO-ETM71	225/45R17	94H	XL	480 A A	10	BSW	7.5	8.86	24.96	1477 @ 50	-	22
ELDO-ETM89	235/55R17	99V	SL	480 A A	10	BSW	7.5	9.25	27.17	1709 @ 44	-	27
*TBC-GPT92	225/55R18	98H	SL	480 A A	10	BSW	7.0	8.86	27.76	1653 @ 44	-	27
*TBC-GPT25	225/50R18	95H	SL	480 A A	10	BSW	7.0	8.86	26.89	1521 @ 44	-	25
ELDO-ETM14	225/45R18	95W	XL	380 A A	10	BSW	7.5	8.86	25.94	1521 @ 50	-	24
ELDO-ETM78	225/40R18	92H	XL	480 A A	10	BSW	8.0	8.86	25.08	1389 @ 50	-	22
ELDO-ETM34	235/55R18	104V	XL	480 A A	10	BSW	7.5	9.25	28.15	1984 @ 50	-	28
ELDO-ETM13	235/50R18	97W	SL	380 A A	10	BSW	7.5	9.25	27.28	1609 @ 44	-	27
ELDO-ETM19	235/45R18	94V	SL	480 A A	10	BSW	8.0	9.25	26.34	1477 @ 44	-	26
ELDO-ETM17	245/45R18	100W	XL	380 A A	10	BSW	8.0	9.65	26.65	1764 @ 50	-	26
ELDO-ETM75	245/40R18	97W	XL	380 A A	10	BSW	8.5	9.65	25.71	1609 @ 50	-	25
ELDO-ETM23	225/55R19	99H	SL	480 A A	10	BSW	7.0	8.86	28.78	1709 @ 44	-	29
ELDO-ETM36	235/55R19	101H	SL	480 A A	10	BSW	7.5	9.25	29.17	1819 @ 44	-	30
ELDO-ETM11	235/40R19	96V	XL	480 A A	10	BSW	8.5	9.25	26.42	1565 @ 50	-	25
ELDO-ETM94	245/45R19	98V	SL	480 A A	10	BSW	8.0	9.65	27.68	1653 @ 44	-	28
ELDO-ETM93	245/45R20	99H	SL	480 A A	10	BSW	8.0	9.65	28.66	1709 @ 44	-	29

*Branded Grand Prix Tour RS, same tread design

ELDORADO HTX SPORT II

The **HTX Sport II** has the versatility to meet the demand for today's most popular SUV/CUV fitments. This highway all-season tread design and blocks provides a smooth ride with superior traction performance. Whether city streets or on the highways, the enhanced technology implemented in the HTX Sport II delivers powerful results wherever you roam.

HIGHWAY SUV/LT

Warranty

- 60,000-mile/97,000-km limited treadwear warranty on P-Metric Sizes
- 55,000-mile/89,000-km limited treadwear warranty on Light Truck Sizes

Fits

Jeeps, Crossovers, Sport Utility Vehicles, and Mid to Full Size Pickups



Features & Benefits

- Wide circumferential grooves allowing rapid water evacuation and provide excellent hydroplaning resistance
- Semi closed shoulder blocks to isolate noise and enhance ride comfort
- Unique outer contour of the tire shoulder effectively disperses the shoulder ground pressure and enhances steering responsiveness
- Increased contact area with a balanced footprint pressure providing even wear and longer service life

Sizes

Available in 16" - 22" rim sizes



ELDORADO HTX SPORT II

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAMETER	SINGLE MAX. LOAD LBS @ PSI	Dual MAX. LOAD LBS @ PSI	SHIP WEIGHT (LBS.)
ELDO-HTX79	245/75R16	111S		600 A A	10	BLK	7.0	9.76	30.47	2403 @ 44	-	33
ELDO-HTX93	265/70R16	112T		600 A A	10	BLK	8.0	10.71	30.63	2469 @ 44	-	36
ELDO-HTX76	225/65R17	102H		600 A A	10	BLK	6.5	8.98	28.5	1874 @ 44	-	28
ELDO-HTX96	225/60R17	99H		600 A A	10	BLK	6.5	8.98	27.64	1709 @ 44	-	27
ELDO-HTX77	235/65R17	104H		600 A A	10	BLK	7.0	9.45	29.06	1985 @ 44	-	31
ELDO-HTX07	235/60R17	102H		600 A A	10	BLK	7.0	9.45	28.11	1874 @ 44	-	28
ELDO-HTX89	245/70R17	110T		600 A A	10	BLK	7.0	9.76	30.55	2335 @ 44	-	34
ELDO-HTX51	245/65R17	107H		600 A A	10	BLK	7.0	9.76	29.53	2150 @ 44	-	33
ELDO-HTX87	265/70R17	115T		600 A A	10	BLK	8.0	10.71	31.65	2680 @ 44	-	39
ELDO-HTX58	265/65R17	112T		600 A A	10	BLK	8.0	10.71	30.55	2469 @ 44	-	37
ELDO-HTX34	225/60R18	100H		600 A A	10	BLK	6.5	8.98	28.62	1764 @ 44	-	28
ELDO-HTX82	225/55R18	98V		600 A A	10	BLK	7.0	9.17	27.76	1653 @ 44	-	28
ELDO-HTX05	235/65R18	106H		600 A A	10	BLK	7.0	9.45	30.04	2094 @ 44	-	32
ELDO-HTX49	235/60R18	103H		600 A A	10	BLK	7.0	9.45	29.09	1929 @ 44	-	31
ELDO-HTX35	235/55R18	100H		600 A A	10	BLK	7.5	9.65	28.15	1764 @ 44	-	30
ELDO-HTX68	245/60R18	105H		600 A A	10	BLK	7.0	9.76	29.57	2039 @ 44	-	31
ELDO-HTX52	255/70R18	113T		600 A A	10	BLK	7.5	10.24	32.09	2535 @ 44	-	38
ELDO-HTX32	255/65R18	111H		600 A A	10	BLK	7.5	10.24	31.06	2403 @ 44	-	37
ELDO-HTX22	265/70R18	116T		600 A A	10	BLK	8.0	10.71	32.64	2756 @ 44	-	40
ELDO-HTX56	265/65R18	114T		600 A A	10	BLK	8.0	10.71	31.54	2601 @ 44	-	39

ELDORADO HTX SPORT II

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAMETER	SINGLE MAX. LOAD LBS @ PSI	Dual MAX. LOAD LBS @ PSI	SHIP WEIGHT (LBS.)
ELDO-HTX91	265/60R18	110T		600 A A	10	BLK	8.0	10.71	30.51	2337 @ 44	-	34
ELDO-HTX63	275/65R18	116H		600 A A	10	BLK	8.0	10.98	32.09	2756 @ 44	-	39
ELDO-HTX80	285/60R18	116V		600 A A	10	BLK	8.5	11.50	31.46	2756 @ 44	-	41
ELDO-HTX86	235/55R19	101V		600 A A	10	BLK	7.5	9.65	29.17	1819 @ 44	-	31
ELDO-HTX66	245/55R19	103V		600 A A	10	BLK	7.5	9.96	29.65	1929 @ 44	-	32
ELDO-HTX90	255/55R19	107H		600 A A	10	BLK	8.0	10.43	30.04	2149 @ 44	-	34
ELDO-HTX09	255/50R19	107Y	XL	600 A A	10	BLK	8.0	10.43	29.09	2149 @ 50	-	33
ELDO-HTX94	275/55R19	111V		600 A A	10	BLK	8.5	30.91	30.91	2403 @ 44	-	37
ELDO-HTX25	235/55R20	102H		600 A A	10	BLK	7.5	9.65	30.16	1874 @ 44	-	32
ELDO-HTX28	245/60R20	107H		600 A A	10	BLK	7.0	9.76	31.57	2149 @ 44	-	35
ELDO-HTX27	245/50R20	102V		600 A A	10	BLK	7.5	9.96	29.69	1874 @ 44	-	33
ELDO-HTX29	255/55R20	107H		600 A A	10	BLK	8.0	10.43	31.02	2149 @ 44	-	36
ELDO-HTX83	255/50R20	105H		600 A A	10	BLK	8.0	10.43	30.08	2039 @ 44	-	34
ELDO-HTX24	255/45R20	105Y	XL	600 A A	10	BLK	8.5	10.04	29.06	2039 @ 50	-	31
ELDO-HTX21	255/40R20	101Y	XL	600 A A	10	BLK	9.0	10.24	28.03	1819 @ 50	-	30
ELDO-HTX85	265/50R20	107V		600 A A	10	BLK	8.5	10.91	30.47	2149 @ 44	-	36
ELDO-HTX15	275/60R20	115T		600 A A	10	BLK	8.0	10.98	32.99	2679 @ 44	-	39
ELDO-HTX97	275/55R20	113T		600 A A	10	BLK	8.5	11.18	31.89	2535 @ 44	-	38
ELDO-HTX08	275/45R21	110W	XL	600 A A	10	BLK	9.0	10.75	30.75	2337 @ 50	-	36
ELDO-HTX13	275/50R22	115H	XL	600 A A	10	BLK	8.5	11.18	32.87	2535 @ 50	-	38

ELDORADO HTX SPORT II

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAMETER	SINGLE MAX. LOAD LBS @ PSI	Dual MAX. LOAD LBS @ PSI	SHIP WEIGHT (LBS.)
ELDO-HTX31	285/45R22	114H	XL	600 A A	10	BLK	9.5	11.22	32.09	2601 @ 50	-	39
ELDO-HTX17	LT235/85R16	120/116R	E		14	BLK	6.5	9.25	31.73	3042 @ 80	2778 @ 80	44
ELDO-HTX26	LT225/75R16	115/112R	E		14	BLK	6.0	8.78	29.29	2680 @ 80	2470 @ 80	39
ELDO-HTX38	LT245/75R16	120/116R	E		14	BLK	7.0	9.76	30.47	3042 @ 80	2778 @ 80	44
ELDO-HTX39	LT265/75R16	123/120S	E		14	BLK	7.5	10.51	31.65	3415 @ 80	3085 @ 80	48
ELDO-HTX95	LT235/80R17	120/117R	E		14	BLK	6.5	9.25	31.81	3085 @ 80	2835 @ 80	45
ELDO-HTX19	LT245/75R17	121/118S	E		14	BLK	7.0	9.76	31.50	3195 @ 80	2910 @ 80	46
ELDO-HTX92	LT265/70R17	123/120S	E		14	BLK	8.0	10.71	31.65	3415 @ 80	3085 @ 80	48
ELDO-HTX84	LT285/70R17	126/123S	E		14	BLK	8.5	11.54	32.76	3750 @ 80	3415 @ 80	54
ELDO-HTX40	LT275/70R18	125/122S	E		14	BLK	8.0	10.98	33.19	3640 @ 80	3305 @ 80	52
ELDO-HTX72	LT275/65R18	123/120S	E		14	BLK	8.0	10.98	32.09	3415 @ 80	3085 @ 80	53
ELDO-HTX43	LT275/65R20	126/123S	E		14	BLK	8.0	10.98	34.09	3750 @ 80	3415 @ 80	56



ELDORADO SPORT FURY AT4S

The **Eldorado Sport Fury AT4S** is designed to deliver all-weather superior traction for SUVs, pickups and vans, both on and off the road. The **Eldorado Sport Fury AT4S** provides exceptional handling, while maintaining a quiet and comfortable ride, making it the perfect choice to tackle whatever obstacles the elements throw at your vehicle!

Eldorado Sport Fury AT4S is designated with the USTMA Three Peak Mountain Snow Flake (3PMSF) symbol, indicating superior performance in snow and winter conditions.

ALL-TERRAIN SUV/LT

Warranty

55,000-mile/89,000-km limited treadwear warranty

Fits

Mid/Full-size pickups, Jeeps, SUVs, Vans



Features & Benefits

- Certified with USTMA 3PMSF symbol for severe winter performance
- Aggressive open shoulder tread design expels water, winter slush and mud for optimum traction in all terrain conditions
- Extra-deep tread sipes at varying angles improve comfort without sacrificing traction
- Jagged edge tread blocks improve grip on ice and in the mud providing superior traction
- Zigzag grooves and continuous center block provide outstanding grip and superior handling

Sizes

Available in 15" - 22" rim sizes



ELDORADO SPORT FURY AT4S

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAMETER	SINGLE MAX. LOAD LBS @ PSI	Dual MAX. LOAD LBS @ PSI	SHIP WEIGHT (LBS.)
ELDO-ESF12	235/75R15	109S	XL	500 AB	13	BSW	6.5	9.30	28.86	2271 @ 50	-	34
ELDO-ESF35	245/75R16	111S	SL	500 AB	13	BSW	7.0	9.80	30.47	2403 @ 44	-	37
ELDO-ESF32	265/75R16	116T	SL	500 AB	13	BSW	7.5	10.50	31.65	2756 @ 44	-	43
ELDO-ESF53	235/70R16	106S	SL	500 AB	13	BSW	7.0	9.40	28.98	2094 @ 44	-	35
ELDO-ESF80	245/70R16	111T	XL	500 AB	13	BSW	7.0	9.80	29.53	2403 @ 50	-	36
*TBC-TCA86	255/70R16	111T	SL	500 AB	13	BSW	7.5	10.20	30.08	2403 @ 44	-	38
ELDO-ESF37	265/70R16	112T	SL	500 AB	13	BSW	8.0	10.70	30.63	2469 @ 44	-	40
ELDO-ESF69	245/70R17	108T	SL	500 AB	13	BSW	7.0	9.80	30.55	2205 @ 44	-	39
ELDO-ESF10	255/70R17	110T	SL	500 AB	13	BSW	7.5	10.20	31.10	2337 @ 44	-	40
ELDO-ESF87	265/70R17	115S	SL	500 AB	13	BSW	8.0	10.70	31.65	2679 @ 44	-	42
ELDO-ESF51	245/65R17	107S	SL	500 AB	13	BSW	7.0	9.80	29.53	2150 @ 44	-	36
ELDO-ESF58	265/65R17	112T	SL	500 AB	13	BSW	8.0	10.70	30.55	2469 @ 44	-	40
ELDO-ESF52	255/70R18	113T	SL	500 AB	13	BSW	7.5	10.20	32.09	2535 @ 44	-	43
ELDO-ESF22	265/70R18	116T	SL	500 AB	13	BSW	8.0	10.70	32.64	2756 @ 44	-	46
ELDO-ESF56	265/65R18	114T	SL	500 AB	13	BSW	8.0	10.70	31.54	2601 @ 44	-	40
ELDO-ESF41	275/65R18	116T	SL	500 AB	13	BSW	8.0	11.00	32.09	2756 @ 44	-	42
*TBC-TCA91	265/60R18	110T	SL	500 AB	13	BSW	8.0	10.70	30.51	2337 @ 44	-	41
ELDO-ESF15	275/60R20	115T	SL	500 AB	13	BSW	8.0	11.00	32.99	2679 @ 44	-	44
ELDO-ESF48	275/55R20	117T	XL	500 AB	13	BSW	8.5	11.20	31.89	2833 @ 50	-	45
ELDO-ESF17	LT235/85R16	120/116R	E	-	16	BSW	6.5	9.30	31.73	3042 @ 80	2778 @ 80	48
ELDO-ESF23	LT225/75R16	115/112S	E	-	16	BSW	6.0	8.80	29.29	2680 @ 80	2470 @ 80	39
ELDO-ESF36	LT245/75R16	120/116S	E	-	16	BSW	7.0	9.80	30.47	3042 @ 80	2778 @ 80	45
ELDO-ESF33	LT265/75R16	123/120S	E	-	16	BSW	7.5	10.50	31.65	3415 @ 80	3085 @ 80	50
ELDO-ESF67	LT285/75R16	126/123R	E	-	16	BSW	8.0	11.30	33.07	3750 @ 80	3415 @ 80	57

ELDORADO SPORT FURY AT4S

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	UTQG	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAMETER	SINGLE MAX. LOAD LBS @ PSI	Dual MAX. LOAD LBS @ PSI	SHIP WEIGHT (LBS.)
ELDO-ESF95	LT235/80R17	120/117R	E	-	16	BSW	6.5	9.30	31.81	3085 @ 80	2835 @ 80	48
ELDO-ESF19	LT245/75R17	121/118S	E	-	16	BSW	7.0	9.80	31.73	3195 @ 80	2910 @ 80	49
ELDO-ESF70	LT245/70R17	119/116R	E	-	16	BSW	7.0	9.80	30.55	3000 @ 80	2755 @ 80	48
ELDO-ESF92	LT265/70R17	121/118S	E	-	16	BSW	8.0	10.70	31.65	3195 @ 80	2910 @ 80	49
ELDO-ESF83	LT285/70R17	121/118R	E	-	16	BSW	8.5	11.50	32.76	3195 @ 80	2910 @ 80	55
*TBC-TCA02	LT315/70R17	121/118S	E	-	16	BSW	9.5	12.70	34.41	3195 @ 65	2910 @ 65	66
ELDO-ESF30	LT265/70R18	124/121S	E	-	16	BSW	8.0	10.70	32.64	3525 @ 80	3195 @ 80	55
ELDO-ESF72	LT275/70R18	125/122R	E	-	16	BSW	8.0	11.00	33.19	3640 @ 80	3305 @ 80	54
ELDO-ESF40	LT275/65R18	123/120S	E	-	16	BSW	8.0	11.00	32.09	3415 @ 80	3085 @ 80	53
*TBC-TCA57	LT285/65R18	125/122S	E	-	16	BSW	8.5	11.10	32.56	3640 @ 80	3305 @ 80	58
*TBC-TCA98	LT325/65R18	127/124R	E	-	16	BSW	9.5	13.00	34.61	3860 @ 65	3525 @ 65	70
ELDO-ESF43	LT275/65R20	126/123S	E	-	16	BSW	8.0	11.00	34.09	3750 @ 80	3415 @ 80	57
*TBC-TCA74	LT265/60R20	121/118R	E	-	16	BSW	8.0	10.70	32.52	3195 @ 80	2910 @ 80	56
*TBC-TCA76	LT285/60R20	125/122R	E	-	16	BSW	8.5	11.50	33.46	3640 @ 80	3305 @ 80	60
*TBC-TCA99	LT325/60R20	121/118S	D	-	16	BSW	9.5	13.00	35.35	3195 @ 50	2910 @ 50	71
*TBC-TCA75	LT285/55R20	122/119R	E	-	16	BSW	9.0	11.7	32.36	3305 @ 80	3000 @ 80	58
*TBC-TCA54	LT305/55R20	121/118R	E	-	16	BSW	9.5	12.4	33.23	3195 @ 65	2910 @ 65	63
*TBC-TCA94	35X12.50R17LT	119Q	D	-	16	BSW	10.0	12.5	34.53	3000 @ 50	-	65
*TBC-TCA96	35X12.50R18LT	118Q	D	-	16	BSW	10.0	12.5	34.53	2910 @ 50	-	65
*TBC-TCA88	33X12.50R20LT	114S	E	-	16	BSW	10.0	12.5	32.52	2600 @ 65	-	62
*TBC-TCA71	35x12.50R20LT	121Q	E	-	16	BSW	10.0	12.5	34.53	3195 @ 65	-	66
*TBC-TCA89	33X12.50R22LT	109Q	E	-	16	BSW	10.0	12.5	32.52	2270 @ 65	-	60

*Branded Trailcutter AT4S, same tread pattern.

MUD CLAW COMP MTX

No matter the obstacle, the **Mud Claw Comp MTX** is designed to increase tire toughness, while providing an extreme level of off-road traction along with an aggressive, sleek tread design. For the driver who wants a combination of a Mud Traction light truck tire that offers plenty of on-road aptitude and aggressive off-road ability, the **Mud Claw Comp MTX** exceeds expectations when trail and terrain conditions are at their worst.

MUD TRACTION LT

Sizes

Available in 15" - 22" LT and Flotation sizes

Fits

Mid/Full-size Pickups, Jeeps, SUVs



Features & Benefits

- Maximum off-road performance at an economical price
- 3-ply sidewall construction for 18" - 20" provides enhanced strength and durability
- Deep, aggressive self-cleaning tread with stone ejectors
- Stylized black-letter sidewall boosts aesthetic appeal and delivers stylish, eye-catching appearance



MUD CLAW COMP MTX

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAMETER	SINGLE MAX. LOAD LBS @ PSI	Dual MAX. LOAD LBS @ PSI	SHIP WEIGHT (LBS.)
MTX12	LT235/75R15	104/101Q	C	19	BLK	6.5	9.25	28.86	1985 @ 50	1820 @ 50	41
MTX17	LT235/85R16	120/116Q	E	19	BLK	6.5	9.25	31.73	3085 @ 80	2755 @ 80	50
MTX36	LT245/75R16	120/116Q	E	19	BLK	7.0	9.76	30.47	3085 @ 80	2455 @ 80	48
MTX39	LT265/75R16	123/120Q	E	19	BLK	7.5	10.51	31.65	3415 @ 80	3085 @ 80	50
MTX67	LT285/75R16	126/123Q	E	19	BLK	8.0	11.26	32.83	3750 @ 80	3415 @ 80	60
MTX77	LT315/75R16	127/124Q	E	19	BLK	8.5	12.32	34.57	3860 @ 65	3525 @ 65	66
MTX79	LT235/80R17	120/117Q	E	19	BLK	6.5	9.25	31.81	3085 @ 80	2835 @ 80	59
MTX37	LT245/75R17	121/118Q	E	19	BLK	7.0	9.76	31.50	3195 @ 80	2910 @ 80	50
MTX90	LT265/70R17	121/118Q	E	19	BLK	8.0	10.71	31.65	3195 @ 80	2910 @ 80	51
MTX83	LT285/70R17	121/118Q	E	19	BLK	8.5	11.50	32.76	3195 @ 80	2910 @ 80	58
MTX21	LT295/70R17	121/118Q	E	19	BLK	8.5	11.77	33.31	3195 @ 80	2910 @ 80	60
MTX72	LT275/70R18	125/122Q	E	19	BLK	8.0	10.98	33.19	3640 @ 80	3305 @ 80	57
MTX40	LT275/65R18	123/120Q	E	19	BLK	8.0	10.98	32.09	3415 @ 80	3085 @ 80	57
MTX43	LT275/65R20	126/123Q	E	19	BLK	8.0	10.98	34.09	3750 @ 80	3415 @ 80	63
MTX42	LT295/65R20	129/126Q	E	19	BLK	8.5	11.77	35.12	4080 @ 80	3750 @ 80	69
MTX54	LT305/55R20	121/118Q	E	19	BLK	9.5	12.44	33.23	3195 @ 65	2910 @ 65	59
MTX78	30x9.50R15LT	104Q	C	19	BLK	7.5	9.45	29.53	1985 @ 50	-	42
MTX44	31x10.50R15LT	109Q	C	19	BLK	8.5	10.55	30.51	2270 @ 50	-	47
MTX41	32X11.50R15LT	113Q	C	19	BLK	9.0	11.42	31.54	2535 @ 50	-	52

MUD CLAW COMP MTX

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAMETER	SINGLE MAX. LOAD LBS @ PSI	Dual MAX. LOAD LBS @ PSI	SHIP WEIGHT (LBS.)
MTX33	33x12.50R15LT	108Q	C	19	BLK	10.0	12.52	32.52	2205 @ 35	-	66
MTX76	35X12.50R15LT	113Q	C	19	BLK	10.0	12.52	34.53	2535 @ 35	-	63
MTX93	33X12.50R17LT	121Q	F	20	BLK	10.0	12.52	32.52	3195 @ 80	-	66
MTX94	35x12.50R17LT	121Q	F	20	BLK	10.0	12.52	34.53	3195 @ 80	-	72
MTX99	33X12.50R18LT	122Q	F	20	BLK	10.0	12.52	32.52	3305 @ 80	-	66
MTX95	35X12.50R18LT	128Q	F	20	BLK	10.0	12.52	34.53	3970 @ 80	-	72
MTX02	33X12.50R20LT	119Q	F	20	BLK	10.0	12.52	32.52	3000 @ 80	-	64
MTX71	35X12.50R20LT	125Q	F	20	BLK	10.0	12.52	34.53	3640 @ 80	-	72
MTX03	37X12.50R20LT	128Q	F	20	BLK	10.0	12.52	36.54	3970 @ 80	-	77
MTX04	33X12.50R22LT	114Q	F	20	BLK	10.0	12.52	32.52	2600 @ 80	-	63
MTX05	35X12.50R22LT	121Q	F	20	BLK	10.0	12.52	34.53	3195 @ 80	-	71
MTX06	37X13.50R22LT	128Q	F	20	BLK	11.0	13.58	36.54	3970 @ 80	-	81

PERFORMER CXV-C

The ALL-NEW **Performer CXV-C** is an all-season, commercial highway light truck tire designed for vans and multi-purpose vehicles that transport heavy loads. With superior handling and year-round traction on dry and wet roads, the **Performer CXV-C** is the ideal tire to complement your needs, whether for modern delivery or recreational use.

HIGHWAY ALL-SEASON

Features & Benefits

- Large shoulder block design enhances steering and cornering
- Steel-belt construction resists damage and irregular wear
- Deep, wide grooves provide traction in all conditions
- M & S-rated for year-round performance capability

Sizes

Available in 15" - 16" LT and C-rated sizes

Fits

Commercial Vans, Transporters



PERFORMER CXV-C

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAMETER	SINGLE MAX. LOAD LBS @ PSI	Dual MAX. LOAD LBS @ PSI	SHIP WEIGHT (LBS.)
PCX73	185/60R15C	94/92T	C	12	BSW	5.5	7.44	23.74	1475 @ 54	1390 @ 54	21
PCX39	195/75R16C	107/105R	D	12	BSW	5.5	7.72	27.48	2150 @ 69	2040 @ 69	26
PCX31	205/75R16C	113/111Q	E	12	BSW	5.5	7.99	28.11	2535 @ 76	2405 @ 76	26
PCX77	225/75R16C	121/120R	E	12	BSW	6.0	8.78	29.29	3195 @ 83	3085 @ 83	33
PCX56	235/65R16C	121/119R	E	11	BSW	7.0	9.45	28.03	3195 @ 83	3000 @ 83	33
PCX26	LT225/75R16	115/112R	E	12	BSW	6.0	8.78	29.29	2680 @ 80	2470 @ 80	33
PCX38	LT245/75R16	120/116S	E	12	BSW	7.0	9.76	30.47	3085 @ 80	2755 @ 80	36



CUSTOM 428 A/S

Dependable and affordable all-season passenger tire. The **Custom 428 A/S** features attractive white sidewall styling and nine popular 70/75 series sizes. All-season tread design for dependable traction and handling.

PASSENGER ALL-SEASON

Features & Benefits

- White sidewall
- Smooth, quiet ride
- M & S rated for year-round performance capability
- Economy-priced
- 4 circumferential grooves provide outstanding water evacuation

Sizes

Available in 14" & 15" S-rated sizes

Fits

Sedans, Coupes, Compacts, Minivans



CUSTOM 428 A/S

ARTICLE NO.	TIRE SIZE	SERVICE DESC.	LOAD RANGE	TREAD DEPTH (32ND)	SIDE WALL	RIM WIDTH	OVERALL WIDTH	OVERALL DIAMETER	SINGLE MAX. LOAD LBS @ PSI	Dual MAX. LOAD LBS @ PSI	SHIP WEIGHT (LBS.)
CUS39	P195/75R14	92S	SL	440 A B	10	WSW	5.5	7.72	25.51	1400 @ 44	18
CUS47	P205/75R14	95S	SL	440 A B	10	WSW	5.5	7.99	26.14	1532 @ 44	20
CUS34	P205/75R15	97S	SL	440 A B	10	WSW	5.5	7.99	27.13	1598 @ 44	22
CUS45	P215/75R15	100S	SL	440 A B	10	WSW	6.0	8.50	27.68	1742 @ 44	23
CUS49	P225/75R15	102S	SL	440 A B	10	WSW	6.0	8.78	28.31	1874 @ 44	24
CUS64	P235/75R15	105S	SL	440 A B	10	WSW	6.5	9.25	28.86	2028 @ 44	27
CUS29	P205/70R15	95S	SL	440 A B	10	BSW	6.0	8.23	26.34	1499 @ 44	21
CUS33	P215/70R15	97S	SL	440 A B	10	WSW	6.5	8.70	26.89	1620 @ 44	23
CUS96	P225/70R15	100S	SL	440 A B	11	WSW	6.5	8.98	27.44	1753 @ 44	25

ELDORADO TIRE[®]

TBCBrands[®]

4260 Design Center Drive, Palm Beach Gardens, FL 33410



eldoradotire.com · tbcbrands.com · 1-866-822-4968

ELDORADO is a registered trademark of TBC Corporation