Non-Marring Lug Nut Socket Set MODEL 40308





BENEFITS & FEATURES:

- ▶ The most popular size lug nuts in the performance market.
- ▶ ½" Drive Suitable for use with impact tool.
- Nylon sleeve and insert to prevent alloy wheel damage or marring.
- ► Color-coded sockets for simple identification.
- Extended socket length eliminates needs for torque extension.
- CR-MO Alloy Steel for long lasting use.

ESCO 3-piece socket sets are the most popular size lug nuts and are ideal for automotive shops and garages. Color-coded, etched sockets allow for easy identification and the non-slip design provides accurate application with each use. The chamfered socket design easily attached to nuts and durable sleeves protect wheels and nuts from marring or damage.









Model # Description	40308 1/2 in. Drive 6-Piece Metric Non-Marring Lug Nut Socket Set w/ MS17 6-Point "Flower Design" Socket
Socket Size(s)	1 PC 1/2 in. MS17 Nylon Protected Wheel CR-MO Socket 1 PC 1/2 in. 15mm Nylon Protected Wheel CR-MO Socket 1 PC 1/2 in. 17mm Nylon Protected Wheel CR-MO Socket 1 PC 1/2 in. 19mm Nylon Protected Wheel CR-MO Socket 1 PC 1/2 in. 21mm Nylon Protected Wheel CR-MO Socket 1 PC 1/2 in. 22mm Nylon Protected Wheel CR-MO Socket
Socket Color(s)	Assorted
Measurement System	Metric
Wall Thickness	Standard
Drive Size	1/2 in.
Socket(s) Length	3.5 in. 89 mm
Case Dimensions	12 (L) \times 6.5 (W) \times 1.75 in. (H) 305 \times 177.8 \times 50.8 mm
Includes	(6) Sockets, (6) Nylon Rim Protective Sleeves (Installed on Sockets), Case
Weight	4 lbs. 1.82 kg
Material	CR-MO (Chromium-Molybdenum) alloy steel
Markets	Automotive, Performance, Shop
Warranty	Limited Lifetime*
UPC	816904024918



NOTE: ESCO reserves the right to change, alter, or modify product(s) without notice. This includes but is not limited to product: color, design, parts, accessories, etc.

