



INSTALL GUIDE

Ferrari 488 GTB & 458 Italia Harness Bar & Mounting Kit



Included Components

- 1 Harness Bar
- 8 Shoulder Harness Collars
- 2 Sub-Belt Mounting Brackets
- 4 Sub-Belt Mounting Bracket Bolts
- 4 Sub-Belt Mounting Bracket Nuts
- 8 Sub-Belt Mounting Bracket Washers
- 1 Child Restraint Bracket Mounting Bolt

Required Tools

Ratchet & Metric Socket Set
T25 Torx Bit
Open-End Wrench Set
Needle-Nose Pliers
Hex/Allen Wrench Set
Painters Tape (*Recommended*)

CAUTION

- *Always allow car to cool before performing any installation(s) or service(s) on it.*
- *Always be sure to work on an even and level surface when raising vehicle(s) with a jack, and support all raised vehicles with locked jack stands once elevated.*
- *Fabspeed Motorsport recommends that all installations be supervised or verified by a trained professional technician.*
- *Fabspeed Motorsport is not responsible for any personal injury or damage(s) sustained to a vehicle during installation of aftermarket performance parts.*




1. Park car and slide both seats fully forward.



2. Remove both top seatbelt covers.



3. Using a 17mm socket, remove the upper seatbelt mounting bolts.





- Using needle nose pliers, remove the plastic retaining ring and separate the bolt and spacer from the mounting collar.



- 488 GTB ONLY** (For 458, skip to step 6): Using a T-25 Torx bit, remove the (2) fasteners securing the child seat restraint cover panel.



- 458 ITALIA ONLY:** Using a 3mm hex wrench, remove the (2) fasteners securing the child seat restraint cover panel.







7. Remove the plastic cover panel.



8. Using a 13mm socket, remove the top mounting bolt.



9. Using painter's tape, cover the rear side panels to protect them during installation of the bar.





10. Position the bar inside of the car and slide the bolt into position, sandwiching the bar's end mount between the seatbelt mounting collar and the spacer. *(NOTE: It is helpful to have a second person during this step to help support the other end of the bar during positioning.)*



11. Thread the bolt back into the side pillar and finger tighten. Do not fully tighten at this point.



12. Position the support bracket on top of the child seat mounting tab and insert the supplied 13mm bolt. Tighten using a ratcheting wrench. *(NOTE: You can also use a 13mm socket, but it's difficult due to the space constraints. Due to the slight variations in vehicles construction, it may be necessary to remove the child seat restraint bracket in order to get the harness bar support positioned correctly before re-installing the restraint bracket.)*





- Using a 17mm socket, tighten the seatbelt bolts to secure to bar in place.



- Re-install the seatbelt covers and remove the protective tape.



- Using a 5/16" hex wrench, install the supplied shoulder harness collars.





- Using a 13mm socket and a 13mm open-end wrench, install the supplied sub-belt mounting brackets by inserting the supplied 13mm bolts into the forward-most holes in the seat rails.



- Complete the installation by mounting the 5- or 6-point harness of your choice.

