

WILDPEAK A/T

RUGGED, DYNAMIC, ALL-PURPOSE, ALL-TERRAIN PERFORMANCE

The **WILDPEAK A/T** reinvigorates the all-performance sport utility and light truck tire market through its aggressive stance and unparalleled traction. A symmetric five-rib pattern and rigid block design allows for enhanced durability, exceptional on-road response and optimized off-road handling. Two stiff extra-wide steel belts enable stability, while four wide multi-angled grooves enable superb water, mud and snow evacuation. Biting block edges provide additional, unparalleled traction and control. The WILDPEAK A/T is available in 15-inch to 24-inch applications, up to 37" overall diameter.



TIRE HIGHLIGHTS

50K Limited Mileage Warranty**

H, Q, S, & T Speed Ratings

15" – 24" Rim

M+S Rated



** NO MILEAGE WARRANTY ON 33" AND ABOVE OVERALL DIAMETERS.



LIMITED MILEAGE WARRANTY: 50,000 (FOR SIZES LESS THAN 33" OVERALL DIAMETER)

| Wheel Dia. | Pattern | Actual Size | Flotation Equivalent | Load Index / Speed Rating | Load Range | Item Number | Measuring Rim Width (in) | Approved Rim Width Range (in) | Overall Diameter (in) | Section Width (in) | Revolutions Per Mile | Tread Width (in) | Tread Depth (/32") | Tire Weight (lbs.) | Max PSI (Cold) | Max Load (lbs.) | UTQG |
|------------|---------|-----------------|----------------------|---------------------------|------------|-------------|--------------------------|-------------------------------|-----------------------|--------------------|----------------------|------------------|--------------------|--------------------|----------------|-----------------|---------|
| 15" | A/T01 | 30X9.50R15LT † | | 104S | C/6 | 28440512 | 7.5 | 6.0 - 8.5 | 29.6 | 9.7 | 714 | 7.5 | 16 | 39 | 50 | 1985 | |
| | A/T01 | 31X10.50R15LT † | | 109S | C/6 | 28440514 | 8.5 | 7.0 - 9.0 | 30.5 | 10.7 | 693 | 8.3 | 17 | 43 | 50 | 2270 | |
| | A/T01 | 32X11.50R15LT † | | 113S | C/6 | 28440510 | 9.0 | 8.0 - 10.0 | 31.5 | 11.6 | 671 | 9.1 | 17 | 47 | 50 | 2535 | |
| | A/T01 | 33x12.50R15LT | | 108S | C/6 | 28440518 | 10.0 | 8.5 - 11.0 | 32.6 | 12.8 | 651 | 9.9 | 18 | 54 | 35 | 2205 | |
| | A/T01 | 35X12.50R15LT | | 113S | C/6 | 28440920 | 10.0 | 8.5 - 11.0 | 34.5 | 12.9 | 618 | 9.3 | 18 | 72 | 35 | 2535 | |
| | A/T01 | 235/75R15 | 29x9.00R15 | | 105S | | 28440529 | 6.5 | 6.0 - 8.0 | 28.9 | 9.4 | 734 | 6.7 | 12 | 35 | 44 | 2039 |
| 16" | A/T01 | LT225/75R16 | 29x9.00R16 | 110/107Q | D/8 | 28446627 | 6.0 | 6.0 - 7.0 | 29.4 | 8.7 | 709 | 7.0 | 15 | 39 | 65 | 2335 | |
| | A/T01 | 245/70R16 † | 30X9.50R16 | 107S | | 28440686 | 7.0 | 6.5 - 8.0 | 29.5 | 9.8 | 683 | 7.6 | 12 | 38 | 44 | 2149 | 500-A-B |
| | A/T02 | LT245/70R16 † | 29x9.50R16 | 113/110Q | D/8 | 28466624 | 7.0 | 6.5 - 7.5 | 29.5 | 9.9 | 707 | 7.7 | 16 | 45 | 65 | 2535 | |
| | A/T02 | LT245/75R16 † | 31X9.50R16 | 120/116Q | E/10 | 28466492 | 7.0 | 6.5 - 8.0 | | | | | | | 80 | 3042 | |
| | A/T01 | 255/65R16 | 29x10.00R16 | 109S | | 28440642 | 7.5 | 7.0 - 9.0 | 29.1 | 10.2 | 733 | 8.1 | 13 | 38 | 44 | 2271 | 500-A-B |
| | A/T01 | 265/70R16 | 31x10.50R16 | 112T | | 28444606 | 8.0 | 7.0 - 9.0 | 30.5 | 10.9 | 694 | 8.2 | 13 | 42 | 44 | 2469 | 500-A-B |
| | A/T02 | LT265/70R16 † | 30X10.50R16 | 117/114Q | D/8 | 28466638 | 8.0 | 7.0 - 8.5 | 30.7 | 10.8 | 680 | 8.3 | 16 | 50 | 65 | 2835 | |
| | A/T02 | LT265/75R16 † | 31X10.50R16 | 123/120Q | E/10 | 28466639 | 7.5 | 7.0 - 8.0 | | | | | | | 80 | 3415 | |
| | A/T02 | LT285/75R16 † | 33X11.00R16 | 122/119Q | D/8 | 28466611 | 8.0 | 7.5 - 9.0 | | | | | | | 65 | 3305 | |
| | A/T02 | LT305/70R16 | 32x12.00R16 | 124/121S | E/10 | 28460641 | 9.0 | 8.0 - 9.5 | 32.7 | 12.4 | 638 | 9.6 | 18 | 60 | 65 | 3525 | |
| | A/T01 | LT315/75R16 | 35x12.50R16 | 121/118S | D/8 | 28440934 | 9.5 | 8.0 - 11.0 | 34.4 | 12.7 | 608 | 9.5 | 16 | 77 | 50 | 3195 | |
| | A/T01 | LT325/80R16 | 36x13.00R16 | 124/121S | D/8 | 28440935 | 9.0 | 8.5 - 11.0 | 36.3 | 13.1 | 578 | 9.2 | 17 | 80 | 50 | 3525 | |

(†) Denotes Outlined White Sidewall Letters, (*) Denotes XL (Extra Load).

Never mix tires of different size or construction and or type on an axle. (Except for temporary use as a spare tire.) Always refer to vehicle owners manual for proper tire fitment.

More sizes on the next page

NO UTQG RATING FOR LT SIZES



- VARIABLE BLOCK SHOULDER DESIGN**
reduces tire noise while maintaining an aggressive look.
- LONG SWEEPING SIPES**
provide a multitude of biting edges for additional traction.
- FOUR WIDE AGGRESSIVE MULTI-ANGLED GROOVES**
allow for excellent water, mud and snow evacuation while aggressive biting block edges provide unparalleled all-terrain performance.
- SQUARE SHOULDER PROFILE**
features an aggressive stance and exceptional snow and mud traction.
- OPEN SHOULDER GROOVES**
effectively disperse water and debris in all weather conditions for both on and off-road.

WILDPEAK A/T

LIMITED MILEAGE WARRANTY: 50,000 (FOR SIZES LESS THAN 33" OVERALL DIAMETER)

| Wheel Dia. | Pattern | Actual Size | Flotation Equivalent | Load Index / Speed Rating | Load Range | Item Number | Measuring Rim Width (in) | Approved Rim Width Range (in) | Overall Diameter (in) | Section Width (in) | Revolutions Per Mile | Tread Width (in) | Tread Depth (/32") | Tire Weight (lbs.) | Max PSI (Cold) | Max Load (lbs.) | UTQG |
|------------|-------------|---------------|----------------------|---------------------------|------------|-------------|--------------------------|-------------------------------|-----------------------|--------------------|----------------------|------------------|--------------------|--------------------|----------------|-----------------|---------|
| 17" | A/T02 | 33X12.50R17LT | | 114S | D/8 | 28460710 | 10.0 | 8.5 - 11 | 32.5 | 12.5 | 648 | 10.1 | 17 | 63 | 50 | 2600 | |
| | A/T01 | 35X12.50R17LT | | 119S | D/8 | 28440730 | 10.0 | 8.5 - 11.0 | 34.5 | 13.1 | 605 | 9.6 | 16 | 74 | 50 | 3000 | |
| | A/T01 | 37X12.50R17LT | | 124S | D/8 | 28440921 | 10.0 | 8.5 - 11.0 | 36.6 | 13.0 | 579 | 9.3 | 18 | 81 | 50 | 3525 | |
| | A/T01 | 235/65R17 | 29x9.00R17 | 104T | | 28444790 | 7.0 | 6.5 - 8.5 | 29.1 | 9.4 | 718 | 7.3 | 13 | 36 | 44 | 1984 | 500-A-B |
| | A/T01 | P235/70R17* | 30x9.00R17 | 108S | | 28440613 | 7.0 | 6.0 - 8.0 | 30.0 | 9.5 | 703 | 7.3 | 12 | 36 | 50 | 2205 | 500-A-B |
| | A/T01 | 245/65R17 † | 29x9.50R17 | 107S | | 28440768 | 7.0 | 7.0 - 8.5 | 29.6 | 9.5 | 718 | 7.8 | 13 | 37 | 44 | 2149 | 500-A-B |
| | A/T02 | LT245/70R17 | 30x9.50R17 | 119/116Q | E/10 | 28466718 | 7.0 | 6.5 - 8.0 | 30.6 | 9.6 | 680 | 7.7 | 16 | 50 | 80 | 3000 | |
| | A/T02 | LT245/75R17 | 31x9.50R17 | 121/118Q | E/10 | 28466711 | 7.0 | 6.5 - 7.5 | 31.5 | 9.8 | 661 | 7.5 | 16 | 50 | 80 | 3195 | |
| | A/T01 | 255/65R17 † | 30x10.00R17 | 110S | | 28440713 | 7.5 | 7.0 - 9.0 | 30.2 | 10.1 | 706 | 8.1 | 13 | 40 | 44 | 2337 | 500-A-B |
| | A/T01 | 255/70R17 † | 31x10.00R17 | 112S | | 28440769 | 7.5 | 6.5 - 8.5 | 31.1 | 10.0 | 679 | 8.0 | 13 | 41 | 44 | 2469 | 500-A-B |
| | A/T01 | 265/65R17 | 30X10.50R17 | 112S | | 28440721 | 8.0 | 7.5 - 9.5 | 30.6 | 10.6 | 696 | 8.4 | 13 | 41 | 44 | 2469 | 500-A-B |
| | A/T01 | P265/70R17 | 32X10.50R17 | 113S | | 28440701 | 8.0 | 7.0 - 9.0 | 31.6 | 10.9 | 670 | 8.2 | 13 | 43 | 44 | 2535 | 500-A-B |
| | A/T02 | LT265/70R17 | 31X10.50R17 | 121/118S | E/10 | 28460993 | 8.0 | 7.0 - 8.5 | | | | | | | 80 | 3195 | |
| | A/T01 | LT275/70R17 | 32X11.00R17 | 114/110S | C/6 | 28440907 | 8.0 | 7.0 - 8.5 | 32.6 | 10.9 | 640 | 8.3 | 16 | 53 | 50 | 2600 | |
| | A/T02 | LT285/70R17 | 33X11.50R17 | 121/118S | D/8 | 28460719 | 8.5 | 7.5 - 9.0 | 32.7 | 11.6 | 639 | 9.0 | 17 | 55 | 65 | 3195 | |
| | A/T01 | LT295/70R17 | 33x11.50R17 | 121/118S | E/10 | 28440936 | 8.5 | 7.5 - 10.0 | 33.1 | 11.8 | 630 | 9.0 | 16 | 74 | 85 | 3195 | |
| | A/T02 | LT305/65R17 | 33X12.00R17 | 121/118S | E/10 | 28460720 | 9.0 | 8.5 - 11 | 32.6 | 12.3 | 644 | 9.7 | 17 | 60 | 65 | 3195 | |
| | A/T01 | LT315/70R17 | 34X12.50R17 | 121/118Q | D/8 | 28446932 | 9.5 | 8.0 - 11.0 | 34.3 | 12.5 | 610 | 9.6 | 17 | 78 | 50 | 3195 | |
| | A/T01 | LT325/70R17 | 35X13.00R17 | 121S | D/8 | 28440933 | 9.5 | 8.5 - 11.0 | 34.8 | 13.1 | 601 | 9.9 | 17 | 82 | 50 | 3195 | |
| | 18" | A/T01 | 35X12.50R18LT | | 118Q | D/8 | 28446830 | 10.0 | 8.5 - 11.0 | 34.4 | 13.1 | 609 | 9.8 | 16 | 77 | 50 | 2910 |
| A/T01 | | 37X13.50R18LT | | 124S | D/8 | 28440922 | 11.0 | 8.5 - 11.0 | 36.5 | 14.4 | 579 | 10.6 | 18 | 87 | 50 | 3525 | |
| A/T01 | | P265/60R18 | 30X10.50R18 | 109T | | 28444644 | 8.0 | 7.5 - 9.5 | 30.6 | 10.7 | 694 | 8.3 | 13 | 42 | 44 | 2271 | 500-A-B |
| A/T01 | | P265/65R18 | 32X10.50R18 | 112S | | 28440621 | 8.0 | 7.5 - 9.5 | 31.5 | 10.8 | 677 | 8.3 | 13 | 44 | 44 | 2469 | 500-A-B |
| A/T01 | | 265/70R18 † | 33X10.50R18 | 116S | | 28440809 | 8.0 | 7.0 - 9.0 | 32.6 | 10.8 | 648 | 8.3 | 13 | 51 | 44 | 2756 | 500-A-B |
| A/T02 | | LT275/65R18 † | 32X11.00R18 | 123/120Q | E/10 | 28466803 | 8.0 | 7.5 - 9.0 | 32.1 | 10.8 | 651 | 8.7 | 16 | 56 | 80 | 3415 | |
| A/T01 | | LT275/70R18 | 33X11.00R18 | 125/122S | E/10 | 28440703 | 8.0 | 7.0 - 8.5 | 33.2 | 11.0 | 629 | 8.6 | 16 | 66 | 80 | 3640 | |
| AT01 | | 285/60R18* | | 120H | | 28441856 | 8.5 | 8.0 - 10.0 | 31.5 | 11.4 | 675 | 9.0 | 11 | 45 | 50 | 3086 | 500-A-A |
| A/T02 | | LT285/65R18 † | 32x11.00R18LT | 121/118S | D/8 | 28460804 | 8.5 | 8.0 - 10.0 | 32.6 | 11.6 | 642 | 9.1 | 16 | 59 | 65 | 3195 | |
| A/T01 | | LT305/65R18 | 33x12.00R18LT | 124/121S | E/10 | 28440930 | 9.0 | 8.5 - 11.0 | 33.4 | 12.3 | 627 | 9.7 | 16 | 72 | 65 | 3525 | |
| A/T01 | | LT325/60R18 | 33X13.00R18 | 124/121S | E/10 | 28440927 | 9.5 | 9.0 - 12.0 | 33.2 | 12.8 | 630 | 10.6 | 17 | 77 | 65 | 3525 | |
| A/T01 | LT325/65R18 | 35X13.00R18 | 127/124S | E/10 | 28440931 | 9.5 | 9.0 - 12.0 | 34.4 | 13.0 | 606 | 10.3 | 16 | 80 | 65 | 3860 | | |

(†) Denotes Outlined White Sidewall Letters, (*) Denotes XL (Extra Load).

Never mix tires of different size or construction and or type on an axle. (Except for temporary use as a spare tire.)

Always refer to vehicle owners manual for proper tire fitment.

NO UTQG RATING FOR LT SIZES

LIMITED MILEAGE WARRANTY: 50,000 (FOR SIZES LESS THAN 33" OVERALL DIAMETER)

| Wheel Dia. | Pattern | Actual Size | Flotation Equivalent | Load Index / Speed Rating | Load Range | Item Number | Measuring Rim Width (in) | Approved Rim Width Range (in) | Overall Diameter (in) | Section Width (in) | Revolutions Per Mile | Tread Width (in) | Tread Depth (/32") | Tire Weight (lbs.) | Max PSI (Cold) | Max Load (lbs.) | UTQG | |
|------------|---------|---------------|----------------------|---------------------------|------------|-------------|--------------------------|-------------------------------|-----------------------|--------------------|----------------------|------------------|--------------------|--------------------|----------------|-----------------|---------|--|
| 20" | A/T01 | 33X12.50R20LT | | 114S | E/10 | 28440906 | 10.0 | 8.5 - 11.0 | 32.6 | 12.4 | 640 | 10.4 | 16 | 60 | 65 | 2600 | | |
| | A/T01 | 35X12.50R20LT | | 121Q | E/10 | 28446905 | 10.0 | 8.5 - 11.0 | 34.5 | 12.7 | 608 | 10.0 | 17 | 73 | 65 | 3195 | | |
| | A/T01 | P275/55R20 | 32X11.00R20 | 111T | | 28444643 | 8.5 | 7.5 - 9.5 | 31.9 | 11.0 | 663 | 9.4 | 13 | 45 | 44 | 2403 | 500-A-B | |
| | A/T01 | 275/60R20 | 33X10.50R20 | 115S | | 28440003 | 8.0 | 7.5 - 9.5 | 33.1 | 10.9 | 640 | 8.8 | 13 | 46 | 44 | 2679 | 500-A-B | |
| | A/T01 | LT275/65R20 | 34X11.00R20 | 126/123S | E/10 | 28440025 | 10.0 | 8.5 - 11.0 | 34.0 | 10.8 | 613 | 8.5 | 16 | 66 | 80 | 3750 | | |
| | A/T01 | 285/50R20* | 31x11.00R20 | 116T | | 28444020 | 9.0 | 8.0 - 10.0 | 31.3 | 11.3 | 674 | 9.3 | 13 | 46 | 50 | 2756 | 500-A-B | |
| | A/T01 | LT305/55R20 | 33x12.00R20 | 121/118S | E/10 | 28440926 | 9.5 | 8.5 - 11.0 | 33.1 | 12.3 | 628 | 10.1 | 16 | 68 | 65 | 3195 | | |
| | A/T01 | LT325/60R20 | 35X12.50R20 | 121/118S | D/8 | 28440928 | 9.5 | 9.0 - 12.0 | 35.2 | 13.1 | 594 | 10.6 | 17 | 81 | 50 | 3195 | | |
| | A/T01 | LT355/60R20 | 37X14.00R20 | 125S | D/8 | 28440929 | 10.0 | 10.0 - 12.0 | 36.6 | 14.2 | 572 | 11.6 | 17 | 93 | 50 | 3640 | | |
| | 22" | A/T01 | 37X13.50R22LT | | 123S | E/10 | 28440923 | 11.0 | 8.5 - 11.0 | 36.6 | 13.9 | 570 | 11.4 | 16 | 88 | 65 | 3415 | |
| | | A/T01 | LT325/50R22 | 35X13.00R22 | 122S | E/10 | 28440925 | 10.0 | 9.0 - 12.0 | 34.7 | 13.0 | 598 | 11.2 | 17 | 79 | 65 | 3305 | |
| 24" | A/T01 | 37X13.50R24LT | | 120S | E/10 | 28440924 | 11.0 | 8.5 - 11.0 | 36.6 | 13.5 | 567 | 11.9 | 17 | 89 | 65 | 3085 | | |

(†) Denotes Outlined White Sidewall Letters, (*) Denotes XL (Extra Load).

Never mix tires of different size or construction and or type on an axle. (Except for temporary use as a spare tire.)

Always refer to vehicle owners manual for proper tire fitment.

NO UTQG RATING FOR LT SIZES