

ZIEX S/TZ05

ALL-SEASON PERFORMANCE AND COMFORT FOR LUXURY SUVs AND LIGHT TRUCKS

The **ZIEX S/TZ05** features the latest in tread compound and construction technology designed specifically for SUV and 1/2 ton sport truck applications. With an advanced M+S all-season, non-directional tread design, the S/TZ05 allows rotation in all directions, optimizing tread life. With double taper cut tread blocks and staggered shoulder lug grooves, the S/TZ05 is a smooth, quiet and dynamic tire. Available from 16-inch to 24-inch applications, this tire covers many of today's popular SUV and LT wheel fitments. Whether you're cruising through the city or driving on the open highway, the S/TZ05 provides unparalleled performance and comfort.



TIRE HIGHLIGHTS

50K Limited Mileage Warranty

S, T, H & V Speed Ratings

16" – 24" Rim

M+S Rated



LIMITED MILEAGE WARRANTY: 50,000

Wheel Dia.	Size	Extra Load	Load Index/Speed Rating	Item Number	Measuring Rim Width (in)	Approved Rim Width Range (in)	Overall Diameter (in)	Section Width (in)	Revolutions Per Mile	Tread Width (in)	Tread Depth (/32")	Tire Weight (lbs.)	Max PSI (Cold)	Max Load	UTQG
16"	215/70R16		100H							COMING SOON					460-A-A
	235/70R16		106T							COMING SOON					460-A-A
	245/70R16		107T							COMING SOON					460-A-A
	245/75R16		111T							COMING SOON					460-A-A
	255/70R16		111S							COMING SOON					460-A-A
	265/70R16		112T							COMING SOON					460-A-A
	265/75R16		116T							COMING SOON					460-A-A
17"	245/65R17		107T							COMING SOON					460-A-A
	265/65R17		112T							COMING SOON					460-A-A
	265/70R17		115S							COMING SOON					460-A-A
18"	235/60R18	XL	107V	28052816	7.0	6.5 - 8.5	29.1	9.3	726	7.6	10	33	50	2149	460-A-A
	245/60R18		105H							COMING SOON					460-A-A
	255/55R18	XL	109V	28052845	8.0	7.0 - 9.0	29.0	10.4	728	8.7	10	38	50	2271	460-A-A
	255/65R18		111S							COMING SOON					460-A-A
	265/60R18		110V							COMING SOON					460-A-A
	275/65R18		116T							COMING SOON					460-A-A
19"	235/55R19	XL	105V							COMING SOON					460-A-A
	245/55R19		103H	28051814	7.5	7.0 - 8.5	29.6	9.9	711	7.9	13	35	51	1929	460-A-A
	255/50R19	XL	107V							COMING SOON					460-A-A
	255/60R19		109H	28051813	7.5	7.0 - 9.0	31.1	10.2	680	8.0	12	37	51	2271	460-A-A

More sizes on the next page



FIVE RIB SYMMETRIC TREAD DESIGN
provides increased high speed stability and the freedom of tire rotation, enhancing tread life.

WIDE SHOULDER BLOCKS
increase tread stiffness allowing for maximum wet and dry handling and stability.

WIDE AND NARROW SHOULDER LUG GROOVES
designed to optimize noise reduction.

SOLID CENTER RIB
offers excellent handling response especially in high speed conditions.

ZIEX S/TZ05



LIMITED MILEAGE WARRANTY: 50,000

Wheel Dia.	Size	Extra Load	Load Index/Speed Rating	Item Number	Measuring Rim Width (in)	Approved Rim Width Range (in)	Overall Diameter (in)	Section Width (in)	Revolutions Per Mile	Tread Width (in)	Tread Depth (/32")	Tire Weight (lbs.)	Max PSI (Cold)	Max Load	UTQG
20"	245/50R20		102H	28051026	7.5	7.0 - 8.5	29.7	9.9	708	8.2	13	36	51	1874	460-A-A
	245/60R20		107H						COMING SOON						460-A-A
	255/50R20	XL	109H	28051946	8.0	7.0 - 9.0	30.2	10.2	697	8.5	13	39	50	2271	460-A-A
	265/50R20	XL	111H	28051011	8.5	7.5 - 9.5	30.5	10.7	690	8.9	14	40	50	2403	460-A-A
	275/40R20	XL	106H	28051947	9.5	9.5 - 11.0	28.6	10.9	727	9.5	13	37	50	2094	460-A-A
	275/45R20	XL	110H	28051016	9.0	8.5 - 10.5	29.7	10.6	701	9.1	14	38	50	2337	460-A-A
	275/50R20		109H						COMING SOON						460-A-A
	275/55R20	XL	117H	28051021	8.5	7.5 - 9.5	31.9	11.0	663	8.9	14	45	50	2833	460-A-A
	275/60R20	-	115H	28051003	8.0	7.5 - 9.5	33.0	11.0	641	8.7	13	46	51	2670	460-A-A
	285/50R20	XL	116V	28052020	9.0	8.0 - 10.0	31.3	11.6	674	9.6	10		50	2756	460-A-A
	295/45R20	XL	114H	28051018	10.0	9.5 - 11.0	30.3	11.7	688	9.8	14	42	50	2601	460-A-A
	305/50R20	XL	120H	28051015	9.5	8.5 - 11.0	31.9	12.4	662	10.2	14	49	50	3086	460-A-A

NO UTQG RATING FOR LT SIZES

LIMITED MILEAGE WARRANTY: 50,000

Wheel Dia.	Size	Extra Load	Load Index/Speed Rating	Item Number	Measuring Rim Width (in)	Approved Rim Width Range (in)	Overall Diameter (in)	Section Width (in)	Revolutions Per Mile	Tread Width (in)	Tread Depth (/32")	Tire Weight (lbs.)	Max PSI (Cold)	Max Load	UTQG
22"	265/35R22	XL	102H	28051218	9.5	9.0 - 10.5	29.5	10.5	701	9.3	13	37	50	1874	460-A-A
	265/40R22	XL	106H	28051217	9.5	9.0 - 10.5	30.3	10.6	683	9.2	13	37	50	2094	460-A-A
	285/40R22	XL	110H	28051216	10.0	9.5 - 11.0	31.0	11.4	670	9.9	14	42	50	2337	460-A-A
	285/45R22	XL	114H	28051219	9.5	9.0 - 10.5	32.1	11.0	648	9.4	14	43	50	2601	460-A-A
	305/40R22	XL	114H	28051220	11.0	10.0 - 12.0	31.6	12.3	658	10.6	14	45	50	2601	460-A-A
	305/45R22	XL	118H	28051215	10.0	9.5 - 11.5	32.7	12.0	637	10.1	14	48	50	2910	460-A-A
	295/35R24	XL	110H	28051401	10.5	10.0 - 11.5	32.0	11.6	646	10.3	13	45	50	2337	460-A-A
305/35R24	XL	112H	28051402	11.0	10.0 - 12.0	32.4	12.0	639	10.6	13	45	50	2469	460-A-A	

NO UTQG RATING FOR LT SIZES