

7021BFD

Journeyman Flex® Aluminum 2D Climbing Non-belted Full Body Harness

Features:

- Features integral padded shoulder yoke and hip-toseat leg pads to provide advanced breathable user comfort
- Proprietary dorsal attachment sleeve supports effortless addition of personal SRLs.
- Exclusive aluminum camlock torso adjusters provide simple and secure upper-body fit
- Features lightweight forged aluminum alloy dorsal D-ring and steel sternal D-ring
- Tongue buckle legs are uniquely equipped with 9 grommeted adjustment positions for a wider range of fit
- Quick-connect chest buckle features visual indicator showing positive connection
- Includes fully adjustable suspension trauma relief system
- Meets OSHA 1926.502 and 1910.66 Regulations

Material 9	Material Specifications			
Webbing	Polyester; 5,000 lb min. static strength			
D-rings	Aluminum Alloy and Plated Alloy Steel; 5,000 lb min. static strength			
Buckles and Adjusters	Aluminum alloy and plated alloy steel; 3,372 lb min. static strength			

Performance Specifications						
Static Strength	3,600 lb min.					
ANSI User	130 to 310 lb					
Capacity	max.					
OSHA User	130 to 425 lb					
Capacity	max.					

Compliant With:				
OSHA	1926.502 and 1910.66			
CSA	Z259.10-2018			

Sizes & Part Numbers						
7021BFDS -	7021BFDM -	7021BFDL -	7021BFDXL -	7021BFD2X -	7021BFD3X -	
Small	Medium	Large	XL	2X	3X	