

## INSTALLATION INSTRUCTIONS

**PART No.** FB23008, FB23009

**Jeep® JK Wrangler  
Rocker Guards – 2DR & 4DR**



**FB23008 – 2DR**



**FB23009 – 4DR**



**FB23009 shown**

### REQUIRED TOOLS

16mm Socket &  
Extension

### KIT CONTAINS

Rocker Guard – Left  
Rocker Guard – Right

### QTY

1  
1

### 1) REMOVE FACTORY RAILS/GUARDS

Remove the factory equipment if equipped.

### 2) IDENTIFY DRIVER/PASSENGER

**4 Door** - The front bracket's tube is welded in the center, while the rear is welded to the side:



**2 Door** – The front bracket's tube is welded lower than the rear:



### 3) INSTALL ROCKER GUARDS

Using a 16mm socket, remove the nuts on either side of the body mount bolts. Complete this step on both the front and rear brackets.



Identify the driver and passenger side. The front of the rocker guard is welded in the center of the bracket as seen below. The rears are welded off-center of the bracket.



## **INSTALLATION INSTRUCTIONS**

**PART No.** FB23008, FB23009

**Jeep® JK Wrangler  
Rocker Guards – 2DR & 4DR**



### **NOTE**

The use of a floor jack to lift the rocker guard into position can help if you do not have someone to help hold it in place.

Install the rocker guard by lifting it into position over the body studs. Reusing the OEM nuts, secure the rocker guard in place. Torque to factory specifications.



**4) HIT THE TRAILS AND ENJOY YOUR NEW FISHBONE OFFROAD ROCKER GUARDS!**