

2017 PRODUCT



PASSENGER & LIGHT TRUCK



GENERAL TIRE

2016 PRODUCT LINE OVERVIEW

G-MAX™ AS-03



Dominant ultra-high performance all-season tire delivers precise response in dry and wet conditions with excellent light snow grip.

AltiMAX™ RT⁴³



The all-season touring tire designed for a quiet, comfortable ride, all-season traction and enhanced with even treadwear and extended treadlife.

GRABBER™ UHP



Bold ultra-high performance all-season light truck, crossover and SUV tire designed for excellent handling and traction in both wet and dry conditions.

GRABBER™ HTS⁶⁰



The tough highway terrain all-season tire that provides the perfect synergy of comfort, durability and performance for light trucks, SUVs and crossovers.

GRABBER™ X³



General Tire's bold Mud-Terrain tire, delivers extreme off-road performance in mud, dirt and rocky terrain, with 3-ply durability, balanced with impressive on-road performance.

GRABBER™ AT²



This tough, all-terrain tire is designed with an aggressive, self-cleaning tread pattern that provides off-road traction, durability and impressive paved road performance.

GRABBER™ MT



Born from competition, this high void mud-terrain tire provides the ultimate in off-road grip and durability, with a balance of on-road drivability.

AltiMAX™ ARCTIC



Unique grooves and sipes combine with a modern compound to offer outstanding performance in winter conditions.

GRABBER™ ARCTIC



Studdable winter tire with outstanding low temperature traction in snow, ice and wet conditions that is durable, robust and comfortable for large SUVs and pickup trucks.

GRABBER™ ARCTIC LT



Innovative light truck studdable winter tire with outstanding low temperature traction in snow, ice, and wet conditions.



BORN FROM COMPETITION AND ADAPTED FOR THE HIGHWAY

FEATURE:

ULTRA-HIGH STRENGTH STEEL BELTS, MICRO-FIBER CASING REINFORCEMENTS, AND A BROAD TIRE CONTOUR

BENEFIT:

ENHANCED STRENGTH AND DURABILITY WITH EVEN TREADWEAR FOR LONGER MILEAGE AND CONFIDENCE IN CHALLENGING CONDITIONS

AVAILABLE IN:

GRABBER™ HTS⁶⁰, GRABBER™ AT², GRABBER™ X³,
GRABBER™ ARCTIC LT, GRABBER™ ARCTIC

3-D SIPE TECHNOLOGY

FEATURE:

INTERLOCKING TREAD BLOCKS

- The magnified image shows an open view of the sipe with the raised interlocking element (top) and recessed element (below).
- When interlocked the tread blocks work together to improve handling and reduce heat for increased treadlife.

AVAILABLE IN:

G-MAX™ AS-03, ALTiMAX™ RT⁴³





Consists of replacement tire monitor technology (RTM®) and visual alignment indicators (VAI®) to aid the consumer in detecting tire wear.

RTM® TECHNOLOGY

- The replacement tire monitor (RTM®) is an indicator that is clearly visible on the tire's center rib.
- When the tire wears to 2/32 of tread depth the indicator transforms to read "replace tire" alerting the driver a tire change is needed.



AVAILABLE IN:
G-MAX™ AS-03, ALTiMAX™ RT⁴³

VAI® TECHNOLOGY

- Vehicle misalignment can adversely affect tire wear. The Visual Alignment Indicators (VAI®) visually alert the driver to vehicle misalignment allowing a correction before treadlife is compromised.
- VAI® consists of short sipes on both shoulders of the tire. When misalignment occurs, the sipes on one shoulder will wear off before the other, alerting the driver to an alignment condition.

AVAILABLE IN:
G-MAX™ AS-03, ALTiMAX™ RT⁴³



	RIM DIAMETER	SERIES	SIZE	G-MAX™ AS-03 PAGE 14	ALTIMAX™ RT43 PAGE 18	GRABBER™ UHP PAGE 22	GRABBER™ HTS60 PAGE 24	GRABBER™ AT2 PAGE 28	GRABBER™ X3 PAGE 32	GRABBER™ MT PAGE 34	ALTIMAX™ ARCTIC PAGE 36	GRABBER™ ARCTIC PAGE 40	GRABBER™ ARCTIC LT PAGE 42	AMERI TRAC™ PAGE 44	AMERI TRAC™ TR PAGE 44	GRABBER™ APT PAGE 44
13	70	175/70R13		•						•						
14	70	175/70R14		•												
		185/70R14		•						•						
		195/70R14		•												
		205/70R14		•												
		215/70R14		•												
	65	175/65R14		•						•						
		185/65R14		•						•						
	60	185/60R14		•						•						
		195/60R14		•												
	8.5	27X8.50R14LT					•									
15	75	205/75R15					•									
		215/75R15					•									
		LT235/75R15					•		•							
		265/75R15				•										
	70	205/70R15		•						•						
		215/70R15		•						•						
		225/70R15		•			•			•						
		235/70R15		•												
		255/70R15				•	•									
		265/70R15					•									
	65	175/65R15		•												
		185/65R15		•						•						
		195/65R15		•						•						
		205/65R15		•						•						
		215/65R15		•						•						
	60	185/60R15		•						•						
		195/60R15		•						•						
		205/60R15		•						•						
		215/60R15		•						•						
	55	195/55R15	•	•						•						
		33X12.50R15LT					•		•							
	12.5	35X12.50R15LT					•	•								
		33X10.50R15LT						•								
	10.5	31X10.50R15LT				•	•	•	•							
16	85	LT235/85R16				•	•									
	75	225/75R16				•	•									
		LT225/75R16										•				
		235/75R16				•				•						
		245/75R16				•				•						
		LT245/75R16				•	•					•				

New size for 2016

RIM DIAMETER	SERIES	SIZE	G-MAX™ AS-03 PAGE 14	ALTIMAX™ RT43 PAGE 18	GRABBER™ UHP PAGE 22	GRABBER™ HTS60 PAGE 24	GRABBER™ AT2 PAGE 28	GRABBER™ X3 PAGE 32	GRABBER™ MT PAGE 34	ALTIMAX™ ARCTIC PAGE 36	GRABBER™ ARCTIC PAGE 40	GRABBER™ ARCTIC LT PAGE 42	AMERITRAC™ PAGE 44	AMERITRAC™ TR PAGE 44	GRABBER™ APT PAGE 44
16	75	265/75R16													
		LT265/75R16													
		LT285/75R16													
		LT295/75R16													
		LT315/75R16													
	70	205/70R16													
		215/70R16													
		225/70R16													
		235/70R16													
		245/70R16													
		255/70R16													
		P255/70R16													
		265/70R16													
		LT305/70R16													
	65	205/65R16													
		215/65R16													
		225/65R16													
		235/65R16													
		255/65R16													
	60	205/60R16													
		215/60R16													
		225/60R16													
		235/60R16													
	55	195/55R16													
		205/55R16													
		215/55R16													
		225/55R16													
	50	195/50R16													
		205/50R16													
		225/50R16													
	45	205/45R16													
17	80	LT235/80R17													
	75	LT245/75R17													
		LT255/75R17													
	70	235/70R17													
		P245/70R17													
		245/70R17													
		LT245/70R17													
		P255/70R17													

New size for 2016

RIM DIAMETER	SERIES	SIZE	G-MAX™ AS-03 PAGE 14	ALTIMAX™ RT43 PAGE 18	GRABBER™ UHP PAGE 22	GRABBER™ HTS60 PAGE 24	GRABBER™ AT2 PAGE 28	GRABBER™ X3 PAGE 32	GRABBER™ MT PAGE 34	ALTIMAX™ ARCTIC PAGE 36	GRABBER™ ARCTIC PAGE 40	GRABBER™ ARCTIC LT PAGE 42	AMERI TRAC™ PAGE 44	AMERI TRAC™ TR PAGE 44	GRABBER™ APT PAGE 44
17	70	255/70R17				•									
		P265/70R17											•		
		265/70R17			•	•				•					
		LT265/70R17			•	•					•				
		LT285/70R17				•	•								
		LT295/70R17					•								
		LT315/70R17				•	•								
	65	215/65R17	•						•						
		225/65R17	•						•						
		235/65R17	•		•				•						
		245/65R17			•					•					
		255/65R17			•	•									
		265/65R17			•	•				•					
	60	215/60R17	•						•						
		225/60R17	•						•						
		235/60R17	•												
		255/60R17		•											
		275/60R17			•										
	55	215/55R17	•	•					•						
		225/55R17	•	•					•						
		235/55R17	•	•					•						
		275/55R17			•										
	50	205/50R17	•	•					•						
		215/50R17	•	•					•						
		225/50R17	•	•											
		235/50R17	•												
		245/50R17	•												
	45	205/45R17	•	•											
		215/45R17	•	•					•						
		225/45R17	•	•					•						
		235/45R17	•	•					•						
		245/45R17	•	•											
	40	205/40R17	•												
		245/40R17	•												
		255/40R17	•												
	12.5	33X12.50R17LT				•	•								
		35X12.50R17LT				•	•								
		37X12.50R17LT					•								

New size for 2016

RIM DIAMETER	SERIES	SIZE	G-MAX™ AS-03 PAGE 14	ALTIMAX™ RT43 PAGE 18	GRABBER™ UHP PAGE 22	GRABBER™ HTS60 PAGE 24	GRABBER™ AT2 PAGE 28	GRABBER™ X3 PAGE 32	GRABBER™ MT PAGE 34	ALTIMAX™ ARCTIC PAGE 36	GRABBER™ ARCTIC PAGE 40	GRABBER™ ARCTIC LT PAGE 42	AMERITRAC™ PAGE 44	AMERITRAC™ TR PAGE 44	GRABBER™ APT PAGE 44
18	70	255/70R18													
		265/70R18													
		LT265/70R18													
		P275/70R18													
		LT275/70R18													
		LT295/70R18													
	65	235/65R18													
		255/65R18													
		265/65R18													
		275/65R18													
		LT275/65R18													
	60	225/60R18													
		235/60R18													
		245/60R18													
		255/60R18													
		265/60R18													
		LT285/60R18													
	55	215/55R18													
		225/55R18													
		235/55R18													
		255/55R18													
	50	225/50R18													
		235/50R18													
	45	215/45R18													
		225/45R18													
		235/45R18													
		245/45R18													
		255/45R18													
	40	215/40R18													
		225/40R18													
		235/40R18													
		245/40R18													
		255/40R18													
		275/40R18													
		255/35R18													
		265/35R18													
		275/35R18													
	12.5	33X12.50R18LT													
		35X12.50R18LT													
		37X12.50R18LT													

New size for 2016

	RIM DIAMETER	SERIES	SIZE	G-MAX™ AS-03 PAGE 14	ALTIMAX™ RT43 PAGE 18	GRABBER™ UHP PAGE 22	GRABBER™ HTS60 PAGE 24	GRABBER™ AT2 PAGE 28	GRABBER™ X3 PAGE 32	GRABBER™ MT PAGE 34	ALTIMAX™ ARCTIC PAGE 36	GRABBER™ ARCTIC PAGE 40	GRABBER™ ARCTIC LT PAGE 42	AMERI TRAC™ PAGE 44	AMERI TRAC™ TR PAGE 44	GRABBER™ APT PAGE 44
19	60	255/60R19				•										
	55	235/55R19				•										
		245/55R19				•										
		255/55R19			•											
	50	245/50R19	•													
		255/50R19			•											
	45	225/45R19	•													
		245/45R19	•													
		225/40R19	•													
	40	245/40R19	•	•												
		255/40R19	•													
		275/40R19	•													
	35	225/35R19	•													
		235/35R19	•													
		245/35R19	•													
		255/35R19	•													
		275/35R19	•													
	30	265/30R19	•													
		275/30R19	•													
20	65	LT275/65R20					•	•				•				
		LT295/65R20						•								
	60	275/60R20				•					•					
		275/55R20			•	•					•					
		255/55R20				•										
	55	LT295/55R20						•								
		LT305/55R20						•								
		245/50R20		•		•										
		265/50R20				•										
	50	285/50R20			•											
		295/50R20			•											
		305/50R20					•									
		LT315/50R20														
		245/45R20	•													
		255/45R20	•													
	45	275/45R20			•											
		295/45R20			•											
	40	245/40R20	•													
		275/40R20	•													
	35	245/35R20	•													
		255/35R20	•													

New size for 2016

	RIM DIAMETER	SERIES	SIZE	G-MAX™ AS-03 PAGE 14	ALTIMAX™ RT43 PAGE 18	GRABBER™ UHP PAGE 22	GRABBER™ HTS60 PAGE 24	GRABBER™ AT2 PAGE 28	GRABBER™ X3 PAGE 32	GRABBER™ MT PAGE 34	ALTIMAX™ ARCTIC PAGE 36	GRABBER™ ARCTIC PAGE 40	GRABBER™ ARCTIC LT PAGE 42	AMERITRAC™ PAGE 44	AMERITRAC™ TR PAGE 44	GRABBER™ APT PAGE 44
20	30	275/30R20		•												
	12.5	33X12.50R20LT					•	•								
		35X12.50R20LT					•	•								
		37X12.50R20LT						•								
	13.5	37X13.50R20LT						•								
22	45	285/45R22				•										
		305/45R22			•											
	40	265/40R22	•													
		305/40R22			•											
23	40	305/40R23			•											
24	35	305/35R24			•											

 New size for 2016

G-MAX™ AS-03

ALL-SEASON, DIRECTIONAL

DOMINANT ULTRA-HIGH PERFORMANCE ALL-SEASON TIRE DELIVERS PRECISE RESPONSE IN DRY AND WET CONDITIONS WITH EXCELLENT LIGHT SNOW GRIP.

3D Sipes: When interlocked the tread blocks work together to improve handling and reduce heat for increased tread life.

V-Shaped Pattern with Aqua-Cleave Groove Elements: Channel and directs water out of the tread for excellent resistance to hydroplaning.

Monitor Technology: Replacement tire monitor (RTM®) and Visual Alignment Indicators (VAI®) alert drivers of misalignment and treadwear conditions.

Strake Grooves: Expose more biting edges to enhance traction in wet and snow conditions.



UTQG:	TREAD WEAR:	TRACTION:	TEMPERATURE:
All Sizes	480	A	A

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
15	55		195/55R15	85V	SL	BSW	15489620000	23.4	15.1	51	7.9 (6.0)	5.5 - 7.0	1279	10	888	No
16	55		195/55R16	87V	SL	BSW	15490160000	24.4	16.7	51	7.9 (6.0)	5.5 - 7.0	1202	10	851	No
			205/55ZR16	91W	SL	BSW	15489690000	24.9	19.1	51	8.4 (6.5)	5.5 - 7.5	1356	10	834	No
			215/55ZR16	93W	SL	BSW	15489740000	25.3	18.8	51	8.9 (7.0)	6.0 - 7.0	1433	10	821	No
			225/55ZR16	95W	SL	BSW	15489830000	25.7	20.2	51	9.2 (7.0)	6.0 - 8.0	1521	10	877	No
	50		195/50ZR16	84W	SL	BSW	15489630000	23.7	16.8	51	8.5 (6.0)	5.5 - 7.0	1102	10	877	No
			205/50ZR16	87W	SL	BSW	15489670000	24.1	17.4	51	8.4 (6.5)	5.5 - 7.5	1202	10	862	No
			225/50ZR16	92W	SL	BSW	15489810000	24.9	19.5	51	9.2 (7.0)	6.0 - 8.0	1389	10	834	No
	45		205/45ZR16	83W	SL	BSW	15489650000	23.3	16.5	51	8.1 (7.0)	6.5 - 7.5	1074	11	892	Yes
17	55		215/55ZR17	94W	SL	BSW	15489750000	26.3	21.0	51	8.9 (7.0)	6.0 - 7.0	1477	10	790	No
			225/55ZR17	97W	SL	BSW	15490180000	26.7	22.1	51	9.2 (7.0)	6.0 - 8.0	1609	10	778	No
			235/55ZR17	99W	SL	BSW	15489910000	27.2	22.5	51	9.6 (7.5)	6.5 - 8.5	1709	10	764	No
	50		205/50ZR17	93W	XL	BSW	15489680000	25.1	19.2	51	8.5 (6.5)	5.5 - 7.5	1433	10	828	Yes
			215/50ZR17	95W	XL	BSW	15489730000	25.5	19.6	51	8.9 (7.0)	6.0 - 7.0	1521	10	815	Yes
			225/50ZR17	94W	SL	BSW	15489820000	25.9	21.5	51	9.2 (7.0)	6.0 - 8.0	1477	10	802	Yes
			235/50ZR17	96W	SL	BSW	15489890000	26.3	21.2	51	9.6 (7.5)	6.5 - 8.5	1565	10	790	Yes
			245/50ZR17	99W	SL	BSW	15490020000	26.6	24.7	51	10.0 (7.5)	7.0 - 8.5	1709	11	781	Yes
	45		205/45ZR17	88W	XL	BSW	15489660000	24.3	18.0	51	8.4 (7.0)	6.5 - 7.5	1235	11	855	Yes
			215/45ZR17	91W	XL	BSW	15489710000	24.6	20.0	51	8.5 (7.0)	7.0 - 8.0	1356	11	844	Yes
			225/45ZR17	91W	SL	BSW	15489790000	25.0	20.6	51	8.9 (7.5)	7.0 - 8.0	1356	11	831	Yes
			235/45ZR17	94W	SL	BSW	15489870000	25.3	22.1	51	9.3 (8.0)	7.5 - 9.0	1477	11	821	Yes
			245/45ZR17	95W	SL	BSW	15489990000	25.7	22.8	51	9.6 (8.0)	7.0 - 9.0	1521	11	808	Yes
	40		205/40ZR17	84W	XL	BSW	15489640000	23.5	16.6	51	8.4 (7.5)	7.0 - 8.0	1102	10	884	Yes
			245/40ZR17	91W	SL	BSW	15489950000	24.7	22.3	51	9.8 (8.5)	8.0 - 9.5	1356	10	841	Yes
			255/40ZR17	94W	SL	BSW	15490060000	25.0	23.7	51	10.2 (9.0)	8.5 - 10.0	1477	10	831	Yes
18	55		235/55ZR18	100W	SL	BSW	15489920000	28.2	22.9	51	9.6 (7.5)	6.5 - 8.5	1764	10	737	No
	50		225/50ZR18	95W	SL	BSW	15490170000	26.9	23.0	51	9.2 (7.0)	6.0 - 8.0	1521	10	772	Yes
			235/50ZR18	97W	SL	BSW	15489900000	27.3	23.0	51	9.6 (8.0)	6.5 - 8.5	1609	10	761	Yes
	45		215/45ZR18	93W	XL	BSW	15489720000	25.6	20.2	51	8.4 (7.0)	7.0 - 8.0	1433	11	811	Yes
			225/45ZR18	91W	SL	BSW	15489800000	26.0	21.9	51	8.9 (7.5)	7.0 - 8.5	1356	11	799	Yes
			235/45ZR18	98W	XL	BSW	15489880000	26.3	21.4	51	9.3 (8.0)	7.5 - 9.0	1654	11	790	Yes
			245/45ZR18	100W	XL	BSW	15494190000	26.7	23.4	51	9.6 (8.0)	7.5 - 9.0	1764	11	778	Yes
			255/45ZR18	103W	XL	BSW	15490090000	27.0	24.8	51	10.0 (8.5)	8.0 - 9.5	1929	11	769	Yes
	40		215/40ZR18	89W	XL	BSW	15489700000	24.8	19.2	51	8.6 (7.5)	7.0 - 8.5	1279	10	838	Yes
			225/40ZR18	92W	XL	BSW	15489770000	25.1	19.8	51	9.0 (8.0)	7.5 - 9.0	1389	10	828	Yes
			235/40ZR18	95W	XL	BSW	15494160000	25.4	20.8	51	9.5 (8.5)	8.0 - 9.5	1521	10	818	Yes
			245/40ZR18	97W	XL	BSW	15494170000	25.7	21.9	51	9.8 (8.5)	8.0 - 9.5	1609	10	808	Yes
			255/40ZR18	99W	XL	BSW	15490070000	26.0	25.1	51	10.2 (9.0)	8.5 - 10.0	1709	10	799	Yes
			275/40ZR18	99W	SL	BSW	15490140000	26.7	25.4	51	10.9 (9.5)	9.0 - 11.0	1709	10	778	Yes
	35		255/35ZR18	94W	XL	BSW	15494200000	25.0	21.6	51	10.0 (9.0)	8.5 - 10.0	1477	10	831	Yes
			265/35ZR18	97W	XL	BSW	15490110000	25.3	22.5	51	10.7 (9.5)	9.0 - 10.5	1609	10	821	Yes
			275/35ZR18	95W	SL	BSW	15490130000	25.6	23.8	51	11.2 (9.5)	9.0 - 11.0	1521	10	811	Yes

Continued next page

ALL-SEASON, DIRECTIONAL

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
19	50	245/50ZR19	105W	XL	BSW	15498360000	28.7	26.0	51	10.0 (7.5)	7.0 - 8.5	2039	10	724	Yes
	45	225/45ZR19	92W	SL	BSW	15490350000	27.0	22.2	51	9.6 (8.0)	7.0 - 8.5	1389	11	769	Yes
		245/45ZR19	98W	SL	BSW	15490010000	27.7	25.1	51	9.6 (8.0)	7.5 - 9.0	1654	11	750	Yes
	40	225/40ZR19	93W	XL	BSW	15489780000	26.1	20.5	51	9.1 (8.0)	7.5 - 9.0	1279	10	796	Yes
		245/40ZR19	98W	XL	BSW	15494180000	26.7	23.8	51	9.8 (8.5)	8.0 - 9.5	1654	10	778	Yes
		255/40ZR19	100W	XL	BSW	15490080000	27.0	24.2	51	10.2 (9.0)	8.5 - 10.0	1764	10	769	Yes
		275/40ZR19	101W	SL	BSW	15490150000	27.7	28.7	51	11.1 (9.5)	9.0 - 11.0	1819	10	750	Yes
	35	225/35ZR19	88W	XL	BSW	15489760000	25.2	19.4	51	9.1 (8.0)	7.5 - 9.0	1235	10	824	Yes
		235/35ZR19	91W	XL	BSW	15489850000	25.5	21.7	51	9.5 (8.5)	8.0 - 9.5	1356	10	815	Yes
		245/35ZR19	93W	XL	BSW	15489930000	25.8	21.3	51	9.8 (8.5)	8.0 - 9.5	1433	10	805	Yes
		255/35ZR19	96W	XL	BSW	15490040000	26.0	22.6	51	10.2 (9.0)	8.5 - 10.0	1565	10	799	Yes
		275/35ZR19	100W	XL	BSW	15490320000	26.6	25.8	51	10.9 (9.5)	9.0 - 11.0	1764	10	781	Yes
	30	265/30ZR19	93W	XL	BSW	15490100000	25.3	21.7	51	10.7 (9.5)	9.0 - 10.0	1433	10	821	Yes
		275/30ZR19	96W	XL	BSW	15490120000	25.5	22.8	51	10.9 (9.5)	9.0 - 10.0	1565	10	815	Yes
20	45	245/45ZR20	103W	XL	BSW	15490360000	28.7	24.4	51	9.6 (8.0)	7.5 - 9.0	1929	11	724	Yes
		255/45ZR20	105W	XL	BSW	15490340000	29.0	27.7	51	10.0 (8.5)	8.0 - 9.5	2039	10	716	Yes
	40	245/40ZR20	99W	XL	BSW	15489980000	27.7	25.4	51	9.8 (8.5)	8.0 - 9.5	1709	10	750	Yes
		275/40ZR20	106W	XL	BSW	15490330000	28.7	28.8	51	10.9 (9.5)	9.0 - 10.5	2094	10	724	Yes
	35	245/35ZR20	95W	XL	BSW	15489940000	26.8	22.7	51	9.8 (8.5)	8.0 - 9.5	1521	10	775	Yes
		255/35ZR20	97W	XL	BSW	15490050000	27.0	23.9	51	10.2 (9.0)	8.0 - 10.0	1609	10	769	Yes
	30	275/30ZR20	97W	XL	BSW	15490380000	26.5	24.5	51	10.4 (9.5)	9.0 - 10.0	1609	10	784	Yes
22	40	265/40ZR22	106W	XL	BSW	15498370000	30.3	32.7	51	10.7 (9.5)	9.0 - 10.5	2094	10	686	Yes



GENERAL TIRE ™

ALTIMAX™ RT43

ALL-SEASON, SYMMETRIC

THE ALL-SEASON TOURING TIRE DESIGNED FOR A QUIET, COMFORTABLE RIDE ALL-SEASON TRACTION AND ENHANCED WITH EVEN TREADWEAR AND EXTENDED TREADLIFE.

Replacement Tire Monitor (RTM®): Unique tread indicator transforms from REPLACEMENT TIRE MONITOR to read REPLACE TIRE at 2/32nds treadwear, easily alerting the driver a tire change is needed.

Visual Alignment Indicator (VAI®): Identifiable marker on the tread that extends the life of the tire by visually alerting the driver of vehicle misalignment.

Low Surface Abrasion (LSA) Technology: Promotes even treadwear and extended treadlife.

3D Sipe Technology: Interlocking tread blocks work together to improve handling and reduce heat for increased treadlife.

T SPEED RATING	TREAD WEAR:	TRACTION:	TEMPERATURE:
13 - 15	600	A	B
16 - 18	700	A	B

H&V SPEED RATING	TREAD WEAR:	TRACTION:	TEMPERATURE:
13 - 15	600	A	A
16 - 18	700	A	A



	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
13	70		175/70R13	82T	SL	BSW	15494820000	22.6	13.8	44	7.0 (5.0)	4.5 - 6.0	1047	11	919	No
14	70		175/70R14	84T	SL	BSW	15494830000	23.6	13.9	44	7.0 (5.0)	4.5 - 6.0	1102	11	880	No
			185/70R14	88T	SL	BSW	15494890000	24.2	15.2	44	7.4 (5.5)	4.5 - 6.0	1235	11	858	No
			195/70R14	91T	SL	BSW	15494920000	24.7	17.2	44	7.9 (6.0)	5.0 - 6.5	1356	11	841	No
			205/70R14	95T	SL	BSW	15494960000	25.3	20.2	44	8.2 (6.0)	5.0 - 7.0	1521	12	821	No
			215/70R14	96T	SL	BSW	15495050000	25.9	20.4	44	8.7 (6.5)	5.5 - 7.0	1565	12	802	No
			225/70R14	99T	SL	OWL	15502660000	26.5	23.3	44	9.0 (6.5)	6.0 - 7.5	1709	12	784	No
	65		175/65R14	82T	SL	BSW	15494800000	23.0	13.5	44	7.0 (5.0)	5.0 - 6.0	1047	11	903	No
			185/65R14	86T	SL	BSW	15494870000	23.5	14.8	44	7.4 (5.5)	5.0 - 6.5	1168	11	884	No
			185/65R14	86H	SL	BSW	15498020000	23.5	15.1	51	7.4 (5.5)	5.0 - 6.5	1168	10	884	No
	60		185/60R14	82H	SL	BSW	15498000000	22.7	14.6	51	7.4 (5.5)	5.0 - 6.5	1047	10	915	No
			195/60R14	86H	SL	BSW	15498040000	23.2	15.7	51	7.9 (6.0)	5.5 - 7.0	1168	11	895	No
15	70		205/70R15	96T	SL	BSW	15494970000	26.3	20.4	44	8.2 (6.0)	5.0 - 7.0	1565	12	790	No
			215/70R15	98T	SL	BSW	15495060000	26.9	22.4	44	8.7 (6.5)	5.5 - 7.0	1654	12	772	No
			225/70R15	100T	SL	OWL	15502670000	27.4	26.1	44	9.0 (6.5)	6.0 - 7.5	1764	12	758	No
			235/70R15	103T	SL	OWL	15502710000	28.0	27.8	44	9.4 (7.0)	6.0 - 8.0	1929	12	742	No
	65		175/65R15	84H	SL	BSW	15497990000	24.0	14.6	51	7.2 (5.0)	5.0 - 6.0	1102	10	866	No
			185/65R15	88T	SL	BSW	15494880000	24.5	15.9	44	7.4 (5.5)	5.0 - 6.5	1235	11	848	No
			185/65R15	88H	SL	BSW	15498030000	24.5	17.0	51	7.4 (5.5)	5.0 - 6.5	1235	10	848	No
			195/65R15	91T	SL	BSW	15494640000	25.0	16.7	44	7.9 (6.0)	5.5 - 7.0	1356	11	831	No
			195/65R15	91H	SL	BSW	15498060000	25.0	17.6	51	7.9 (6.0)	5.5 - 7.0	1356	11	831	No
			205/65R15	94T	SL	BSW	15494940000	25.5	18.4	44	8.2 (6.0)	5.5 - 7.5	1477	11	815	No
			205/65R15	94H	SL	BSW	15498080000	25.5	18.0	51	8.2 (6.0)	5.5 - 7.5	1477	10	815	No
			215/65R15	96T	SL	BSW	15495030000	26.0	20.7	44	8.7 (6.5)	6.0 - 7.0	1565	11	799	No
	60		185/60R15	84T	SL	BSW	15494840000	23.7	15.2	44	7.4 (5.5)	5.0 - 6.5	1102	11	877	No
			185/60R15	84H	SL	BSW	15498010000	23.7	15.6	51	7.4 (5.5)	5.0 - 6.5	1102	10	877	No
			195/60R15	88T	SL	BSW	15494900000	24.2	17.1	44	8.0 (6.0)	5.0 - 7.0	1235	11	858	No
			195/60R15	88H	SL	BSW	15498050000	24.2	17.4	51	8.0 (6.0)	5.0 - 7.0	1235	11	858	No
			205/60R15	91H	SL	BSW	15498070000	24.7	18.0	51	8.2 (6.0)	5.5 - 7.5	1356	10	841	No
			205/60R15	91T	SL	BSW	15502600000	24.7	17.9	44	8.2 (6.0)	5.5 - 7.5	1356	11	841	No
			215/60R15	94T	SL	BSW	15495010000	25.2	18.8	44	8.7 (6.5)	6.0 - 7.0	1477	11	824	No
			225/60R15	96H	SL	BSW	15497730000	25.6	22.4	51	9.0 (6.5)	6.0 - 8.0	1565	11	811	No
	55		185/55R15	82H	SL	BSW	15502570000	23.0	15.3	51	7.9 (6.0)	5.5 - 7.0	1047	10	903	No
			195/55R15	85V	SL	BSW	15497720000	23.4	15.9	51	7.9 (6.0)	5.5 - 7.0	1135	10	888	No
16	70		205/70R16	97T	SL	BSW	15494980000	27.3	20.3	44	8.2 (6.0)	5.0 - 7.0	1609	12	761	No
			215/70R16	100H	SL	BSW	15495070000	27.9	26.9	51	8.7 (6.5)	5.5 - 7.0	1764	11	745	No
			225/70R16	103T	SL	BSW	15495120000	28.4	26.0	44	9.0 (6.5)	6.0 - 7.0	1929	12	731	No

Continued next page

ALL-SEASON, SYMMETRIC

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
16	65	205/65R16	95T	SL	BSW	15494950000	26.5	19.1	44	8.2 (6.0)	5.5 - 6.5	1521	11	784	No
		205/65R16	95H	SL	BSW	15497790000	26.5	19.8	51	8.2 (6.0)	5.5 - 7.5	1521	10	784	No
		215/65R16	98T	SL	BSW	15494680000	27.0	21.2	44	8.7 (6.5)	6.0 - 7.0	1654	11	769	No
		215/65R16	98H	SL	BSW	15494690000	27.0	22.2	51	8.7 (6.5)	6.0 - 7.0	1654	11	769	No
		225/65R16	100H	SL	BSW	15494720000	27.5	22.5	51	9.0 (6.5)	6.0 - 8.0	1764	11	755	No
		225/65R16	100T	SL	BSW	15502640000	27.5	22.3	44	9.0 (6.5)	6.0 - 8.0	1764	11	755	No
		235/65R16	103T	SL	BSW	15495160000	28.0	25.0	44	9.4 (7.0)	6.5 - 7.5	1929	11	742	No
	60	205/60R16	92T	SL	BSW	15494930000	25.7	18.8	44	8.2 (6.0)	5.5 - 7.5	1389	11	808	No
		205/60R16	92H	SL	BSW	15497780000	25.7	19.6	51	8.2 (6.0)	5.5 - 7.5	1389	10	808	No
		205/60R16	92V	SL	BSW	15502610000	25.7	18.4	51	8.2 (6.0)	5.5 - 7.5	1389	10	808	No
		215/60R16	95T	SL	BSW	15494670000	26.2	20.8	44	8.7 (6.5)	6.0 - 7.0	1521	11	793	No
		215/60R16	95H	SL	BSW	15497810000	26.2	20.8	51	8.7 (6.5)	6.0 - 7.0	1521	10	793	No
		215/60R16	95V	SL	BSW	15497820000	26.2	20.2	51	8.7 (6.5)	6.0 - 7.0	1521	10	793	No
		225/60R16	98T	SL	BSW	15494650000	26.6	21.7	44	9.0 (6.5)	6.0 - 8.0	1654	11	781	No
		225/60R16	98H	SL	BSW	15497840000	26.6	22.5	51	9.0 (6.5)	6.0 - 8.0	1654	10	781	No
		235/60R16	100T	SL	BSW	15494750000	27.1	24.3	44	9.4 (7.0)	6.5 - 8.5	1764	11	767	No
		235/60R16	100H	SL	BSW	15494760000	27.1	24.4	51	9.4 (7.0)	6.5 - 8.5	1764	11	767	No
	55	185/55R16	87H	XL	BSW	15502580000	24.0	15.8	51	7.6 (6.0)	5.0 - 6.5	1202	10	866	No
		195/55R16	87V	SL	BSW	15497740000	24.4	16.7	51	7.9 (6.0)	5.5 - 7.0	1202	10	851	No
		205/55R16	91T	SL	BSW	15494660000	24.9	18.7	44	8.4 (6.5)	5.5 - 7.5	1356	11	834	No
		205/55R16	91H	SL	BSW	15497770000	24.9	19.4	51	8.4 (6.5)	5.5 - 7.5	1356	10	834	No
		215/55R16	97H	XL	BSW	15497800000	25.3	19.0	51	8.9 (7.0)	6.0 - 7.0	1609	10	821	No
		225/55R16	95H	SL	BSW	15497830000	25.7	20.5	51	9.2 (7.0)	6.0 - 8.0	1521	10	808	No
	50	195/50R16	84H	SL	BSW	15497750000	23.7	16.1	51	8.5 (6.0)	5.5 - 7.0	1102	10	877	No
		205/50R16	87H	SL	BSW	15497760000	24.1	17.6	51	8.4 (6.5)	5.5 - 7.5	1202	10	862	No
17	65	215/65R17	99T	SL	BSW	15495040000	28.0	21.4	44	8.7 (6.5)	6.0 - 7.0	1709	11	742	No
		225/65R17	102T	SL	BSW	15494730000	28.5	23.9	44	9.0 (6.5)	6.0 - 8.0	1874	11	729	No
		225/65R17	102H	SL	BSW	15494740000	28.5	24.3	51	9.0 (6.5)	6.0 - 8.0	1874	11	729	No
		235/65R17	104T	SL	BSW	15495170000	29.0	27.2	44	9.4 (7.0)	6.5 - 8.5	1984	11	716	No
	60	215/60R17	96T	SL	BSW	15495020000	27.2	21.1	44	9.3 (6.5)	6.0 - 7.0	1565	11	764	No
		225/60R17	99T	SL	BSW	15494700000	27.6	22.7	44	9.0 (6.5)	6.0 - 8.0	1709	11	753	No
		225/60R17	99H	SL	BSW	15494710000	27.6	23.8	51	9.0 (6.5)	6.0 - 8.0	1709	11	753	No
		235/60R17	102T	SL	BSW	15495150000	28.1	25.8	44	9.4 (7.0)	6.5 - 8.5	1874	11	739	No
	55	215/55R17	94T	SL	BSW	15494990000	26.3	21.1	44	8.9 (7.0)	6.0 - 7.0	1477	11	790	No
		215/55R17	94V	SL	BSW	15497880000	26.3	21.0	51	8.9 (7.0)	6.0 - 7.0	1477	10	790	No
		225/55R17	97T	SL	BSW	15495100000	26.8	21.7	44	9.2 (7.0)	6.0 - 8.0	1609	11	775	No
		225/55R17	97H	SL	BSW	15497910000	26.8	21.8	51	9.2 (7.0)	6.0 - 8.0	1609	10	775	No
		225/55R17	97V	SL	BSW	15497920000	26.8	21.8	51	9.2 (7.0)	6.0 - 8.0	1609	10	775	No
		235/55R17	99T	SL	BSW	15495130000	27.2	22.4	44	9.6 (7.5)	6.5 - 8.5	1709	11	764	No
		235/55R17	99H	SL	BSW	15497930000	27.2	23.6	51	9.6 (7.5)	6.5 - 8.5	1709	10	764	No

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
17	50	205/50R17	93V	XL	BSW	15497850000	25.1	20.2	51	8.4 (6.5)	5.5 - 7.5	1433	10	828	Yes
		215/50R17	95V	XL	BSW	15497870000	25.5	21.1	51	8.9 (7.0)	6.0 - 7.0	1521	10	815	Yes
		225/50R17	94T	SL	BSW	15495080000	25.9	21.4	44	9.2 (7.0)	6.0 - 8.0	1477	11	802	Yes
		225/50R17	98V	XL	BSW	15497900000	25.9	20.9	51	9.2 (7.0)	6.0 - 8.0	1654	10	802	Yes
	45	205/45R17	88V	XL	BSW	15502590000	24.3	19.0	51	8.4 (7.0)	6.5 - 7.5	1235	11	855	Yes
		215/45R17	87V	SL	BSW	15497860000	24.6	20.2	51	8.5 (7.0)	7.0 - 8.0	1202	11	844	Yes
		225/45R17	91H	SL	BSW	15497890000	25.0	21.0	51	8.9 (7.5)	7.0 - 8.5	1356	11	831	Yes
		225/45R17	94V	XL	BSW	15502620000	25.0	20.6	51	8.9 (7.5)	7.0 - 8.5	1477	11	831	Yes
		235/45R17	97H	XL	BSW	15502680000	25.3	21.5	51	9.3 (8.0)	7.5 - 9.0	1609	11	821	Yes
		245/45R17	99H	XL	BSW	15498090000	25.7	23.9	51	9.6 (8.0)	7.5 - 9.0	1709	11	808	Yes
18	65	235/65R18	106T	SL	BSW	15495180000	30.0	27.6	44	9.4 (7.0)	6.5 - 8.5	2095	11	692	No
		225/60R18	100H	SL	BSW	15497960000	28.6	24.8	51	9.0 (6.5)	6.0 - 8.0	1764	10	726	No
		235/60R18	107T	XL	BSW	15502700000	29.1	25.0	51	9.4 (7.0)	6.5 - 8.5	2150	11	714	No
	55	215/55R18	95T	SL	BSW	15495000000	27.3	22.6	44	8.9 (7.0)	6.0 - 7.0	1521	11	761	No
		225/55R18	98H	SL	BSW	15497950000	27.8	23.4	51	9.6 (7.5)	6.5 - 8.5	1654	10	747	No
		235/55R18	100H	SL	BSW	15495140000	28.2	24.0	51	9.6 (7.5)	6.5 - 8.5	1764	11	737	No
	50	225/50R18	95T	SL	BSW	15495090000	26.9	22.5	44	9.2 (7.0)	6.0 - 8.0	1521	11	772	Yes
		235/50R18	97V	SL	BSW	15497970000	27.3	23.9	51	9.6 (8.0)	6.5 - 8.5	1609	10	761	Yes
	45	225/45R18	95V	XL	BSW	15497940000	26.0	21.7	51	8.9 (7.5)	7.0 - 8.5	1521	11	799	Yes
		235/45R18	98V	XL	BSW	15502690000	26.3	21.6	51	9.3 (8.0)	7.5 - 9.0	1654	11	790	Yes
		245/45R18	100V	XL	BSW	15497980000	26.7	22.8	51	9.6 (8.0)	7.5 - 9.0	1764	11	778	Yes
	40	245/40R18	97V	XL	BSW	15502720000	25.7	23.3	51	9.8 (8.5)	8.0 - 9.5	1609	10	808	Yes
19	55	225/55R19	99H	SL	BSW	15502630000	28.8	24.4	51	9.2 (7.0)	6.0 - 8.0	1709	10	721	No
	45	255/45R19	104V	XL	BSW	15502750000	28.0	25.0	51	10.0 (8.5)	8.0 - 9.5	1984	11	742	Yes
	40	245/40R19	98V	XL	BSW	15502730000	26.7	23.8	51	9.8 (8.5)	8.0 - 9.5	1654	10	778	Yes
20	50	245/50R20	105H	XL	BSW	15502740000	29.7	33.4	51	10.0 (7.5)	7.0 - 8.5	2039	11	699	Yes

GRABBER™ UHP

ALL-SEASON, DIRECTIONAL

BOLD ULTRA-HIGH PERFORMANCE ALL-SEASON LIGHT TRUCK, CROSSOVER AND SUV TIRE DESIGNED FOR EXCELLENT HANDLING AND TRACTION IN BOTH WET AND DRY CONDITIONS.

Second Generation Silica Tread Compound: Delivers excellent handling, braking and traction in all conditions.

V-Shaped Directional Tread with Grooves from Center to Shoulder: Aids in efficient water evacuation and improves road contact for control in wet conditions.

Flat Belt Contour, Shallow Slots and Increased Tread Depth in Shoulder Area: Work together to deliver even wear and extended tread life.

Advanced Sound Reduction Technology and Continuously Varying Groove Angles: Helps assure an incredibly quiet, comfortable ride.



UTQG	TREAD WEAR:	TRACTION:	TEMPERATURE:
SERIES ≥ 55	360	A	B
SERIES ≤ 50	320	A	B



RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
16	65	255/65R16	109H	SL	BSW	15477130000	29.1	32.3	51	10.2 (7.5)	7.0 - 9.0	2271	11	714	No	No
17	60	255/60R17	106V	SL	BSW	15477170000	29.0	29.8	51	10.2 (7.5)	7.0 - 9.0	2094	11	716	Yes	Yes
	55	275/55R17	109V	SL	BSW	15477210000	28.9	31.9	51	11.2 (8.5)	7.5 - 9.5	2271	10	719	Yes	Yes
18	60	235/60R18	107V	XL	BSW	15478900000	29.1	26.1	51	9.4 (7.0)	6.5 - 8.5	2150	10	714	Yes	Yes
	55	255/55R18	109W	XL	BSW	15477200000	29.0	29.4	51	10.4 (8.0)	7.0 - 9.0	2271	10	716	Yes	Yes
19	55	255/55R19	111V	XL	BSW	04501900000	30.0	32.4	51	10.4 (8.0)	7.0 - 9.0	2403	10	692	Yes	Yes
	50	255/50R19	107W	XL	BSW	15484090000	29.0	31.5	51	10.4 (8.0)	7.0 - 9.0	2150	10	716	Yes	Yes
20	55	275/55R20	117V	XL	BSW	15477910000	31.9	36.6	51	11.2 (8.5)	7.5 - 9.5	2833	10	651	Yes	Yes
	50	285/50R20	112V	SL	BSW	15477490000	31.2	34.9	51	11.7 (9.0)	8.0 - 10.0	2469	10	666	Yes	Yes
		295/50R20	118V	XL	BSW	15477930000	31.6	41.3	51	12.1 (9.5)	8.0 - 10.5	2910	10	657	Yes	Yes
		275/45R20	110V	XL	BSW	15449440000	29.7	30.3	51	10.7 (9.0)	8.5 - 10.0	2337	10	699	Yes	Yes
	45	295/45R20	114V	XL	BSW	15477900000	30.5	38.6	51	11.7 (10.0)	9.5 - 11.0	2601	10	681	Yes	Yes
22	45	305/45R22	118V	XL	BSW	15478020000	32.8	43.3	51	12.0 (10.0)	9.5 - 11.0	2910	10	633	Yes	Yes
	40	305/40R22	114V	XL	BSW	15477920000	31.6	37.8	51	12.3 (11.0)	10.0 - 12.0	2601	10	657	Yes	Yes
23	40	305/40R23	115V	XL	BSW	15477870000	32.6	41.5	51	12.3 (11.0)	10.0 - 12.0	2679	10	637	Yes	Yes
24	35	305/35R24	112V	XL	BSW	15447940000	32.4	41.2	51	12.3 (11.0)	10.0 - 12.0	2469	10	641	Yes	Yes

GRABBER™ HTS60

HIGHWAY TERRAIN, SYMMETRIC

THE TOUGH HIGHWAY TERRAIN ALL-SEASON TIRE THAT PROVIDES THE PERFECT SYNERGY OF COMFORT, DURABILITY AND PERFORMANCE FOR LIGHT TRUCKS, SUVS AND CROSOVERS.

DuraGen™: Cut and chip resistant compound, coupled with ultra high strength steel belts and a broad, flat contour, provide confident stability, even wear and responsive handling.

Comfort Balance™: An absorption layer isolates the vehicle from road disturbances, while sound barrier ribs impede sound generated in the center of the pattern.

Stabili Tread: A flatter footprint, optimized tread pattern stiffness and an improved tread compound provide up to 25% more tread life than the original Grabber HTS.



S & T SPEED RATING	TREAD WEAR:	TRACTION:	TEMPERATURE:
METRIC SIZES	680	A	B

H SPEED RATING	TREAD WEAR:	TRACTION:	TEMPERATURE:
METRIC SIZES	660	A	A



	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX		LOAD RANGE	SIDEWALL	ARTICLE NUMBER		TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in) (MEASURING RIM)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
15	75	265/75R15	112S	SL	OWL		04504570000	30.6	35.4	44	10.5 (7.5)	7.0 - 9.0	2469	N/A	12	679	Yes		
	70	255/70R15	108S	SL	OWL		04504580000	29.1	32.0	44	10.2 (7.5)	6.5 - 8.5	2205	N/A	12	714	Yes		
	10.5	31X10.50R15LT	109R	C	OWL		04505070000	30.8	40.5	50	10.5 (8.5)	7.0 - 9.0	2270	N/A	14	674	Yes		
16	85	LT235/85R16	120/116R	E	OWL		04505080000	31.7	46.6	80	9.3 (6.5)	6.0 - 7.0	3085	2755	14	655	Yes		
	75	225/75R16	104S	SL	OWL		04504590000	29.3	29.3	44	8.8 (6.0)	6.0 - 7.0	1984	N/A	12	709	Yes		
		235/75R16	108S	SL	OWL		04504600000	29.9	31.2	44	9.3 (6.5)	6.0 - 8.0	2205	N/A	12	695	Yes		
		245/75R16	111S	SL	BSW		04504610000	30.5	32.4	44	9.8 (7.0)	6.5 - 8.0	2403	N/A	12	681	Yes		
		245/75R16	111S	SL	OWL		04504620000	30.5	33.4	44	9.8 (7.0)	6.5 - 8.0	2403	N/A	12	681	Yes		
		LT245/75R16	120/116S	E	BSW		04505090000	30.5	44.8	80	9.8 (7.0)	6.5 - 8.0	3085	2755	14	681	Yes		
		LT245/75R16	120/116S	E	OWL		04505100000	30.5	45.6	80	9.8 (7.0)	6.5 - 8.0	3085	2755	14	681	Yes		
		265/75R16	116T	SL	OWL		04504630000	31.6	41.6	44	10.5 (7.5)	7.0 - 9.0	2756	N/A	12	657	Yes		
		LT265/75R16	123/120R	E	OWL		04505120000	31.6	50.4	80	10.5 (7.5)	7.0 - 8.0	3415	3085	14	657	Yes		
	70	215/70R16	100T	SL	OWL		04504640000	27.9	26.0	44	8.7 (6.5)	5.5 - 7.0	1764	N/A	12	745	Yes		
		225/70R16	103T	SL	OWL		04504650000	28.4	28.5	44	9.0 (6.5)	6.0 - 7.0	1929	N/A	12	731	Yes		
		235/70R16	106T	SL	BSW		04504660000	29.0	29.6	44	9.4 (7.0)	6.0 - 8.0	2094	N/A	12	716	Yes		
		235/70R16	106T	SL	OWL		04504670000	29.0	30.3	44	9.4 (7.0)	6.0 - 8.0	2094	N/A	12	716	Yes		
		245/70R16	107T	SL	BSW		04504680000	29.5	32.7	44	9.8 (7.0)	6.5 - 8.0	2150	N/A	12	704	Yes		
		245/70R16	107T	SL	OWL		04504690000	29.5	33.7	44	9.8 (7.0)	6.5 - 8.0	2150	N/A	12	704	Yes		
		255/70R16	111S	SL	OWL		04504700000	30.1	33.4	44	10.2 (7.5)	6.5 - 8.5	2403	N/A	12	690	Yes		
		265/70R16	112T	SL	BSW		04504710000	30.6	35.7	44	10.7 (8.0)	7.0 - 9.0	2469	N/A	12	679	Yes		
	265/70R16	112T	SL	OWL		04504720000	30.6	36.3	44	10.7 (8.0)	7.0 - 9.0	2469	N/A	12	679	Yes			
65	255/65R16	109S	SL	OWL		04504730000	29.1	31.8	44	10.2 (7.5)	7.0 - 9.0	2271	N/A	12	714	Yes			
	255/65R16	109H	SL	BSW		04504740000	29.1	31.8	51	10.2 (7.5)	7.0 - 9.0	2271	N/A	12	714	Yes			
17	80	LT235/80R17	120/117R	E	OWL		04505130000	31.8	46.2	80	9.3 (6.5)	6.0 - 7.0	3085	2835	14	653	Yes		
	75	LT245/75R17	121/118S	E	BSW		04505140000	31.5	46.8	80	9.7 (7.0)	6.0 - 7.0	3195	2910	14	659	Yes		
		LT245/75R17	121/118S	E	OWL		04505150000	31.5	47.5	80	9.7 (7.0)	6.0 - 7.0	3195	2910	14	659	Yes		
	70	235/70R17	111T	XL	OWL		04504760000	30.0	32.3	51	9.4 (7.0)	6.0 - 8.0	2403	N/A	12	692	Yes		
		245/70R17	110T	SL	OWL		04504770000	30.5	36.9	44	9.8 (7.0)	6.5 - 8.0	2337	N/A	12	681	Yes		
		LT245/70R17	119/116S	E	OWL		04505160000	30.5	52.8	80	9.8 (7.0)	6.5 - 8.0	3000	2755	14	681	Yes		
		265/70R17	115S	SL	BSW		04504780000	31.6	39.2	44	10.7 (8.0)	7.0 - 9.0	2679	N/A	12	657	Yes		
		265/70R17	115S	SL	OWL		04504790000	31.6	40.4	44	10.7 (8.0)	7.0 - 9.0	2679	N/A	12	657	Yes		
		LT265/70R17	121/118S	E	OWL		04505170000	31.6	51.3	80	10.7 (8.0)	7.0 - 9.0	3195	2910	14	657	Yes		
		235/65R17	108T	XL	OWL		04504800000	29.0	31.6	51	9.4 (7.0)	6.5 - 8.5	2205	N/A	12	716	Yes		
	65	235/65R17	108H	XL	BSW		04504810000	29.0	30.1	51	9.4 (7.0)	6.5 - 8.5	2205	N/A	12	716	Yes		
		245/65R17	107T	SL	BSW		04504820000	29.5	32.5	44	9.8 (7.0)	7.0 - 8.5	2150	N/A	12	704	Yes		
		245/65R17	107T	SL	OWL		04504830000	29.5	33.1	44	9.8 (7.0)	7.0 - 8.5	2150	N/A	12	704	Yes		
		255/65R17	110T	SL	OWL		04504840000	30.1	35.2	44	10.2 (7.5)	7.0 - 9.0	2337	N/A	12	690	Yes		
265/65R17		112T	SL	OWL		04504850000	30.6	36.9	44	10.7 (8.0)	7.5 - 9.5	2469	N/A	12	679	Yes			
60	275/60R17	110T	SL	OWL		04504860000	30.0	37.0	44	11.0 (8.0)	7.5 - 9.5	2337	N/A	12	692	Yes			

OWL = Outlined White Letter

Continued next page

HIGHWAY TERRAIN, SYMMETRIC

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
18	70	255/70R18	113T	SL	OWL	04504870000	32.1	37.0	44	10.2 (7.5)	6.5 - 8.5	2535	N/A	12	647	Yes
		265/70R18	116T	SL	OWL	04504880000	32.6	39.1	44	10.7 (8.0)	7.0 - 9.0	2756	N/A	12	637	Yes
		LT275/70R18	125/122S	E	OWL	04505180000	33.2	55.5	80	10.9 (8.0)	7.0 - 8.5	3640	3305	14	626	Yes
	65	235/65R18	106T	SL	OWL	04504890000	30.0	30.7	44	9.4 (7.0)	6.5 - 8.5	2095	N/A	12	692	Yes
		255/65R18	111S	SL	BSW	04504900000	31.1	36.7	44	10.2 (7.5)	7.0 - 9.0	2403	N/A	12	668	Yes
		265/65R18	114T	SL	OWL	04504910000	31.5	38.5	44	10.7 (8.0)	7.5 - 9.5	2601	N/A	12	659	Yes
		275/65R18	116T	SL	OWL	04504920000	32.1	39.1	44	10.9 (8.0)	7.5 - 9.5	2756	N/A	12	647	Yes
		LT275/65R18	123/120S	E	OWL	04505190000	32.1	52.8	80	10.9 (8.0)	7.5 - 9.0	3415	3085	14	647	Yes
	60	235/60R18	103H	SL	BSW	04504930000	29.1	31.8	51	9.4 (7.0)	6.5 - 8.5	1929	N/A	12	714	Yes
		245/60R18	105H	SL	BSW	04504940000	29.6	31.8	51	9.8 (7.0)	7.0 - 8.5	2039	N/A	12	702	Yes
		265/60R18	110T	SL	OWL	04504950000	30.5	38.1	44	10.7 (8.0)	7.5 - 9.5	2337	N/A	12	681	Yes
	55	255/55R18	109H	XL	BSW	04504960000	29.0	34.5	51	10.4 (8.0)	7.0 - 9.0	2271	N/A	12	716	Yes
19	60	255/60R19	109S	SL	BSW	04504970000	31.1	36.4	44	10.2(7.5)	7.0 - 9.0	2271	N/A	12	668	Yes
		255/60R19	109H	SL	BSW	04504980000	31.1	36.4	51	10.2(7.5)	7.0 - 9.0	2271	N/A	12	668	Yes
	55	235/55R19	101H	SL	BSW	04504990000	29.6	29.1	51	9.6 (7.5)	6.5 - 8.5	1819	N/A	12	702	Yes
		245/55R19	103T	SL	BSW	04505000000	29.6	29.5	44	10.0 (7.5)	7.0 - 8.5	1929	N/A	12	702	Yes
20	60	275/60R20	119T	XL	BSW	04505010000	33.0	40.5	51	11.0 (8.0)	7.5 - 9.5	2998	N/A	12	630	Yes
	55	255/55R20	107H	SL	BSW	04505200000	31.0	33.6	51	10.4 (8.0)	7.0 - 9.0	2149	N/A	12	670	Yes
		275/55R20	117T	XL	BSW	04505020000	31.9	38.9	51	11.2 (8.5)	7.5 - 9.5	2833	N/A	12	651	Yes
		275/55R20	117H	XL	BSW	04505030000	31.9	38.9	51	11.2 (8.5)	7.5 - 9.5	2833	N/A	12	651	Yes
	50	245/50R20	102H	SL	BSW	04505040000	29.7	33.5	51	10.0 (7.5)	7.0 - 8.5	1874	N/A	12	699	Yes
		265/50R20	107T	SL	BSW	04505050000	30.4	36.5	44	10.9 (8.5)	7.5 - 9.5	2150	N/A	12	683	Yes
22	45	285/45R22	114H	XL	BSW	04505060000	32.1	39.4	51	11.2 (9.5)	9.0 - 10.5	2601	N/A	12	647	Yes

New size for 2017



GENERAL TIRE ™

GRABBER™ AT²

ALL-TERRAIN, SYMMETRIC

THIS TOUGH, ALL-TERRAIN TIRE IS DESIGNED WITH AN AGGRESSIVE, SELF-CLEANING TREAD PATTERN THAT PROVIDES OFF-ROAD TRACTION, DURABILITY AND IMPRESSIVE PAVED ROAD PERFORMANCE.

5-Row Tread Pattern with Multiple Traction Edges:

Innovative tread design promotes uncompromising on and off-road traction.

Double V-Shaped Tread Pattern: Designed to increase tread life and off-road durability.

Highly-Engineered Acoustic Tread Pattern: Allows the aggressive tread pattern to provide a quiet, comfortable ride during highway driving.

Snowflake Approved* and Studdable Design:

Meets the severe snow service requirements of the RMA and RAC.



UTQG:	TREAD WEAR:	TRACTION:	TEMPERATURE:
METRIC SIZES	640	A	B
255/55R18	480	A	B



Meets the severe snow service requirements of the Rubber Manufacturers Associations (RMA) and the Rubber Association of Canada (RAC). Studdable

GENERAL TIRE 

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
14	8.5	27X8.50R14LT	95Q	C	OWL	05684400000	26.5	28.7	50	8.6 (7.0)	6.0 - 7.0	1520	N/A	16	784	Yes	
15	75	205/75R15	97T	SL	OWL	15463680000	27.1	24.0	44	8.0 (5.5)	5.5 - 7.0	1609	N/A	14	767	No	
		215/75R15	100S	SL	OWL	15463720000	27.7	28.3	44	8.5 (6.0)	5.5 - 7.0	1764	N/A	14	750	No	
		LT235/75R15	104/101S	C	OWL	05684060000	28.9	33.3	50	9.3 (6.5)	6.0 - 7.0	1985	1820	16	719	Yes	
	70	225/70R15	100S	SL	OWL	15474600000	27.4	30.0	44	9.0 (6.5)	6.0 - 7.0	1764	N/A	16	758	Yes	
		255/70R15	108S	SL	BSW	15483390000	29.1	38.3	44	10.2 (7.5)	6.5 - 8.5	2205	N/A	16	714	Yes	
		265/70R15	112S	SL	OWL	15463780000	29.6	39.2	44	10.7 (8.0)	7.0 - 9.0	2469	N/A	16	702	Yes	
	12.5	35X12.50R15LT	113Q	C	OWL	04505390000	34.8	55.7	35	12.5 (10.0)	9.0 - 11.0	2535	N/A	16	597	Yes	
		33X12.50R15LT	108Q	C	OWL	05684050000	32.8	50.6	35	12.5 (10.0)	8.5 - 11.0	2205	N/A	16	633	Yes	
	10.5	31X10.50R15LT	109S	C	OWL	05684040000	30.8	40.4	50	10.5 (8.5)	7.0 - 9.0	2270	N/A	16	674	Yes	
	9.5	30X9.50R15LT	104S	C	OWL	05684030000	29.7	35.9	50	9.5 (7.5)	6.5 - 8.5	1985	N/A	16	699	Yes	
16	85	LT235/85R16	120/116S	E	OWL	05684070000	31.7	48.0	80	9.3 (6.5)	6.0 - 7.0	3085	2755	16	655	Yes	
	75	225/75R16	108S	XL	OWL	15463740000	29.3	32.5	51	8.8 (6.0)	6.0 - 7.0	2205	N/A	16	709	Yes	
		LT245/75R16	120/116S	E	OWL	05684080000	30.5	44.4	80	9.8 (7.0)	6.5 - 8.0	3085	2755	16	681	Yes	
		LT265/75R16	123/120Q	E	OWL	05684090000	31.6	52.2	80	10.5 (7.5)	7.0 - 8.0	3415	3085	16	657	Yes	
		LT285/75R16	122/119Q	D	OWL	05684100000	32.8	56.7	65	11.3 (8.0)	7.5 - 9.0	3305	3000	16	633	Yes	
		LT295/75R16	123/120Q	D	OWL	05684110000	33.4	56.3	65	11.6 (8.0)	7.5 - 9.5	3415	3085	16	622	Yes	
		LT315/75R16	121Q	D	OWL	05684120000	34.6	62.9	50	12.3 (8.5)	8.0 - 10.0	3195	N/A	16	600	Yes	
	70	215/70R16	100T	SL	BSW	15463710000	27.9	28.2	44	8.7 (6.5)	5.5 - 7.0	1764	N/A	14	745	Yes	
		235/70R16	106T	SL	OWL	04504040000	29.0	31.3	44	9.4 (7.0)	6.0 - 8.0	2094	N/A	14	716	Yes	
		245/70R16	107T	SL	OWL	04504050000	29.5	35.4	44	9.8 (7.0)	6.5 - 8.0	2150	N/A	16	704	Yes	
		255/70R16	111S	SL	OWL	15474590000	30.1	37.8	44	10.2 (7.5)	6.5 - 8.5	2403	N/A	16	690	Yes	
		265/70R16	112S	SL	OWL	15483090000	30.6	40.5	44	10.7 (8.0)	7.0 - 9.0	2469	N/A	16	679	Yes	
	65	LT305/70R16	118/115Q	D	OWL	05684190000	32.8	57.6	50	12.2 (9.0)	8.0 - 9.5	2910	2680	16	633	Yes	
		215/65R16	98T	SL	BSW	15463700000	27.0	27.0	44	8.7 (6.5)	6.0 - 7.0	1654	N/A	14	769	No	
		255/65R16	109T	SL	BSW	15463770000	29.1	36.9	44	10.2 (7.5)	7.0 - 9.0	2271	N/A	16	714	Yes	
17	80	LT235/80R17	120/117Q	E	OWL	04563390000	31.8	46.1	80	9.3 (6.5)	6.0 - 7.0	3085	2835	16	653	Yes	
	75	LT245/75R17	121/118R	E	OWL	04503000000	31.5	49.1	80	9.7 (7.0)	6.0 - 7.0	3195	2910	16	659	Yes	
	70	245/70R17	110S	SL	OWL	15447730000	30.5	38.1	44	9.8 (7.0)	6.5 - 8.0	2337	N/A	16	681	No	
		255/70R17	112S	SL	BSW	15447660000	31.1	38.8	44	10.2 (7.5)	6.5 - 8.5	2469	N/A	16	668	No	
		265/70R17	115S	SL	OWL	04504060000	31.6	40.8	44	10.7 (8.0)	7.0 - 9.0	2679	N/A	16	657	Yes	
		LT265/70R17	121/118Q	E	OWL	04564990000	31.6	52.4	80	10.7 (8.0)	7.0 - 9.0	3195	2910	16	657	Yes	
		LT285/70R17	121/118R	E	OWL	04502990000	32.7	57.5	80	11.5 (8.5)	7.5 - 9.0	3195	2910	16	635	Yes	
		LT315/70R17	121/118R	D	OWL	04503020000	34.4	64.3	65	12.7 (9.5)	8.5 - 10.0	3195	2910	16	604	Yes	
	65	255/65R17	110S	SL	OWL	15447710000	30.1	38.1	44	10.2 (7.5)	7.0 - 9.0	2337	N/A	16	690	No	
		265/65R17	112S	SL	OWL	15447810000	30.6	39.3	44	10.7 (8.0)	7.5 - 9.5	2469	N/A	16	679	No	
		265/65R17	112T	SL	BSW	15449010000	30.6	40.6	44	10.7 (8.0)	7.5 - 9.5	2469	N/A	16	679	Yes	
	12.5	33X12.50R17LT	105Q	C	OWL	04505400000	33.0	57.9	50	12.5 (10.0)	7.5 - 9.0	2040	N/A	16	630	Yes	
		35X12.50R17LT	119Q	D	OWL	04505420000	34.8	64.4	50	12.5 (10.0)	9.0 - 10.5	3000	N/A	16	597	Yes	

OWL = Outlined White Letter

Stud Length: 12 mm (TSMI #13)
N/A = Not Applicable

Continued next page

ALL-SEASON, SYMMETRIC

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
18	70	LT265/70R18	124/121R	E	OWL	04503030000	32.6	55.0	80	10.7 (8.0)	7.0 - 9.0	3525	3195	16	637	Yes
		265/70R18	116S	SL	OWL	15447740000	32.6	42.7	44	10.7 (8.0)	7.0 - 9.0	2756	N/A	16	637	No
		LT275/70R18	125/122Q	E	OWL	04566550000	33.2	57.6	80	10.9 (8.0)	7.0 - 8.5	3640	3305	16	626	No
	65	275/65R18	116S	SL	BSW	04501220000	32.1	42.8	44	10.9 (8.0)	7.5 - 9.5	2756	N/A	16	647	Yes
		LT275/65R18	123/120Q	E	OWL	04565950000	32.1	55.0	80	10.9 (8.0)	7.5 - 9.0	3415	3085	16	647	Yes
	60	255/60R18	112H	XL	BSW	15484070000	30.0	36.7	51	10.2 (7.5)	7.0 - 9.0	2469	N/A	13	692	Yes
		LT285/60R18	122/119Q	E	BSW	04566890000	31.5	55.2	80	11.5 (8.5)	8.0 - 10.0	3305	3000	16	659	No
	55	255/55R18	109H	XL	BSW	15477940000	29.0	34.2	51	10.4 (8.0)	7.0 - 9.0	2271	N/A	13	716	Yes
	12.5	33X12.50R18LT	118Q	E	BSW	04505430000	33.0	61.7	65	12.5 (10.0)	8.5 - 11.0	2910	N/A	16	630	Yes
		35X12.50R18LT	118Q	D	BSW	04505440000	34.8	64.2	50	12.5 (10.0)	8.5 - 11.0	2910	N/A	16	597	Yes
20	65	LT275/65R20	126/123S	E	OWL	04503010000	34.1	59.4	80	11.0 (8.0)	7.5 - 9.5	3750	3415	16	609	Yes
	50	305/50R20	120T	XL	BSW	15478240000	32.0	50.4	51	12.4 (9.5)	8.5 - 11.0	3086	N/A	16	649	Yes
	12.5	33X12.50R20LT	114Q	E	BSW	04505450000	32.8	63.1	65	12.5 (10.0)	8.5 - 11.0	2600	N/A	16	633	Yes
		35X12.50R20LT	121Q	E	BSW	04504030000	34.8	66.7	65	12.5 (10.0)	8.5 - 11.0	3195	N/A	16	597	Yes

OWL = Outlined White Letter

Stud Length: 12 mm (TSMI #13)

N/A = Not Applicable



GENERAL TIRE ™

GRABBER™ X3

EXTREME TERRAIN, SYMMETRIC

EXTREME TERRAIN TIRE DELIVERS EXCEPTIONAL OFF-ROAD PERFORMANCE IN MUD, DIRT AND ROCK COVERED TERRAIN FOR LIGHT TRUCKS AND SUVS.

3-Ply DURAGEN™ Technology: Race proven durability and puncture resistance provide driving confidence under the world's most extreme conditions.

High Void Pattern Design: An aggressive open pattern with massive tread blocks delivers extreme off-road traction, with quick and efficient self cleaning evacuation channels.

Sidewall Protection Lugs: Boldly styled protection pads alternate in-and-out for additional side grip during extreme off-roading.

Deflection Ribs: A series of stacked ribs in the upper sidewall deflect obstacles from the tire body to protect against damage and penetration.

Alternating Shoulder Scoops: Aggressive areas of high void expose large grip surfaces on neighboring blocks that provide additional traction in loose, deep and rocky terrain.

Stone Bumpers: Raised protection ribs in groove bottoms, minimize stone retention and drilling for improved puncture resistance.



GENERAL TIRE 

		RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX			LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in) (MEASURING RIM)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
15	10.5	31X10.50R15LT		109Q	C	BSW			04505660000	30.8	55.0	50	10.5 (8.5)	7.0 - 9.0	2270	N/A	21	674	Yes	
		33X10.50R15LT		114Q	C	SRL			04506840000	33.0	62.1	50	10.5 (8.5)	7.0 - 9.0	2600	N/A	21	630	Yes	
	12.5	33X12.50R15LT		108Q	C	BSW			04505670000	32.8	65.5	35	12.5 (10.0)	8.5 - 11.0	2205	N/A	21	633	Yes	
		35X12.50R15LT		113Q	C	BSW			04505680000	35.0	72.3	35	12.5 (10.0)	8.5 - 11.0	2535	N/A	21	594	Yes	
16	75	LT265/75R16		112/109Q	C	SRL			04505700000	31.6	49.2	50	10.5 (7.5)	7.0 - 8.0	2470	2270	18	657	Yes	
		LT265/75R16		123/120Q	E	BSW			04505710000	31.6	63.2	80	10.5 (7.5)	7.0 - 8.0	3415	3085	18	657	Yes	
		LT285/75R16		126/123Q	E	BSW			04505720000	32.8	66.6	80	11.3 (8.0)	7.5 - 9.0	3750	3415	18	633	Yes	
		LT315/75R16		127/124Q	E	BSW			04505730000	34.6	76.3	65	12.3 (8.5)	8.0 - 10.0	3860	3525	18	600	Yes	
17	12.5	37X12.50R17LT		124Q	D	SRL			04505860000	36.8	79.7	50	12.5 (10.0)	8.5 - 11.0	3525	N/A	21	565	Yes	
		37X12.50R17LT		124Q	D	BSW			04505870000	36.8	79.7	50	12.5 (10.0)	8.5 - 11.0	3525	N/A	21	565	Yes	
	75	LT255/75R17		111/108Q	C	BSW			04505750000	30.3	63.9	50	10.0 (7.0)	6.5 - 8.0	2405	2205	18	686	Yes	
	12.5	35X12.50R17LT		121Q	E	SRL			04505840000	35.0	78.7	65	12.5 (10.0)	8.5 - 11.0	3195	N/A	21	594	Yes	
		35X12.50R17LT		121Q	E	BSW			04505850000	35.0	78.7	65	12.5 (10.0)	8.5 - 11.0	3195	N/A	21	594	Yes	
	70	LT265/70R17		121/118Q	E	SRL			04505760000	31.6	61.9	80	10.7 (8.0)	7.0 - 9.0	3195	2910	18	657	Yes	
		LT265/70R17		121/118Q	E	BSW			04505770000	31.6	61.9	80	10.7 (8.0)	7.0 - 9.0	3195	2910	18	657	Yes	
		LT285/70R17		121/118Q	E	SRL			04505780000	32.7	69.4	80	11.5 (8.5)	7.5 - 9.0	3195	2910	18	635	Yes	
		LT295/70R17		121/118Q	E	SRL			04505790000	33.3	70.6	80	11.8 (8.5)	7.5 - 10.0	3195	2910	18	624	Yes	
		LT295/70R17		121/118Q	E	BSW			04505800000	33.3	70.6	80	11.8 (8.5)	7.5 - 10.0	3195	2910	18	624	Yes	
		LT315/70R17		121/118Q	E	BSW			04505810000	34.4	75.0	80	12.7 (9.5)	8.5 - 10.0	3195	2910	18	604	Yes	
	12.5	33X12.50R17LT		114Q	D	SRL			04505820000	33.0	71.7	50	12.5 (10.0)	8.5 - 11.0	2600	N/A	21	630	Yes	
		33X12.50R17LT		114Q	D	BSW			04505830000	33.0	71.7	50	12.5 (10.0)	8.5 - 11.0	2600	N/A	21	630	Yes	
18	12.5	37X12.50R18LT		128Q	E	SRL			04505970000	36.8	79.2	65	12.5 (10.0)	8.5 - 11.0	3970	N/A	21	565	Yes	
	70	LT265/70R18		124/121Q	E	BSW			04505880000	32.6	66.2	80	10.7 (8.0)	7.0 - 9.0	3525	3195	18	637	Yes	
		LT275/70R18		125/122Q	E	SRL			04505890000	33.2	65.3	80	10.8 (8.0)	7.0 - 8.5	3640	3305	18	626	Yes	
		LT275/70R18		125/122Q	E	BSW			04505900000	33.2	68.4	80	10.8 (8.0)	7.0 - 8.5	3640	3305	18	626	Yes	
		LT295/70R18		129/126Q	E	BSW			04505910000	34.5	72.8	80	11.8 (8.5)	7.5 - 10.0	4080	3750	18	602	Yes	
	12.5	35X12.50R18LT		123Q	E	SRL			04505950000	35.0	79.0	65	12.5 (10.0)	8.5 - 11.0	3415	N/A	21	594	Yes	
		35X12.50R18LT		123Q	E	BSW			04505960000	35.0	79.0	65	12.5 (10.0)	8.5 - 11.0	3415	N/A	21	594	Yes	
	65	LT275/65R18		123/120Q	E	BSW			04505920000	32.1	55.0	80	10.9 (8.0)	7.5 - 9.0	3415	3085	18	647	Yes	
	12.5	33X12.50R18LT		118Q	E	SRL			04505930000	33.0	74.2	65	12.5 (10.0)	8.5 - 11.0	2910	N/A	21	630	Yes	
		33X12.50R18LT		118Q	E	BSW			04505940000	33.0	74.2	65	12.5 (10.0)	8.5 - 11.0	2910	N/A	21	630	Yes	
20	13.5	37X13.50R20LT		127Q	E	SRL			04506080000	36.8	72.1	65	13.6 (11.0)	8.5 - 11.0	3860	N/A	21	565	Yes	
		37X13.50R20LT		127Q	E	BSW			04506090000	36.8	72.1	65	13.6 (11.0)	8.5 - 11.0	3860	N/A	21	565	Yes	
	65	LT275/65R20		126/123Q	E	BSW			04505980000	34.1	70.6	80	11.0 (8.0)	7.5 - 9.5	3750	3415	18	609	Yes	
		LT295/65R20		129/126Q	E	SRL			04505990000	35.4	75.0	80	11.8 (8.5)	8.0 - 10.0	4080	3750	18	587	Yes	
		LT295/65R20		129/126Q	E	BSW			04506000000	35.4	75.0	80	11.8 (8.5)	8.0 - 10.0	4080	3750	18	587	Yes	
	12.5	33X12.50R20LT		114Q	E	BSW			04506050000	32.8	63.1	65	12.5 (10.0)	8.5 - 11.0	2600	N/A	21	633	Yes	
		35X12.50R20LT		121Q	E	SRL			04506060000	35.0	80.6	65	12.5 (10.0)	8.5 - 11.0	3195	N/A	21	594	Yes	
		35X12.50R20LT		121Q	E	BSW			04506070000	35.0	80.6	65	12.5 (10.0)	8.5 - 11.0	3195	N/A	21	594	Yes	
	55	LT295/55R20		123/120Q	E	BSW			04506010000	33.0	71.7	80	12.2 (9.5)	8.0 - 10.0	3415	3085	18	630	Yes	
LT305/55R20			121/118Q	E	SRL			04506030000	33.5	73.9	65	12.4 (9.5)	8.5 - 11.0	3195	2910	18	620	Yes		
LT305/55R20			121/118Q	E	BSW			04506040000	33.5	73.9	65	12.4 (9.5)	8.5 - 11.0	3195	2910	18	620	Yes		

New size for 2017

SRL = Smooth Red Letter

GRABBER™ MT

EXTREME TERRAIN, SYMMETRIC

BORN FROM COMPETITION, THIS HIGH VOID MUD-TERRAIN TIRE PROVIDES THE ULTIMATE IN OFF-ROAD GRIP AND DURABILITY, WITH A BALANCE OF ON-ROAD DRIVABILITY.

3-Ply DURAGEN™ Technology: Race proven durability and puncture resistance provides driving confidence under the world's most extreme conditions.

Aggressive Open Pattern Design: High void and large lug design delivers a high level of traction in loose, muddy and rocky surfaces.

Stone Deflection Ribs: Raised ribs in key grooves minimize stone retention and stone drilling.

High Void Shoulder Design: Aggressive open shoulder with wide lugs provide additional traction in loose, deep and rocky surfaces



GENERAL TIRE 

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in) (MEASURING RIM)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
15	75	LT235/75R15	104/101Q	C	BSW	04501680000		28.9	42.1	50	9.3 (6.5)	6.0 - 7.0	1985	1820	18	719	Yes
	12.5	33X12.50R15LT	108Q	C	BSW	04501660000		32.8	62.0	35	12.5 (10.0)	8.5 - 11.0	2205	N/A	18	633	Yes
	10.5	31X10.50R15LT	109Q	C	BSW	04501650000		30.8	50.0	50	10.5 (8.5)	7.0 - 9.0	2270	N/A	18	674	Yes
16	75	LT265/75R16	112/109Q	C	BSW	04505620000		31.6	49.2	50	10.5 (7.5)	7.0 - 8.0	2470	2270	18	657	Yes
		LT265/75R16	123/120Q	E	BSW	04501670000		31.6	56.3	80	10.5 (7.5)	7.0 - 8.0	3415	3085	18	657	Yes

ALTIMAX™ ARCTIC

WINTER STUDDABLE, DIRECTIONAL

UNIQUE GROOVES AND SIPES COMBINE WITH A MODERN COMPOUND TO OFFER OUTSTANDING PERFORMANCE IN WINTER CONDITIONS.

Multi-Angle Sipe System: 270 degrees of sipes with biting edges that maximize snow, ice and wet traction in all directions.

Directional Tread Pattern with Center Stability Rib: Provides active water evacuation while the solid center rib provides straight-line stability.

Reactive Contour Technology (RCT): Contour reacts to different road conditions to maintain enhanced contact with road surface throughout the life of the tire.

All-Weather Dual Tread Compound: A mixture of natural rubber and silica rubber compound maintains cold-weather flexibility and provides excellent wet traction and long even treadwear.



Meets the severe snow service requirements of the Rubber Manufacturers Association (RMA) and the Rubber Association of Canada (RAC). Studdable

GENERAL TIRE 

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
13	70		175/70R13	82Q	SL	BSW	15486000000	22.6	14.8	44	7.0 (5.0)	4.5 - 6.0	1047	N/A	12	919	No
14	70		185/70R14	88Q	SL	BSW	15486100000	24.2	17.3	44	7.4 (5.5)	4.5 - 6.0	1235	N/A	12	858	No
	65		175/65R14	82Q	SL	BSW	15486110000	23.0	14.6	44	7.0 (5.0)	5.0 - 6.0	1047	N/A	12	903	No
			185/65R14	86Q	SL	BSW	15486120000	23.5	15.8	44	7.4 (5.5)	5.0 - 6.5	1168	N/A	12	884	No
	60		185/60R14	82Q	SL	BSW	15489030000	22.7	16.4	44	7.4 (5.5)	5.0 - 6.5	1047	N/A	12	915	No
15	70		205/70R15	96Q	SL	BSW	15486200000	26.3	21.5	44	8.2 (6.0)	5.0 - 7.0	1565	N/A	12	790	No
			215/70R15	98Q	SL	BSW	15486300000	26.9	25.2	44	8.7 (6.5)	5.5 - 7.0	1654	N/A	12	772	No
			225/70R15	100Q	SL	BSW	15455980000	27.4	27.1	44	9.0 (6.5)	6.0 - 7.0	1764	N/A	12	758	No
	65		185/65R15	88Q	SL	BSW	15486130000	24.5	17.3	44	7.4 (5.5)	5.0 - 6.5	1235	N/A	12	848	No
			195/65R15	91Q	SL	BSW	15486140000	25.0	19.5	44	7.9 (6.0)	5.5 - 7.0	1356	N/A	12	831	No
			205/65R15	94Q	SL	BSW	15486150000	25.5	21.0	44	8.2 (6.0)	5.5 - 7.5	1477	N/A	12	815	No
			215/65R15	96Q	SL	BSW	15454580000	26.0	23.5	44	8.7 (6.5)	6.0 - 7.0	1565	N/A	12	799	No
	60		185/60R15	84Q	SL	BSW	15486160000	23.7	16.7	44	7.4 (5.5)	5.0 - 6.5	1102	N/A	12	877	No
			195/60R15	88Q	SL	BSW	15486170000	24.2	17.7	44	8.0 (6.0)	5.0 - 7.0	1235	N/A	12	858	No
			205/60R15	91Q	SL	BSW	15486220000	24.7	20.0	44	8.2 (6.0)	5.5 - 7.5	1356	N/A	12	841	No
			215/60R15	94Q	SL	BSW	15453470000	25.2	21.7	44	8.7 (6.5)	6.0 - 7.0	1477	N/A	12	824	No
	55		195/55R15	85Q	SL	BSW	15486180000	23.4	17.7	44	7.9 (6.0)	5.5 - 7.0	1135	N/A	12	888	No
16	75		235/75R16	108Q	SL	BSW	15456980000	29.9	31.9	44	9.3 (6.5)	6.0 - 8.0	2205	N/A	12	695	No
			265/75R16	116Q	SL	BSW	15458960000	31.6	39.1	44	10.5 (7.5)	7.0 - 9.0	2756	N/A	12	657	Yes
	70		215/70R16	100Q	SL	BSW	15531580000	27.9	26.9	44	8.7 (6.5)	5.5 - 7.0	1764	N/A	12	745	No
			225/70R16	103Q	SL	BSW	15486190000	28.4	29.5	44	9.0 (6.5)	6.0 - 7.0	1929	N/A	12	731	No
			245/70R16	107Q	SL	BSW	15489020000	29.5	30.4	44	9.8 (7.0)	6.0 - 8.0	2150	N/A	12	704	No
			255/70R16	111Q	SL	BSW	15457960000	30.1	34.4	44	10.2 (7.5)	6.5 - 8.5	2403	N/A	12	690	No
	65		215/65R16	98Q	SL	BSW	15486210000	27.0	23.6	44	8.7 (6.5)	6.0 - 7.0	1654	N/A	12	769	No
	60		205/60R16	92Q	SL	BSW	15486230000	25.7	21.2	44	8.2 (6.0)	5.5 - 7.5	1389	N/A	12	808	No
			215/60R16	95Q	SL	BSW	15486240000	26.2	22.8	44	8.7 (6.5)	6.0 - 7.0	1521	N/A	12	793	No
			225/60R16	98Q	SL	BSW	15486250000	26.6	23.5	44	9.0 (6.5)	6.0 - 8.0	1654	N/A	12	781	No
			235/60R16	100Q	SL	BSW	15486290000	27.1	24.0	44	9.4 (7.0)	6.5 - 8.5	1764	N/A	12	767	No
	55		205/55R16	91Q	SL	BSW	15486260000	24.9	19.8	44	8.4 (6.5)	5.5 - 7.5	1356	N/A	12	834	No
			215/55R16	93Q	SL	BSW	15486270000	25.3	21.8	44	8.9 (7.0)	6.0 - 7.0	1433	N/A	12	821	No
			225/55R16	95Q	SL	BSW	15486280000	25.7	22.8	44	9.2 (7.0)	6.0 - 8.0	1521	N/A	12	808	No
17	65		215/65R17	99Q	SL	BSW	15489010000	28.0	25.1	44	8.7 (6.5)	6.0 - 7.0	1709	N/A	12	742	No
			225/65R17	102Q	SL	BSW	15488990000	28.5	26.7	44	9.0 (6.5)	6.0 - 8.0	1874	N/A	12	729	No
			235/65R17	108Q	XL	BSW	15486310000	29.0	33.4	51	9.4 (7.0)	6.5 - 8.5	2205	N/A	12	716	Yes

Continued next page

WINTER STUDDABLE, DIRECTIONAL

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in) (MEASURING RIM)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
17	60	215/60R17	96Q	SL	BSW	15453480000	27.2	23.7	44	9.3 (6.5)	6.0 - 7.0	1565	N/A	12	764	No
		225/60R17	99Q	SL	BSW	15489000000	27.6	24.8	44	9.0 (6.5)	6.0 - 8.0	1709	N/A	12	753	No
	55	215/55R17	94Q	SL	BSW	15452050000	26.3	23.7	44	8.9 (7.0)	6.0 - 7.0	1477	N/A	12	790	No
		225/55R17	97Q	SL	BSW	15455000000	26.8	25.2	44	9.2 (7.0)	6.0 - 8.0	1609	N/A	12	775	No
		235/55R17	99Q	SL	BSW	15455990000	27.2	29.8	44	9.6 (7.5)	6.5 - 8.6	1709	N/A	12	764	No
	50	205/50R17	93Q	XL	BSW	15486320000	25.1	21.7	51	8.4 (6.5)	5.5 - 7.5	1433	N/A	12	828	Yes
		215/50R17	91Q	SL	BSW	15451570000	25.5	22.6	44	8.9 (7.0)	6.0 - 7.0	1356	N/A	12	815	No
	45	215/45R17	87Q	SL	BSW	15451480000	24.6	20.6	44	8.5 (7.0)	7.0 - 8.0	1202	N/A	12	844	Yes
		225/45R17	91Q	SL	BSW	15486330000	25.0	22.3	44	8.9 (7.5)	7.0 - 8.5	1356	N/A	12	831	Yes
		235/45R17	94Q	SL	BSW	15486340000	25.3	23.3	44	9.3 (8.0)	7.5 - 9.0	1477	N/A	12	821	Yes



GENERAL TIRE ™

GRABBER™ ARCTIC

WINTER STUDDABLE, DIRECTIONAL

STUDDABLE WINTER TIRE WITH OUTSTANDING LOW TEMPERATURE TRACTION IN SNOW, ICE AND WET CONDITIONS THAT IS DURABLE, ROBUST AND COMFORTABLE FOR LARGE SUVs AND PICK UP TRUCKS

DuraGen™ Technology: A robust cut and chip resistant compound, combined with ultra high-strength steel belts and a broad contour, promote confident stability, even wear, excellent braking and responsive handling.

Directional Tread Pattern with Center Stability Rib: Provides active water evacuation and snow traction while the center rib provides straight-line stability.

Strong Interlocking Light Truck Winter Sipes combined with smooth car like serrated Sipes: Exceptional grip in snow, ice and wet conditions while providing stable handling and strong braking in dry and wet conditions. Combination of truck and car sipes provide durability and comfort.

Pinned for Winter Studs: For those that desire the added ice grip winter studs provide.

Tread Block Reinforcement Butress: Add strength and stability to tread blocks, providing improved handling dynamics and improved wet and dry braking performance.



Meets the severe snow service requirements of the Rubber Manufacturers Association (RMA) and the Rubber Association of Canada (RAC). Studdable

GENERAL TIRE 

	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in) (MEASURING RIM)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
16	75		245/75R16	115T	XL	BSW	15503330000	30.5	34.2	51	9.8 (7.0)	6.5 - 8.0	2679	12	681	Yes
	70		235/70R16	109T	XL	BSW	15503280000	29.0	29.9	51	9.4 (7.0)	6.0 - 8.0	2271	12	716	Yes
			265/70R16	116T	XL	BSW	15503340000	30.6	35.7	51	10.7 (8.0)	7.0 - 9.0	2756	12	679	Yes
17	70		245/70R17	114T	XL	BSW	15503290000	30.5	33.8	51	9.8 (7.0)	6.5 - 8.0	2601	12	681	Yes
			265/70R17	116T	XL	BSW	15502540000	31.6	35.7	51	10.7 (8.0)	7.0 - 9.0	2756	12	657	Yes
	65		245/65R17	111T	XL	BSW	15503260000	29.5	32.1	51	9.8 (7.0)	7.0 - 8.5	2403	12	704	Yes
			265/65R17	116T	XL	BSW	15503370000	30.6	37.0	51	10.7 (8.0)	7.5 - 9.5	2756	12	679	Yes
18	65		255/65R18	115T	XL	BSW	15503380000	31.1	36.8	51	10.2 (7.5)	7.0 - 9.0	2679	12	668	Yes
			265/65R18	116T	XL	BSW	15503360000	31.5	37.9	51	10.7 (8.0)	7.5 - 9.5	2756	12	659	Yes
			275/65R18	116T	XL	BSW	15503300000	32.1	41.1	51	10.9 (8.0)	7.5 - 9.5	2756	12	647	Yes
	60		245/60R18	109T	XL	BSW	15503310000	29.6	29.9	51	9.8 (7.0)	7.0 - 8.5	2271	12	702	Yes
			265/60R18	114T	XL	BSW	15503350000	30.5	37.5	51	10.7 (8.0)	7.5 - 9.5	2601	12	681	Yes
	55		255/55R18	109T	XL	BSW	15502560000	29.0	30.0	51	10.4 (8.0)	7.0 - 9.0	2271	12	716	Yes
20	65		275/60R20	116T	XL	BSW	15503320000	33.0	40.6	51	11.0 (8.0)	7.5 - 9.5	2756	12	630	Yes
	55		275/55R20	117T	XL	BSW	15503270000	31.9	38.1	51	11.2 (8.5)	7.5 - 9.5	2833	12	651	Yes

GRABBER™ ARCTIC LT

WINTER STUDDABLE, DIRECTIONAL

INNOVATIVE LIGHT TRUCK STUDDABLE WINTER TIRE
WITH OUTSTANDING LOW TEMPERATURE TRACTION IN SNOW,
ICE, AND WET CONDITIONS.

Light Truck Tread Compound: A strong, cut and chip resistant compound that maintains coldweather flexibility and provides excellent winter traction with long, even treadwear.

DuraGen™: Robust design and materials provide confident stability under all approved load conditions with responsive handling and even tread wear.

Interlocking Light Truck Winter Sipes: Interlocking straight sipes provide exceptional grip in snow and icy conditions with strong wet/dry braking and stable handling.

Snow Traction Ridges: Raised ridges in the grooves provide additional grip during cornering, accelerating and braking in deep snow.



Meets the severe snow service requirements of the Rubber Manufacturers Associations (RMA) and the Rubber Association of Canada (RAC). Studdable

GENERAL TIRE 

RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	TIRE DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT
16	75	LT225/75R16	115/112R	E	BSW	04504420000	29.3	42.5	80	8.8 (6.0)	6.0 - 7.0	2680	2470	16	709	Yes
		LT245/75R16	120/116R	E	BSW	04504440000	30.5	46.7	80	9.8 (7.0)	6.5 - 8.0	3085	2755	16	681	Yes
		LT265/75R16	123/120R	E	BSW	04504450000	31.6	51.1	80	10.5 (7.5)	7.0 - 8.0	3415	3085	16	657	Yes
17	75	LT245/75R17	121/118R	E	BSW	04504470000	31.5	49.5	80	9.7 (7.0)	6.0 - 7.0	3195	2910	16	659	Yes
	70	LT245/70R17	119/116R	E	BSW	04504460000	30.5	47.6	80	9.8 (7.0)	6.5 - 8.0	3000	2755	16	681	Yes
		LT265/70R17	121/118R	E	BSW	04504480000	31.6	53.2	80	10.7 (8.0)	7.0 - 9.0	3195	2910	16	657	Yes
18	70	LT265/70R18	124/121R	E	BSW	04504490000	32.6	54.4	80	10.7 (8.0)	7.0 - 9.0	3525	3195	16	637	Yes
		LT275/70R18	125/122R	E	BSW	04504510000	33.2	55.6	80	10.9 (8.0)	7.0 - 8.5	3640	3305	16	626	Yes
	65	LT275/65R18	123/120R	E	BSW	04504500000	32.1	54.7	80	10.9 (8.0)	7.5 - 9.0	3415	3085	16	647	Yes
20	65	LT275/65R20	126/123R	E	BSW	04504520000	34.1	59.5	80	11.0 (8.0)	7.5 - 9.5	3750	3415	16	609	Yes

ORIGINAL EQUIPMENT PRODUCT LINE



AMERITRAC™



AMERITRAC™ TR



GRABBER™ APT



GRABBER™ HTS

OE	RIM DIAMETER	SERIES	SIZE	LOAD / SPEED INDEX	LOAD RANGE	SIDEWALL	ARTICLE NUMBER	OVERALL TIRE / WHEEL DIAMETER (in)	TIRE WEIGHT (LBS)	MAX. INFLATION PRESSURE (PSI)	OVERALL SECTION WIDTH (in)	APPROVED RIM WIDTHS (in)	MAX LOAD (LBS)	MAX DUAL LOAD (LBS)	TREAD DEPTH (in - 32nds)	REVS PER MILE	RIM PROTECT	UTQG
AMERITRAC™																		
GM	16	70	P255/70R16	109H	SL	BSW	15480400000	30.1	34.8	44	10.2 (7.5)	6.5 - 8.5	2271	N/A	11	690	No	420 B B
Dodge	17	80	LT235/80R17	120/117R	E	BSW	04501890000	31.8	46.4	80	9.3 (6.5)	6.0 - 7.0	3085	2835	14	653	No	none
Chevy/GMC	17	70	P245/70R17	108S	SL	BSW	15448380000	30.5	28.5	44	9.8 (7.0)	6.5 - 8.0	2205	N/A	10	681	No	420 B B

AMERITRAC™ TR																		
Dodge	17	80	LT235/80R17	120/117R	E	OWL	04501870000	31.8	48.6	80	9.3 (6.5)	6.0 - 7.0	3085	2835	16	653	No	none
Dodge	17	80	LT235/80R17	120/117R	E	BSW	04501880000	31.8	48.0	80	9.3 (6.5)	6.0 - 7.0	3085	2835	16	653	No	none
Ford	17	70	P255/70R17	110S	SL	OWL	15448240000	31.1	35.4	44	10.2 (7.5)	6.5 - 8.5	2337	N/A	14	668	No	500 A B
GM	17	70	P265/70R17	113H	SL	BSW	15482850000	31.6	36.6	44	10.7 (8.0)	7.0 - 9.0	2535	N/A	13	657	No	500 A A

GRABBER™ APT																		
Nissan	18	70	P275/70R18	116S	SL	BSW	04503130000	33.2	41.9	44	11.0 (8.0)	7.0 - 9.0	2756	N/A	11	626	Yes	520 A B
Nissan	18	65	LT275/65R18	123/120R	E	BSW	04503200000	32.1	53.4	80	10.9 (8.0)	7.5 - 9.0	3415	3085	15	647	Yes	none

GRABBER™ HTS																		
Nissan	15	75	235/75R15	105T	SL	OWL	04503120000	28.9	29.1	44	9.3 (6.5)	6.0 - 8.0	2039	N/A	12	719	Yes	640 A B
Nissan	15	70	225/70R15	100T	SL	OWL	15486010000	27.4	26.6	44	9.0 (6.5)	6.0 - 7.0	1764	N/A	12	758	Yes	640 A B
GM	16	75	LT225/75R16	115/112S	E	BSW	04501200000	29.3	38.7	80	8.8 (6.0)	6.0 - 7.0	2680	2470	13	709	No	none
GM	16	70	P215/70R16	99S	SL	BSW	15449050000	27.9	23.1	44	8.7 (6.5)	5.0 - 7.0	1709	N/A	11	745	Yes	640 A B
Ford	17	75	LT245/75R17	121/118S	E	BSW	04501840000	31.5	45.3	80	9.7 (7.0)	6.0 - 7.0	3195	2910	12	659	No	none
GM	17	70	P245/70R17	108S	SL	BSW	15448420000	30.5	31.6	44	9.8 (7.0)	6.5 - 8.0	2205	N/A	11	681	No	640 A B
GM	17	70	P245/70R17	108T	SL	BSW	15449490000	30.5	31.2	44	9.8 (7.0)	6.5 - 8.0	2205	N/A	11	681	No	640 A B
GM	17	70	P255/70R17	110S	SL	BSW	04503280000	31.1	31.6	44	10.2 (7.5)	6.5 - 8.5	2337	N/A	11	668	No	640 A B
GM	17	70	P255/70R17	110S	SL	BSW	15490430000	31.1	33.0	44	10.2 (7.5)	6.5 - 8.5	2337	N/A	11	668	No	640 A B
AM General	17	65	235/65R17	108H	XL	BSW	15485310000	29.0	29.7	51	9.4 (7.0)	6.5 - 8.5	2205	N/A	12	716	Yes	640 A B
Nissan	18	70	265/70R18	116S	SL	OWL	04503190000	32.6	39.3	44	10.7 (8.0)	7.0 - 9.0	2756	N/A	11	637	No	640 A B
Nissan	20	60	LT265/60R20	121/118R	E	BSW	04503240000	32.5	53.4	80	10.7 (8.0)	7.5 - 9.5	3195	2910	12	639	Yes	none

AM GENERAL MV-1											
15485310000		235/65R17 108H XL	Grabber HTS	BSW				13	14	15	16
15485320000	X	235/65R17 108T XL	Grabber HTS	BSW	04504800000	Grabber HTS60	12				

CHEVROLET COLORADO										
15449050000		P215/70R16 99S SL	Grabber HTS	BSW			12			

CHEVROLET EXPRESS										
04501160000	X	LT215/85R16 115/112S E	AmeriTrac	BSW	no replacement		12			
04501200000		LT225/75R16 115/112S E	Grabber HTS	BSW			12	13	14	15
15448380000		P245/70R17 108S SL	AmeriTrac	BSW			12	13	14	

CHEVROLET SILVERADO										
15449490000		P245/70R17 108T SL	Grabber HTS	BSW			12	13		
15449020000	X	P245/70R17 108H SL	AmeriTrac	BSW	no replacement		12	13	14	
15490430000		P255/70R17 110S SL	Grabber HTS	BSW				13	14	15
04503280000		P255/70R17 110S SL	Grabber HTS	BSW						16
15482850000		P265/70R17 113H SL	AmeriTrac TR	BSW			12	13	14	15

CHEVROLET TRAVERSE										
15448420000		P245/70R17 108S SL	Grabber HTS	BSW			12	13	14	15

DODGE RAM 3500										
04566420000	X	LT235/80R17 120/117R E	AmeriTrac TR	OWL	04501870000	AmeriTrac TR	12			
04501870000		LT235/80R17 120/117R E	AmeriTrac TR	OWL			12	13	14	
04566430000	X	LT235/80R17 120/117R E	AmeriTrac TR	BSW	04501880000	AmeriTrac TR	12			
04501880000		LT235/80R17 120/117R E	AmeriTrac TR	BSW			12	13	14	
04566450000	X	LT235/80R17 120/117R E	AmeriTrac	BSW	04501890000	AmeriTrac	12			
04501890000		LT235/80R17 120/117R E	AmeriTrac	BSW				13	14	

FORD F250/F350										
04569450000	X	LT245/75R17 121/118S E	Grabber HTS	BSW	04501840000	Grabber HTS	12	13		
04501840000		LT245/75R17 121/118S LRE	Grabber HTS	BSW				13	14	15

GMC CANYON										
15449050000		P215/70R16 99S SL	Grabber HTS	BSW			12			

YEAR SELECTED AS OE											
GMC SAVANA											
04568620000	X	LT215/85R16 115/112S E	AmeriTrac	BSW	04501160000	AmeriTrac	12				
04501200000		LT225/75R16 115/112S E	Grabber HTS	BSW			12	13	14	15	16
15448380000		P245/70R17 108S SL	AmeriTrac	BSW			12	13	14		
GMC SIERRA											
15449020000	X	P245/70R17 108H SL	AmeriTrac	BSW	no replacement		12	13	14		
15449490000		P245/70R17 108T SL	Grabber HTS	BSW			12	13			
04503280000		P255/70R17 110S SL	Grabber HTS	BSW							16
NISSAN FRONTIER											
15486010000		225/70R15 100T SL	Grabber HTS	OWL			12	13	14		
04503120000		235/75R15 105T SL	Grabber HTS	OWL					14	15	
15480030000		P235/75R15 105S SL	Grabber AW	BSW			12	13	14		
NISSAN PATHFINDER											
15473830000	X	P245/75R16 109S SL	Grabber AW	BSW	15483640000	Grabber HTS	12				
NISSAN TITAN											
04503190000		265/70R18 116S SL	Grabber HTS	OWL							16
04503200000		275/65R18 123/120R E	Grabber HTS	BSW							16
04503130000		275/70R18 116S SL	Grabber APT	BSW							16
04503240000		LT265/60R20 121/118R E	Grabber HTS	BSW							16
SUZUKI EQUATOR											
15480030000		P235/75R15 105S SL	Grabber AW	BSW			12	13	14		

PASSENGER TIRE AND LIGHT TRUCK DEPTH CONVERSION TABLE TO PERCENTAGE OF WEAR:

All numbers to the right designate the percentage of usable tread remaining, used to determine credit due to customer toward the purchase of a replacement tire. The numbers to the left designate the percentage of usable tread worn, to determine customer's charge for a replacement tire.

To obtain the remaining tread depth, take three (3) measurements on the tire, one on the inner groove, one on the center and one in the outer groove and then average the three (3) measurements. Locate (below) the tire's original tread depth. Read down and across matching the tire's measured remaining tread depth. Use the percentages shown as a charge and/or credit towards the purchase of a replacement tire.

ORIGINAL TIRE TREAD DEPTHS IN 32NDS

	9/32	10/32	11/32	12/32	13/32	14/32	15/32	16/32	17/32	18/32	19/32	20/32	21/32	22/32	23/32	24/32	25/32	26/32	27/32	28/32
Remaining Tread																				
2/32	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0	100%/0
3/32	86%/14	88%/12	89%/11	90%/10	91%/9	92%/8	92%/8	93%/7	93%/7	94%/6	94%/6	94%/6	95%/5	95%/5	95%/5	95%/5	96%/4	96%/4	96%/4	96%/4
4/32	71%/29	75%/25	78%/22	80%/20	82%/18	83%/17	85%/15	86%/14	87%/13	88%/12	88%/12	89%/11	89%/11	90%/10	90%/10	91%/9	91%/9	92%/8	92%/8	92%/8
5/32	57%/43	63%/37	67%/33	70%/30	73%/27	75%/25	77%/23	79%/21	80%/20	81%/19	82%/18	83%/17	84%/16	85%/15	86%/14	86%/14	87%/13	88%/12	88%/12	88%/12
6/32	43%/57	50%/50	56%/44	60%/40	64%/36	67%/33	69%/31	71%/29	73%/27	75%/25	76%/24	78%/22	79%/21	80%/20	81%/19	82%/18	83%/17	83%/17	84%/16	85%/15
7/32	29%/71	38%/62	44%/56	50%/50	55%/45	58%/42	62%/38	64%/36	67%/33	69%/31	71%/29	72%/28	74%/26	75%/25	76%/24	77%/23	78%/22	79%/21	80%/20	81%/19
8/32	14%/86	25%/75	33%/67	40%/60	45%/55	50%/50	54%/46	57%/43	60%/40	63%/37	65%/35	67%/33	68%/32	70%/30	71%/29	73%/27	74%/26	75%/25	76%/24	77%/23
9/32	0%/100	13%/87	22%/78	30%/70	36%/64	42%/58	46%/54	50%/50	53%/47	56%/44	59%/41	61%/39	63%/37	65%/35	67%/33	68%/32	70%/30	71%/29	72%/28	73%/27
10/32		0%/100	11%/89	20%/80	27%/73	33%/67	38%/62	43%/57	47%/53	50%/50	53%/47	56%/44	58%/42	60%/40	62%/38	64%/36	65%/35	67%/33	68%/32	69%/31
11/32			0%/100	10%/90	18%/82	25%/75	31%/69	36%/64	40%/60	44%/56	47%/53	50%/50	53%/47	55%/45	57%/43	59%/41	61%/39	62%/38	64%/36	65%/35
12/32				0%/100	9%/91	17%/83	23%/77	29%/71	33%/67	37%/63	41%/59	44%/56	47%/53	50%/50	52%/48	55%/45	57%/43	58%/42	60%/40	62%/38
13/32					0%/100	8%/92	15%/85	21%/79	27%/73	31%/69	35%/65	39%/61	42%/58	45%/55	48%/52	50%/50	52%/48	54%/46	56%/44	58%/42
14/32						0%/100	8%/92	14%/86	20%/80	25%/75	29%/71	33%/67	37%/63	40%/60	43%/57	45%/55	48%/52	50%/50	52%/48	54%/46
15/32							0%/100	7%/93	13%/87	19%/81	24%/76	28%/72	32%/68	35%/65	38%/63	41%/59	43%/57	46%/54	48%/52	50%/50
16/32								0%/100	7%/93	12%/88	18%/82	22%/78	26%/74	30%/70	33%/67	36%/64	39%/61	42%/58	44%/56	46%/54
17/32									0%/100	6%/94	12%/88	17%/83	21%/79	25%/75	29%/71	32%/68	35%/65	38%/62	40%/60	42%/58
18/32										0%/100	6%/94	11%/89	16%/84	20%/80	24%/76	27%/73	30%/70	33%/67	36%/64	38%/62
19/32											0%/100	6%/94	11%/89	15%/85	19%/81	23%/77	26%/74	29%/71	32%/68	35%/65
20/32												0%/100	5%/95	10%/90	14%/86	18%/82	22%/78	25%/75	28%/72	31%/69
21/32													0%/100	5%/95	10%/90	14%/86	17%/83	21%/79	24%/76	27%/73
22/32														0%/100	5%/95	9%/91	13%/87	17%/83	20%/80	23%/77
23/32															0%/100	5%/95	9%/91	12%/88	16%/84	19%/81
24/32																0%/100	4%/96	8%/92	12%/88	15%/85
25/32																	0%/100	4%/96	8%/92	12%/88
26/32																		0%/100	4%/96	8%/92
27/32																			0%/100	4%/96
28/32																				0%/100



Dot shows an example of where to take measurements. It is NOT recommended to measure straight across in one location.