



SPECIAL DELIVERY

G622 RSD[®]

**THE GOODYEAR[®] G622 RSD —
FOR REGIONAL AND LOCAL HIGH-SCRUB APPLICATIONS**

The G622 RSD is a long-lasting tire ideal for regional and local high-scrub applications.

Get outstanding traction from a tire that can hold up under tough conditions — and help your fleet save money.

Additionally, the speed rating for the size 225/70R19.5 Load Range G G622 RSD has now been updated from 75 mph to 87 mph.

GOODYEAR
MORE DRIVEN.




G622 RSD[®]

The G622 RSD is available in the following sizes and load ranges:

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm			
TUBELESS TIRES ON 15" DROP CENTER RIMS																										
225/70R19.5	F	3,640	1,650	95	660	3,415	1,550	95	660	63	28	6.75	8.9	226	32.4	824	15.1	384	641	398	19	10.0	254	75		
225/70R19.5	G	3,970	1,800	110	760	3,750	1,700	110	760	65	29	6.75	8.9	226	32.4	824	15.1	384	641	398	19	10.0	254	87		
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	75	34	7.50	9.7	245	33.5	852	15.6	397	620	389	19	11.0	280	75		
10R22.5	G	5,675	2,575	115	790	5,355	2,430	115	790	112	51	7.50	10.2	259	40.6	1,031	19.0	483	512	318	23	11.4	290	75		
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	128	58	8.25	11.1	282	42.0	1,067	19.7	500	497	309	26	12.5	318	75		
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	139	63	9.00	11.7	297	43.3	1,100	20.3	516	482	300	22	13.5	343	75		
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	96	44	7.50	10.0	254	37.0	940	17.3	439	561	349	23	11.3	287	81		
245/75R22.5	G	4,675	2,120	110	760	4,410	2,000	110	760	94	43	7.50	9.6	244	37.6	955	17.7	450	552	343	23	11.0	279	75		
265/75R22.5	G	5,205	2,360	110	760	4,805	2,180	110	760	102	47	7.50	10.0	254	38.9	988	18.3	465	561	349	23	11.6	295	75		
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	118	54	8.25	11.2	284	40.8	1,036	19.1	485	512	318	26	12.9	328	75		
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	135	61	8.25	11.1	282	43.9	1,115	20.6	523	475	295	26	12.5	318	75		

Check goodyeartrucktires.com for updated data.



- AGGRESSIVE BLADING helps provide outstanding traction
- TIE-BARRED SHOULDERS enhance handling and help deliver even wear
- INCREASED WEARABLE TREAD RUBBER helps enhance mileage
- UNISTEEL[®] CONSTRUCTION enhances toughness and retreadability

Matching Retreads

Retreads	Size	Available Width		Tread Depth
		in	mm	32nds
UniCircle [®]	225/70R19.5	7½	190	19
UniCircle	245/70R19.5	8½	215	20
UniCircle	11R22.5	8½, 9	215, 230	26
UniCircle	295/75R22.5	8½, 9	215, 230	26
UniCircle	11R24.5	8½	215	26
Precure	-	7, 7½, 8, 8½, 8¾, 9¼	180, 190, 205, 215, 225, 235	22
Precure LT		7, 7½, 8, 8½*	180,* 190,* 205,* 215*	16

*Tread design also available with sipes.



GOODYEAR
MORE DRIVEN.