

550 CC/MIN • 52 LBS/HR



EV6-USCAR electrical connector

Fuel Pressure			Voltage Offset				Flow Rate	
PSID	BAR	8 Volts	10 Volts	12 Volts	14 Volts	16 Volts	cc/min	lbs/hr
43.5	3.00	2.700	1.540	1.120	0.730	0.523	550	52
45	3.10	2.850	1.560	1.130	0.740	0.529	559	53
50	3.44	2.970	1.580	1.144	0.745	0.534	589	56
55	3.79	3.120	1.600	1.151	0.749	0.538	618	59
60	4.13	3.300	1.620	1.158	0.751	0.541	645	61
65	4.48	3.600	1.640	1.164	0.753	0.543	672	64
70	4.82	3.840	1.660	1.171	0.756	0.545	697	66
75	5.17	4.090	1.680	1.179	0.760	0.547	722	69
80	5.51	4.330	1.700	1.188	0.765	0.549	745	71
85	5.86	4.580	1.723	1.196	0.770	0.552	768	73
90	6.20	4.820	1.740	1.203	0.775	0.557	791	75
95	6.55	5.060	1.756	1.211	0.777	0.562	812	77
100	6.89	5.310	1.770	1.218	0.780	0.567	833	79