1150 cc/min • 109 lbs/hr

| Fuel Pr | essure | | Voltage Offset | | | | Flow Rate | |
|---------|--------|---------|----------------|----------|----------|----------|-----------|--------|
| PSID | BAR | 8 Volts | 10 Volts | 12 Volts | 14 Volts | 16 Volts | cc/min | lbs/hr |
| 43.5 | 2.99 | 2.070 | 1.875 | 1.500 | 1.300 | 1.177 | 1150 | 109 |
| 45 | 3.10 | 2.152 | 1.950 | 1.560 | 1.352 | 1.224 | 1170 | 111 |
| 50 | 3.44 | 2.238 | 2.028 | 1.622 | 1.406 | 1.272 | 1233 | 117 |
| 55 | 3.79 | 2.327 | 2.109 | 1.686 | 1.462 | 1.322 | 1293 | 123 |
| 60 | 4.13 | 2.420 | 2.193 | 1.753 | 1.520 | 1.374 | 1350 | 128 |
| 65 | 4.48 | 2.516 | 2.280 | 1.823 | 1.580 | 1.428 | 1405 | 133 |
| 70 | 4.82 | 2.616 | 2.371 | 1.895 | 1.643 | 1.485 | 1459 | 138 |
| 75 | 5.17 | 2.676 | 2.431 | 1.955 | 1.703 | 1.545 | 1510 | 143 |
| 80 | 5.51 | 2.731 | 2.486 | 2.010 | 1.758 | 1.600 | 1559 | 148 |
| 85 | 5.86 | 2.781 | 2.536 | 2.060 | 1.808 | 1.650 | 1607 | 152 |

