

Have fun in your garage!®

Safety Data Sheet

Complete Polish

	SECTION 1: PRODUCT AND COMPANY INFORMATION
Product Identifiers Name Number Brand Product Use Supplier Name Address Telephone Emergency Phone	Complete Polish 10876, 99597 Griot's Garage Defect and Scratch Removal
Prepared/Revised	SECTION 2: MAZARD IDENTIFICATION
Classification of the su	SECTION 2: HAZARD IDENTIFICATION
Physical Hazards Health Hazards Environmental Hazards Precautionary Stateme Label Elements Signal Word Prevention Response Storage Disposal Hazards not otherwise	Flammable Liquids (Category 4), Combustible liquid. Not Classified ents and Label Elements None WARNING Keep away from heat, sparks, open flames and hot surfaces. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use dry chemical, foam or water fog to extinguish. Do not use direct water stream. Store in a well-ventilated place. Dispose of container or contents in accordance with all regulations. e classified (HNOC) or not covered by GHS HMIS Rating: Health hazard: 0 Chronic Health Hazard: 0 Flammability: 1 Physical Hazard 0 NFPA Rating: Health hazard: 0 Fire Hazard: 1 Reactivity Hazard: 0
Supplemental Informa	see Section 16 for alphanumeric H-Statements and P-Statements.
	SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS
This composition consists o	Component stillates (Hydrotreated Middle)CAS No. 64742-46-7EC-No. 265-148-2% Wt. 8-12f a combination of ingredients. The ones potentially contributing to classified hazards are reported above. The above r industrial hygiene and environmental purposes and are not intended to represent product specifications.The above above
	Section 4: First Aid Measures
Description of first aid General advice In case of eye contact In case of skin contact If inhaled If swallowed Most important sympt Indication of any imme	Move out of dangerous area. Consult a physician if you feel unwell. Show this safety data sheet to the doctor and first responders. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eve irritation persists, get medical advice/attention.
	Section 5: Firefighting Measures
Extinguishing Media Suitable Unsuitable Special hazards arising Advice for firefighters Further information	Use dry chemical, CO2, water spray (FOG) or foam. Avoid solid water stream as it may scatter and spread fire. <u>from the substance or mixture</u> Use water spray to cool fire exposed container surfaces and to protect personnel. Thermal decomposition can produce carbon monoxide (highly toxic) and carbon dioxide (an asphyxiate at sufficient concentrations). As in any fire, fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. (MSHA/NIOSH approved or equivalent). If employees are expected to fight fires, training and equipment information can be found in OSHA Fire Brigades Standard (29 CFR 1910.156).

Safety Data Sheet: Complete Polish SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions,	protective equipment and emergency procedures Use appropriate safety equipment. Keep unnecessary and unprotected personnel from entering the area. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. For large spills,
Environmental precaut	warn public of downwind explosion hazard. tions
Methods and materials	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. s for containment and cleaning up
Reference to other sec	Contain spilled material if possible. Collect in suitable and properly labeled containers. tions-resources
	For additional information, refer to Section 8: Exposure Controls and Personal Protection, Section 7: Handling, Section 12: Ecological Information, Section 13: Disposal Considerations and OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120).
	Section 7: Handling and Storage
Precautions for safe ha	undling
	Avoid contact with skin and eyes. Avoid inhalation of dust for dry products and vapor or mist for liquids. When product is flammable or combustible, keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. For precautions see Section 2.
Conditions for safe sto Specific end use	rage, including any incompatibilities Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. See Section 1.
Specific end use	
	SECTION 8: EXPOSURE CONTROL AND PERSONAL PROTECTION
Control parameters	Under normal conditions of use, no special precautions or control measures are required. If inhalation or skin and eye contact are possible, exposure limits determined by OSHA, ACGIH and NIOSH for components are provided. Limits are for air levels only. Skin contact can cause over
Component Exposure L	exposure even when limits are met. .imits
	<u>Distillates (Hydrotreated Light)</u> (64742-47-8): The following exposure limits are for Mineral Oil mist: OSHA: The legal airborne permissible exposure limit (PEL) is 5 mg/m3 averaged over an 8-hour work shift. NIOSH: The recommended airborne exposure limit is 5 mg/m3 averaged over a 10-hour work shift and 10 mg/m3, not to be exceeded during any 15-minute work period. ACGIH: The recommended airborne exposure limit is 5 mg/m3 (as the inhalable fraction) averaged over an 8-hour work shift.
Appropriate engineering	Where possible, enclose operations and use local exhaust ventilation at the site of chemical
Dennedanting	release. Maintain airborne levels below exposure limit requirements or guidelines. If local exhaust ventilation or enclosure is not used respirators should be worn. Wear protective work clothing. Facilities storing, packaging or utilizing product should be equipped with an eyewash and a safety shower facility. Wash thoroughly immediately after exposure, before breaks and the end of the work shift. Post hazard and warning information in the work area. In addition, as part of an ongoing education and training effort, communicate all information on the health and safety hazards to potentially exposed workers.
Personal protective eq	Safety glasses and chemical resistant gloves are recommended whenever chemicals are handled.
	Obtain detailed information from OSHA Personal Protective Equipment Standard (29 CFR 1910.132) and equipment suppliers.
Eye/face protection	Face shield and, or safety glasses are recommended where misting or splashing is a risk. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
Skin protection	Wear protective gloves/protective clothing. Dispose of contaminated gloves after use in accordance with applicable regulations and good practices. Wash and dry hands. Wash contaminated clothing and decontaminate shoes before reuse.
Respiratory protection	Use when overexposure potential. Improper use of respirators is dangerous. Respirators should only be used with a written program as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).
Control of environmen	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State: Creamy Liquid Color: White **Odor: Slightly Sweet** Odor Threshold: Not Determined pH: 8.5 - 9.0 Boiling Point/Range: Not Determined / Not Determined Freezing Point/Melting Point: Not Determined / Not Determined Flash Point: ≥147°F (≥64°C) Auto Ignition Temperature: Not Determined **Decomposition Temperature: Not Determined** Upper/Lower Flammability Limits: Not Determined Upper/Lower Explosive Limits: Not Determined Vapor Pressure (psi @100°F): Not Determined Vapor Density: >1 **Relative Density: Not Determined** Solubility (Water): Complete Partition Coefficient (n-octanol/water): Not Determined Specific Gravity: 1.01 Evaporation Rate (Butyl Acetate = 1): Not Determined Viscosity: 12,000 - 18,000 cPs Volatility: Not Determined

Physical Data is typical values based on material tested, but may vary based on composition. Values should not be accepted as guaranteed for every lot or as specifications for this product.

	Section 10. STABILITY AND REACTIVITY
Reactivity Chemical Stability	Does not react under normal conditions of use. Stable under normal conditions of use.
Stability/Incompatibili	
	Avoid contact with strong oxidizers.
Conditions to Avoid	None known.
Hazardous Reactions/	Decomposition Products
	Does not decompose under normal conditions; may produce CO, CO2, volatile hydrocarbons and
	other possibly toxic gases in fire.
	SECTION 11: TOXICOLOGICAL INFORMATION
	SECTION 11: TOXICOLOGICAL INFORMATION
Information on Toxica	
Information on Toxico	
Component toxicity	Distillates (Hydrotreated Light) (64742-47-8): LC50 Rat >5 mg/L (4 Hr. mist) - Oral LD50 Rat >15,000 mg/kg - Dermal LD50 Rabbit >5000 mg/kg.
Mixture toxicity	Skin corrosion/irritation – Inhalation - Serious eye damage/eye irritation - Respiratory or skin
WINCH E CONCILY	<u>sensitization - Germ cell mutagenicity - Reproductive toxicity - Specific target organ toxicity - single</u>
	<u>exposure</u> – Specific target organ toxicity - repeated exposure - <u>Aspiration</u> : All no data available.
	<u>Carcinogenicity</u> : No component of this product present at levels greater than or equal to 0.1% is
	classified as a carcinogen by the National Toxicology Program (NTP), the International Agency for
	Research on Cancer (IARC), or the Occupational Safety and Health Administration (OSHA).
Additional Information	
	SECTION 12: ECOLOGICAL INFORMATION
Component Etoxicity	Distillates (Hydrotreated Light) (64742-47-8): 96 hr. LL50 Fathead Minnow >100 mg/L 7 Day LL50
-	NOELR Trout >1000 mg/L 72 hr. EbL50 Scenedesmus subspicatus >50% % of WAF 21 Day WAF
	Daphnia magna >1000 mg/L
Mixture Etoxicity	Toxicity to Fish - Persistence and Biodegradability - Bioaccumulative Potential - Mobility in Soil:
	All no data available.
Other adverse effects	None known.

SECTION 13: DISPOSAL CONSIDERATION

Waste treatment methods

ProductContact a licensed professional waste disposal service to dispose of this material.Contaminated packagingEmpty containers should be taken to an approved waste handling site for recycling or disposal.
Since emptied containers may retain product residue, follow label warnings even after container
is emptied.

Consumer Package Exemption

§173.150 Exceptions for Class 3 (flammable and combustible liquids)

DOT: Not Regulated - IATA: Not Regulated - IMDG: Not Regulated

For Non-exempt Shipments

DOT	UN 1268 Proper shipping name Petroleum Distillates, n.o.s. Class / Division Combustible Liquid Packing group III Contains OIL This material is not regulated under 49 CFR if in a container of 119-gallon capacity or less. This material is an 'OIL' under 49 CFR Part 130 when transported in a container of 3500-gallon capacity or greater.
IMDG	This material is not classified as dangerous under IMDG regulations.
IATA	This material is not classified as dangerous under IATA regulations

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through a shipper authorized sales or customer service representative.

SECTION 15: REGULATORY INFORMATION		
Federal	<u>TSCA</u> : Components of this product are listed on the TSCA Inventory. <u>RCRA</u> : None of the ingredients are currently listed as a substance or a source waste under current regulations (40 CFR 261.31, 32 and 33). <u>CERCLA</u> : Product is not found in "List of Hazardous Substances and Reportable Quantities" (40 CFR 302.4) <u>SARA TITLE III</u> : (Superfund Amendments and Reauthorization Act) 302 Components: None are subject to the reporting requirements of Section 302.	
States	313 Components: None are subject to the reporting requirements of Section 313. 311/312 Hazards: None State Bight to Know Components: BA & NI: Distillatos (Hydrotroated Light) (64742-47-8) Minoral	
Sidles	<u>State Right to Know Components</u> : PA & NJ: Distillates (Hydrotreated Light) (64742-47-8) - Mineral Seal Oil (64742-46-7) - Polyoxyethylene Stearate (9004-99-3)	
Canada	<u>DSL</u> : Components of this product are listed on the Canadian Domestic Substances List. <u>WHMIS</u> : Distillates (Hydrotreated Light) - Mineral Seal Oil - Polyoxyethylene Stearate: Uncontrolled products according to WHMIS classification criteria.	

SECTION 16: OTHER INFORMATION

Full alphanumeric H-Statements and P-Statements

eric H-St	atements and P-Statements
	H227 Combustible liquid. Warning - None
	P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
	P280 Wear protective gloves/protective clothing/eye protection/face protection.
	P370+P378 In case of fire: Use dry chemical, foam or water fog to extinguish. Do not use direct
	water stream.
	P403 Store in a well-ventilated place.
	P501 Dispose of container or contents in accordance with all regulations.
	The data presented here relates only to the specific material designated herein and does not

Disclaimer The data presented here relates only to the specific material designated herein and does not relate to use in combination with any other materials or in any process. The information set forth above is based on technical data believed to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside our control, no warranties, expressed or implied are made, and no liability is assumed in connection with any use of this information. Judgments as to the suitability of this information for the user's purposes are necessarily the user's responsibility. Although reasonable care has been taken in the preparation of this information, no responsibility is assumed as to the accuracy or suitability of this information for its application to the users intended purpose or for consequences of its use.

Potential Health Effects

This product is a mixture for which no specific health hazard data exists. OSHA requires that one should assume such mixtures present the same health hazards as do any components present in amounts greater than 1% (0.1% for carcinogens). Consumers accessing our SDS information should keep in mind the information is presented in a format required by the U.S. Government's Occupational Safety and Health Administration (OSHA). We provide SDS as a service for our business customers. These industrial SDSs are not applicable to consumer use of these products. We thoroughly evaluate the safety aspects of all of our consumer products prior to their use in the home