

## **FEATURES & BENEFITS**

- 12 different selectable flash patterns in either of two phases, plus steady-on
- Extremely low current draw
- Durable polycarbonate twist on/off lens
- S-Link<sup>™</sup> System\* synchronizing capabilities with up to six other units (for hardwire models only). Allows for synchronization with other S-Link compatible products
- Circuit board is conformal coated to protect circuitry
- Durable, lightweight polycarbonate base, flange 3-hole permanent mount, 1" pipe mount, vacuum magnet mount with cig. plug (on/off and pattern select switch)
- 5 year warranty

PERMANENT MOUNT Voltage: 12 to 24 VDC Amp Draw: 0.5 amps @ 12 VDC VACUUM MAGNET Voltage: 12 VDC

Amp Draw: 0.5 amps @ 12 VDC

APPROVALS: SAE J845 CLASS I ● AMBER ○ WHITE SAE J845 CLASS II ● BLUE

PART#	DESCRIPTION	MOUNT	COLOR
SHORT LENS			
78031	LED Beacon, Class I, Short Lens	Permanent	O White
78041	LED Beacon, Class I, Short Lens	Vacuum Magnet	○ White
78033	LED Beacon, Class I, Short Lens	Permanent	Amber
78043	LED Beacon, Class I, Short Lens	Vacuum Magnet	Amber
78035	LED Beacon, Class II, Short Lens	Permanent	<ul><li>Blue</li></ul>
78045	LED Beacon, Class II, Short Lens	Vacuum Magnet	<ul><li>Blue</li></ul>
TALL LENS			
78051	LED Beacon, Class I, Tall Lens	Permanent	<ul><li>White</li></ul>
78053	LED Beacon, Class I, Tall Lens	Permanent	Amber
78055	LED Beacon, Class II, Tall Lens	Permanent	<ul><li>Blue</li></ul>
SERVICE PARTS			
98221	Replacement Short Lens		<ul><li>Clear</li></ul>
98223	Replacement Short Lens		<ul><li>Amber</li></ul>
98225	Replacement Short Lens		<ul><li>Blue</li></ul>
98171	Replacement Tall Lens		Clear
98173	Replacement Tall Lens		Amber
98175	Replacement Tall Lens		<ul><li>Blue</li></ul>
98470	Branch Guard (Low Profile)		
98460	Branch Guard (High Profile)		

S-Link is a Trademark of Star1889 Headlight & Lantern Co.





\*S-LINK TECHNOLOGY: S-Link System is a proprietary technology that will allow similar S-Link products to be synchronized. This would allow for a user to define the flash patterns on multiple devices for a customized, tailored look on a vehicle. Note: Only S-Link compatible products can be synchronized together. Refer to user installation manuals for details on S-Link Synchronization.

CONNECT & PROTECT