

NEW | Class II LED Beacon Medium Profile

►► NOW AVAILABLE!

This Class II beacon combines all the major benefits of the latest LED technology with a traditional, strobe style housing. Designed to provide optimal lighting where Class II light is required. Perfect for use in the agriculture, mining, towing, utility and construction industry. The unique flash pattern increases visibility to oncoming traffic. Available in permanent and vacuum mount options in 12 volt to 48 volt amperage.

LED technology benefits also include low power draw and reduced on-going maintenance costs and down time. Outfit your vehicle with these high quality and economical beacons!



FEATURES AND BENEFITS

- SAE J845 Class II
- 70 flash per minute
- Reinforced polypropylene base, polycarbonate lens
- Switched cigarette plug adapter (vacuum-magnet models)
- 12 to 48 VDC
- 2.5 AMPs
- Temperature Range: -22°F to +122°F (-30°C to +50°C)
- Dimensions: 5" (H) x 6.5" (Dia)

PART #	DESCRIPTION	VOLTAGE	AMPS	COLOUR
78853	LED BEACON MEDIUM PROFILE, PERMANENT MOUNT	12 – 48 V	2.5	AMBER
78855	LED BEACON MEDIUM PROFILE, PERMANENT MOUNT	12 – 48 V	2.5	BLUE
78863	LED BEACON MEDIUM PROFILE, VACUUM MOUNT	12 – 48 V	2.5	AMBER
78865	LED BEACON MEDIUM PROFILE, VACUUM MOUNT	12 – 48 V	2.5	BLUE