

Aerosol Metal, 11 oz. 078698219561

ELECTRIC MOTOR ENERGIZED ELECTRICAL CLEANER

NM11

A non-flammable, non-conductive, fast drying, solvent for dissolving and flushing away greases, oils, gummy residues, tar, etc. from energized electrical equipment. Leaves no residue. CLEANS & DEGREASES ENERGIZED COMPONENTS SUCH AS ELECTRIC MOTORS – GENERATORS – INSTRUMENTS – ELECTRICAL CONTROLS. CONTAINS NO CARBON TETRACHLORIDE, TRICHLOROETHYLENE, OR ACETONE. Professional Users must read the MSDS before using this product. Call 704-821-7643 or go to www.gunk.com for MSDS.

APPLICATIONS:

- Non-Flammable, Non-Conductive, Fast Drying
- · Dissolves Grease, Oil, Tar And Gum

DIRECTIONS: 1. Protect rubber and plastic parts from overspray. 2. For energized equipment use only. Not to be used for motorized vehicle maintenance or their parts. 3. Spray generously on equipment to be cleaned and allow dissolved contaminants to flow off. 4. Repeat process, if necessary. Keep can away from contact with electrical current or connections such as battery terminals because burn-through may occur. DO NOT SPRAY ON HOT METAL SURFACES LIKE GENERATOR EXHAUST PIPES.

STORAGE, HANDLING & DISPOSAL: Dispose of product residue, rinsate, and empty container in accordance with all local, state, and federal laws and regulations. Empty aerosol cans are recyclable: consult your local recycling authority. Emptied containers contain product residue, so follow all warnings, even after container is emptied.

DANGER: EXPLOSION HAZARD: Use only in a well-ventilated area away from heat, sparks, and flame. Do not place can on hot surfaces or in direct sunlight which could cause can to burst violently. Store in a dry, well-ventilated area below 120°F/49°C. Do not puncture, crush, or incinerate (burn) can. BREATHING & CONTACT HAZARDS: Do not breathe vapors. Use NIOSH-approved respirator. Use only in a well-ventilated area, and open doors and windows to prevent vapor buildup. INHALING CONCENTRATED VAPORS, INTENTIONALLY OR OTHERWISE, CAN CAUSE BRAIN AND PERMANENT ORGAN DAMAGE OR CAN BE FATAL. Avoid contact with eyes, skin, or clothing. Repeated contact may dry and defat the skin. Wear chemical-resistant goggles and solvent-proof gloves and apron. Remove contaminated clothing and wash before reuse. Remove contact lenses before use. Wash thoroughly after handling.

FIRST AID: EYE CONTACT: Flush thoroughly with water for 15 minutes while lifting eyelids occasionally and get prompt medical attention. SKIN CONTACT: Wash with soap and water. If irritation persists, get prompt medical attention. INHALATION: Move to fresh air. If breathing becomes difficult, get prompt medical attention. INGESTION: DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room immediately.

KEEP AWAY FROM CHILDREN AND ANIMALS WARNING: This product contains a chemical known to the State of California to cause cancer.

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.

