

Specification Sheet Product Name: Premium Exhaust Wrap

# **Section 1: Applications**

Cobra Skin exhaust wrap is used on exhaust pipes, mufflers, headers, manifolds, mufflers, DPFs. Suitable for use on automotive, motorcycle, genset, diesel, and marine applications.

## **Section 2: Features and Benefits**

Premium Exhaust Wrap offers superior insulating properties as well as low chloride content. Will resist most acids and alkalis and will remain unaffected by solvents and bleaches. Premium Exhaust Wrap is woven from multi-plied continuous filament fiberglass yarn providing superior strength and flexibility. A black high temperature treatment is applied to the Premium Exhaust Wrap to increase its temperature resistance to 1350°F. HPTC treatment not only increases temperature resistance but also provides high temperature flexibility and strength at top temperatures. Also improves abrasion resistance at high temperatures.

### **Section 3: Technical Data**

### **Temperature Parameters:**

Base Fabric Service: 1350°F Max Fabric Service: 2000°F <30 sec

### **Physical Characteristics**

Fiber content: **Texturized E-Glass** 

Weave: Plain

Thickness: **0.065**" (+/- **10%**) Widths: ½" – 6" Standard

Treatment: **HPTC coating**Color: **White or Black**Electrical: **Non Conductive**