

Section 1: Applications**Applications**

Electrical connectors, heat shield sleeves,

Section 2: Features and Benefits

The very flexible polyolefin tubing has a 3:1 shrink ratio and meets all AMS-DTL-23053/5C, UL and CSA specifications. HP Shrink is a great alternative to zip ties, tape, and provide a clean tight seal with a professional look. Sealing the ends of any heat shield sleeve, improves the efficiency and prevents hot air from working its way in between your hose or wire.

Section 3: Technical Data

| | |
|-------------------------------------|---|
| Base Material: | Polyolefin |
| Available Thicknesses: | .004" |
| Available ID's: | 1/2", 3/4", 1-1/2", 3" |
| Shrink Temperature (min): | 212°F (100°C) |
| Dielectric Strength (V-mil): | 700 |
| Volume Resistivity (ohm-cm): | 10 ¹⁵ |
| Chemical Resistance: | Resists most acids, alkalis and solvents except Hydrofluoric acid and hot phosphoric. |
| Applicable Specifications: | AMS-DTL-23053/5C, Class 1; UL File E-48398; CSA LR38227 |
| Sizes: | 1/2" id x 1" (P/N: 353010 & 353011) 3/4" id x 1-1/4" (P/N: 353014 & 353015) 1-1/2" id x 1-3/8" (P/N: 353018 & 353019) 3" id x 1-1/2" (P/N: 353022) |

