

HP Shrink™



1200°F
CONTINUOUS



2000°F
INTERMITTENT

HP Shrink is extra flexible and has a low shrink threshold making them ideal to seal off any high temperature sleeve! The very flexible polyolefin tubing has a 3:1 shrink ratio and meets all AMS-DTL-23053/5C, UL and CSA specifications. HP Shrink is a great alternative to zip ties, tape, and provide a clean tight seal with a professional look. Sealing the ends of any heat shield sleeve, improves the efficiency and prevents hot air from working its way in between your hose or wire. We offer them in black with yellow logo in diameters of 1/2, 3/4, 1-1/2, and 3 inch to fit whatever you need. Shrink and seal your way to optimize your heat sleeve.

FEATURES

- Low shrink temperature threshold
- 3 to 1 shrink ratio
- Extra flexibility makes them easy to work with



HEAT SHIELD SLEEVING

PART NO.	DESCRIPTION
353010	1/2" id x 1" wide (10 pack)
353011	1/2" id x 1" wide (25 pack)
353014	3/4" id x 1-1/4" wide (8 pack)
353015	3/4" id x 1-1/4" wide (16 pack)
353018	1-1/2" id x 1-3/8" wide (4 pack)
353019	1-1/2" id x 1-3/8" wide (8 pack)
353022	3" id x 1-1/2" wide (4 pack)



Discover other performance oil filters & relocation kits on our website.