



HEININGER AUTOMOTIVE

Advantage
SportsRack®

Hitch Extension (for 2 x 2 Receiver Hitch)

Instructions for use

Contents:

1-Hitch Extension Assembly (includes anti-wobble device)

1-Receiver Hitch bolt (5/8" x 1.5")

1-Receiver Bolt Lock Washer

Precautions:

- **This product is NOT to be used for TOWING of anything, in any way!**
- The unit is quite heavy for its size, please handle with caution.
- When not in use it is advised to remove the Hitch Extension from the vehicle and store in a sheltered/dry location, or the vehicle (securely) until use is necessary.

Installation:

- Once removed from the carton, insert the Hitch Extension into the 2" x 2" receiver until the holes in the Hitch Extension and hitch line up. There are two holes in the Hitch Extension available for this. Use the hole that allows for as little leverage on the Hitch Extension as is possible.
- After aligning the holes, place the washer on the bolt and thread the bolt into the unit (inside the blue nut retainer) and then tighten with a proper wrench to insure the bolt is very tight and secure. This is very important. Finger-tight is not adequate. Note there is a blue nut retainer noted. This is the anti-wobble device and it can be positioned to either hole in the Hitch Extension.
- After tightening the receiver hitch bolt, insert the bike, motorcycle or cargo carrier into the Hitch Extension and align the holes similarly to the previous method. Insert your pin or bolt and tighten as noted above. If you have an Advantage® Sports Rack, there is an anti-wobble device in it most likely. Be sure to use the hole where the blue nut retainer and the nut are aligned with the hole in the larger end of the Hitch Extension.