

## CARE AND USE INSTRUCTIONS

Thank you for selecting a WeatherBeater® Floor Liner from Winfield Consumer Products. Your new front floor liners are custom molded to fit your Honda Accord Sedan (4-Doors). The liners are made to take the place of your factory floor mats. *For correct fit, it is necessary to remove the factory floor mats before installing your new floor liners*. However, do not remove the factory-installed carpeting.

Your liners are made from an engineering resin that is lightweight and extremely tough and durable. The easiest way to clean your liners is with a damp cloth or sponge. If using a cleaner, 409<sup>®</sup> or Glass Plus<sup>®</sup> work well. Use of Armor All<sup>®</sup>, Son-of-a-Gun<sup>®</sup> or similar items is discouraged as these products make the liners slick.

## INSTALLATION INSTRUCTIONS FOR YOUR HONDA ACCORD FRONT FLOOR LINERS







RIGHT OR PASSENGER'S SIDE

YOUR ACCORD LINERS ATTACH TO THE FACTORY "TWIST LOCK" FASTENERS. YOU MUST REMOVE THE FACTORY MATS BEFORE INSTALLING YOUR ACCORD LINERS. MAKE SURE YOUR LINERS ARE SECURED TO THE TWIST-LOCK FASTENERS BEFORE OPERATING THE VEHICLE.




## CARE AND USE INSTRUCTIONS

Thank you for selecting a WeatherBeater® Floor Liner from Winfield Consumer Products. Your new rear floor liners are custom molded to fit your Honda Accord Sedan (4-Doors). The liners are made to take the place of your factory floor mats. *For correct fit, it is necessary to remove the factory floor mat before installing your new floor liners*. However, do not remove the factory-installed carpeting.

Your liners are made from an engineering resin that is lightweight and extremely tough and durable. The easiest way to clean your liners is with a damp cloth or sponge. If using a cleaner, 409<sup>®</sup> or Glass Plus<sup>®</sup> work well. Use of Armor All<sup>®</sup>, Son-of-a-Gun<sup>®</sup> or similar items is discouraged as these products make the liners slick.

## INSTALLATION INSTRUCTIONS FOR YOUR HONDA ACCORD REAR SEAT FLOOR LINER



TO EASE INSTALLATION OF YOUR 2<sup>nd</sup> SEAT ACCORD SEDAN FLOOR LINER, FIRST MOVE THE FRONT SEATS TO THEIR MOST FORWARD POSITIONS. WITH THIS DONE, INSERT LINER IN VEHICLE, POSITIONING IT AS SHOWN ABOVE. YOU CAN THEN REPOSITION THE FRONT SEATS AS DESIRED.