


THANK YOU FOR SELECTING A HUSKY FLOOR LINER FROM WINFIELD CONSUMER PRODUCTS

CARE AND USE INSTRUCTIONS

Your new liner is custom molded to fit your vehicle. Upon removal from the box your liner will not completely unroll and lay flat. This is normal and only temporary. Just place the liner on the floor or in the back of your vehicle with a weight in each corner (a book works well). After about 15 minutes, your liner will remain flat. In colder climates this “relaxing” may take longer; moving the liner to a heated area will accelerate the process.

Your liner is manufactured using an engineering resin that is lightweight and extremely tough and durable. The easiest way to clean your liner is with a damp cloth or sponge. If using a cleaner, 409[®] or Glass Plus[®] work well. Use of Armor All[®], Son-of-a-Gun[®] or similar items is discouraged as these products make the liner slick.

INSTALLATION INSTRUCTIONS FOR YOUR TOYOTA SEQUOIA CARGO LINER



TO ACCESS THE FACTORY CARGO HOOK TIE DOWN LOCATIONS WITH YOUR CARGO LINER IN PLACE YOU MUST FIRST MAKE A SLIT IN THE FOUR (4) RAISED AREAS ON YOUR LINER (SHOWN CIRCLED). THEN, PUSH THE HOOK RINGS UP THROUGH THE LINER.

PHOTOS OF THE TOYOTA SEQUOIA CARGO LINER #2555
TRIMMED FOR USE WITH THE THIRD SEATS—RECESSED
AREAS TRIMMED AWAY TO ACCESS SEAT MOUNTS

