Dublished and patent pending2010-2015Audi B8 & B8.5 S43.0L TFSI Supercharged1-1 pc. Short Ram Intake system with MR TechnologyPlease check the contents of this box immediately. Please check the contents of this product from.1-Bracket Extension 1-Heat shield cover 1-3.5" Injen dry filter1-3.5" Injen dry filter 1-3" Hump hose 2-Power Bands #0482-Power Bands #048 1-M6 vibramount 1-M6 flange nut 2-Corse cover screws 1-8 Rubber trim@9.5"L 1-1/4" coupler1-4 page instruction1-4 page instruction1-4 page instruction2-Power Bands #0481-4 page instruction2-Power Bands #0482-Power Bands #0482-Fonder washer 2-Power Bands #0482-Power Bands #0483-Rubber trim@9.5"L3-Rubber trim@9.5"L3-Rubber trim@9.5"L3-Rubber trim@9.5"L4-Poage instruction3-Poage instruction3-Poage instruction3-Poage instruction3-Poage instruct	Part number SP3081	Warning: Manufactures attempting to duplicate Injen's patented process will now face legal action. MR Technology Step down process: 1- Calibration Method for Air Intake Tracts for Internal Combustion Engines. Covered under Patent# 7,359,795 2- Calibration Device for Air Intake Tracts for Internal Combustion Engines. Published and patent pending 3- Calibration Method and Device for Air Intake Tracts having Air Fusion Inserts
Audi B8 & B8.5 S4 3.0L TFSI Supercharged1-1 pc. Short Ram Intake system with MR TechnologyPlease check the contents of this box immediately. Please check the contents of this box immediately. Report any defective or missing parts to the Authorized Injen Technology dealer you purchased this product from. Before installing any parts of this system, please read the instructions thoroughly. If you have any questions regarding installation please contact the dealer you purchased this product from. Installation DOES require some mechanical skills. A qualified mechanic is always recommended. *Do not attempt to install the intake system while the engine is hot. The installation may require removal of radiator fluid line that may be hot. Injen dry filter (#6020) Power Bands #048 (#4004) *Do not attempt to install the intake system while the engine is hot. The installation may require removal of radiator fluid line that may be hot. Injen Technology offers a limited lifetime warranty to the original purchased. Injen Technology 244 Pioneer Place Pomona, CA 91768 USA 		Published and patent pending
 3.0L TFSI Supercharged 1 pc. Short Ram Intake system with MR Technology Bracket Extension (#20118) Heat shield cover (#11082) 3.5" Injen dry filter (#1021) 3" Hump hose (#3033) Power Bands #048 (#4004) M6 vibramount (#6020) M6 flange nut (#6020) Fender washer (#6010) Fender washer (#6010) Rubber trim@9.5"L (#6058) Rubber trim@9.5"L (#6058) 8mm hose@2.5"L (#3091) 1/4" coupler (#8008) 4 page instruction Mote: Injen strongly recommends that this system be installed by a 		Congratulations! You have just purchased the best engineered,
 1 pc. Short Ram Intake system with MR Technology Bracket Extension (#20118) Heat shield cover (#11082) 3.5" Injen dry filter (#1021) 3.5" Injen dry filter (#1021) 3.5" Hump hose (#3033) Power Bands #048 (#4004) M6 vibramount (#6020) M6 flange nut (#6020) Fender washer (#6010) Corse cover screws (#6093) Rubber trim@9.5"L (#6058) 8mm hose@2.5"L (#3091) 1/4" coupler (#8008) 4 page instruction Keport any defective or missing parts to the Authorized Injen Technology dealer you purchased this product from. Before installing any parts of this system, please read the instructions thoroughly. If you have any questions regarding installation please contact the dealer you purchased this product from. Installation DOES require some mechanical skills. A qualified mechanic is always recommended. *Do not attempt to install the intake system while the engine is hot. Injen Technology offers a limited lifetime warranty to the original purchaser against defects in materials and workmanship. Warranty claims must be handled through the dealer from which the item was purchased. Injen Technology 244 Pioneer Place Pomona, CA 91768 USA Please check the contents of this box immediately. Note: This intake system was Dyno-tested with an Injen filter and Injen parts. The use of any other filter or part will void the warranty and CARB exemption number. 		
with MR Technology1- Bracket Extension(#20118)1- Heat shield cover(#11082)1- 3.5" Injen dry filter(#1021)1- 3.5" Injen dry filter(#1021)1- 3" Hump hose(#3033)2- Power Bands #048(#4004)1- M6 vibramount(#6020)1- Fender washer(#6020)1- Rubber trim@9.5"L(#6010)2- Rubber trim@9.5"L(#6010)1- Rubber trim@9.5"L(#6030)1- 4 page instruction(#8008)1- 4 page instruction(#8008)		, , , , , , , , , , , , , , , , , , , ,
1- Bracket Extension (#20118) 1- Heat shield cover (#1082) 1- 3.5" Injen dry filter (#1021) 1- 3.5" Hump hose (#3033) 2- Power Bands #048 (#4004) 1- M6 vibramount (#6020) 1- Fender washer (#6010) 2- Rubber trim@9.5"L (#6073) 1- Rubber trim@9.5"L (#6088) 1- 1/4" coupler (#8008) 1- 4 page instruction (#8008) 1- 4 page instruction .		
 Heat shield cover (#1082) Heat shield cover (#11082) 3.5" Injen dry filter (#1021) 3" Hump hose (#3033) Power Bands #048 (#4004) M6 vibramount (#6020) M6 flange nut (#6020) Fender washer (#6010) Corse cover screws (#6093) Rubber trim@9.5"L (#6058) 8mm hose@2.5"L (#3091) 1/4" coupler (#8008) 4 page instruction Water and the strengty recommends that this system be installed by a 	•.	
 1- Heat shield cover (#11082) 1- 3.5" Injen dry filter (#1021) 1- 3" Hump hose (#3033) 2- Power Bands #048 (#4004) 1- M6 vibramount (#6020) 1- M6 flange nut (#6020) 1- Fender washer (#6010) 5- Corse cover screws (#6010) 1- Rubber trim@9.5"L (#6058) 1- 8mm hose@2.5"L (#3091) 1- 1/4" coupler (#8008) 1- 4 page instruction (#8008) 1- 4 page instruction (#102) Contact the dealer you purchased this product from. Installation DOES require some mechanical skills. A qualified mechanic is always recommended. *Do not attempt to install the intake system while the engine is hot. The installation may require removal of radiator fluid line that may be hot. Injen Technology offers a limited lifetime warranty to the original purchaser against defects in materials and workmanship. Warranty claims must be handled through the dealer from which the item was purchased. Injen Technology 244 Pioneer Place Pomona, CA 91768 USA Please check the contents of this box immediately. Note: This intake system was Dyno-tested with an Injen filter and Injen parts. The use of any other filter or part will void the warranty and CARB exemption number. 		there used in the second s
 1- 3.5" Injen dry filter (#1021) 1- 3" Hump hose (#3033) 2- Power Bands #048 (#4004) 1- M6 vibramount (#6020) 1- M6 flange nut (#6020) 1- Fender washer (#6010) 5- Corse cover screws (#6093) 1- Rubber trim@9.5"L (#6058) 1- 8mm hose@2.5"L (#3091) 1- 1/4" coupler (#8008) 1- 4 page instruction (#8008) 1- 4 page instruction (#8008) 1- 4 page instruction (#1021) Installation DOES require some mechanical skills. A qualified mechanic is always recommended. *Do not attempt to install the intake system while the engine is hot. The installation may require removal of radiator fluid line that may be hot. Injen Technology offers a limited lifetime warranty to the original purchaser against defects in materials and workmanship. Warranty claims must be handled through the dealer from which the item was purchased. Injen Technology 244 Pioneer Place Pomona, CA 91768 USA Please check the contents of this box immediately. Note: This intake system was Dyno-tested with an Injen filter and Injen parts. The use of any other filter or part will void the warranty and CARB exemption number. 		contact the dealer you purchased this product from.
 2- Power Bands #048 (#4004) 1- M6 vibramount (#6020) 1- M6 flange nut (#6020) 1- Fender washer (#6010) 5- Corse cover screws (#6093) 1- Rubber trim@9.5"L (#6058) 1- 8mm hose@2.5"L (#3091) 1- 1/4" coupler (#8008) 1- 4 page instruction (#8008) <l< td=""><td></td><td>Installation DOES require some mechanical skills. A qualified</td></l<>		Installation DOES require some mechanical skills. A qualified
 1- M6 vibramount (# 6020) 1- M6 flange nut (# 6020) 1- Fender washer (# 6010) 5- Corse cover screws (# 6093) 1- Rubber trim@9.5"L (# 6058) 1- 8mm hose@2.5"L (# 3091) 1- 1/4" coupler (# 8008) 1- 4 page instruction (# 8008) 1- 4 page instruction (# 8008) 1- 4 page instruction (# 8008) 		
 I- M6 flange nut I- M6 flange nut I- Fender washer I- Fender washer I- Rubber trim@9.5"L I- Rubber trim@9.5"L I- 8mm hose@2.5"L I- 1/4" coupler I- 4 page instruction I- 4 page instruction<!--</td--><td>· · · · · · · · · · · · · · · · · · ·</td><td></td>	· · · · · · · · · · · · · · · · · · ·	
 1- M6 flange nuf (#6002) 1- Fender washer (#6010) 5- Corse cover screws (#6093) 1- Rubber trim@9.5"L (#6058) 1- 8mm hose@2.5"L (#3091) 1- 1/4" coupler (#8008) 1- 4 page instruction (#8008) 1- 4 page instruction (#8008) 1- 4 page instruction (#8008) 1- 6 page instruction (#8008) 1- 7 page instruction (#8008) 1- 8 page instruction (#8008) 1- 9 page instruction (#8008) 1- 1/4" coupler (#808) 1- 1/4" coupler (#808)<!--</td--><td>1- M6 vibramount (#6020)</td><td></td>	1- M6 vibramount (#6020)	
 Fender washer (#6010) Corse cover screws (#6093) Rubber trim@9.5"L (#6058) 8mm hose@2.5"L (#3091) 1/4" coupler (#8008) 4 page instruction (#8008) Mote: This intake system was Dyno-tested with an Injen filter and Injen parts. The use of any other filter or part will void the warranty and CARB exemption number. Note: Injen strongly recommends that this system be installed by a 	1- M6 flange nut (#6002)	
 5- Corse cover screws (#6093) 1- Rubber trim@9.5"L (#6058) 1- 8mm hose@2.5"L (#3091) 1- 1/4" coupler (#8008) 1- 4 page instruction (#8008) 1- 4 page instruction (#8008) 1- 6 page instruction (#8008) 1- 7 page instruction (#8008) 1- 8 page instruction (#8008) 1- 9 page instruction (#8008) 1- 1/4" coupler (#8008) 1- 4 page instruction (#8008)	1- Fender washer (#6010)	
 1- 8mm hose@2.5"L (#3091) 1- 1/4" coupler (#8008) 1- 4 page instruction Injen Technology 244 Pioneer Place Pomona, CA 91768 USA Please check the contents of this box immediately. Note: This intake system was Dyno-tested with an Injen filter and Injen parts. The use of any other filter or part will void the warranty and CARB exemption number. Note: Injen strongly recommends that this system be installed by a 	5- Corse cover screws (#6093)	
1- 1/4" coupler (#8008) 1- 4 page instruction (#8008) Note: This intake system was Dyno-tested with an Injen filter and Injen parts. The use of any other filter or part will void the warranty and CARB exemption number. Note: Injen strongly recommends that this system be installed by a	1- Rubber trim@9.5"L (#6058)	
1- 1/4" COUPLER (#8008) 1- 4 page instruction Note: This intake system was Dyno-tested with an Injen filter and Injen parts. The use of any other filter or part will void the warranty and CARB exemption number. Note: Injen strongly recommends that this system be installed by a	1- 8mm hose@2.5"L (#3091)	
1- 4 page instruction Note: This make system was byno-tested with an injen inter and Injen parts. The use of any other filter or part will void the warranty and CARB exemption number. Note: Injen strongly recommends that this system be installed by a	· · · · · · · · · · · · · · · · · · ·	Please check the contents of this box immediately.
the warranty and CARB exemption number. Note: Injen strongly recommends that this system be installed by a	, , , , , , , , , , , , , , , , , , , ,	Inote. This make system was Dyno-tested with an injeri inter and
Note: Injen strongly recommends that this system be installed by a		
		Note: Inion strongly recommends that this system he installed by a
professional mechanic.		professional mechanic.



MR Technology

"The World's First Tuned air Intake System!" Factory safe air/fuel ratio's for Optimum performance Patent# 7,359,795

Now equipped with "Air Fusion" Patent pending "At Injen Technology, we didn't copy the step down process, we invented it!"







Figure 2



Stock box shown in this picture




Carefully pull back the vacuum line from the stock intake tube.



Loosen the clamp on the throttle body using 8mm nut driver.




Pull back the vacuum line from the intake tube.




Loosen all the screws holding in the upper part of the air box.




With all lines pulled away from the stock intake system, lift up and remove the stock intake system.




With provided coupler, connect to the 8mm hose. This will be an extension to the intake tube.



Now attach the coupler extension to the factory vacuum line. Install the 3" hump hose with clamps to the throttle body. Tighten the clamp on the throttle body only.



Now install the vibramount to the provided bracket insert. Secure and tighten




Locate on the strut tower the M6 thredded insert holding the A/C line. Attach the offset side of the bracket to the fitting. Do not tighten.



Install the air filter to the intake tube and tighten using 8mm nut driver.



Install the intake tube and position the intake system to the throttle body hose.



provided M6 fender washer and nut.



g Position for best fit, locate the natural position for the bracket to fit, check filter clearance. Tighten both nuts on brackets using 10mm socket or wrench.



Connect the vacuum line from step 9/10.



Rotate the intake system if needed for clearance of the filter. Position for the best fit and tighten using 8mm nut driver.



Attach the rubber trim to the edge of the cover.



Install the engine cover to the top of the air box, and secure using provided corse screws and tighten using T25 torx screw driver.



Position for the best possible fit and check for clearance. Re-adjust if necessary.



Congratulations! You have just completed the installation of this intake system. Periodically, check the alignment of the intake, normal wear and tear can cause nuts and bolts to come loose. <u>Note: Check clearance and adjust if needed!</u> <u>Failure to check the alignment and adjust the intake can cause damage that</u> <u>will void the warranty. Injen Technology is not responsible for any damages</u> <u>caused by/from improper installation.</u>

- 1. Upon completion of the installation, reconnect the negative battery terminal before you start the engine.
- 2. Align the entire intake system for the best possible fit. Once the intake has been properly fitted continue to tighten all nuts, bolts and clamps.
- **3.** Periodically, recheck the alignment of the intake system and make sure there is proper clearance around and along the length of the intake. Failure to follow proper mainentance procedures may cause damage to the intake and will void the warranty.
- 4. Start the engine and listen carefully for any odd noises, rattles and/or air leaks prior to taking it for a test drive. If any problems arise go back and check the vacuum lines, hoses and clamps that maybe causing leaks or rattles and correct the problem.
- 5. Check the filter for excessive dirt build up. Clean or replace the filter with an original Injen filter. Congratulations! You have just completed the installation of the best intake system sold on the market. Enjoy the added power and performance of your new intake system.