

287602

JET® JLP-A Series lever hoists combine safety, reliability, and durability that are designed to perform in light to medium-duty industrial applications. The patented Brake Wear Indicator increases safety by letting you know when to replace the friction disks. JET® also offers the option of shipyard hooks, virtually eliminating stretched hooks caused by point or tip loading. The JET® JLP-A lever hoist is available in ¼ ton to 6 ton capacities with standard lifts of 5, 10, 15, and 20 feet (custom lifts available). The JET® JLP-A Series is the perfect choice for a contractor grade lever hoist.

FEATURES

Safety

- NEW! Innovative brake wear indicator provides a visual indication when the friction disks are worn and need replacing
- NEW! JET's improved easy free chain design is a two-step, no load, free chaining system. The system permits quicker hoist positioning and take up of slack chain, and is engineered not to free chain under load
- The Weston style double ratchet pawl brake design splits the load to opposite sides of the ratchet gear for greater load security and increased safety
- Industrial rated alloy steel hooks rotate 360 degrees for easy rigging and slowly stretch to indicate an overload situation
- NEW! Redesigned ergonomic grip allows for greater operator control and increased comfort
- Durability
- Secured with Allen screws and lock nuts, the cast-steel safety latches are more durable than stamped steel latches and will not bend out of compliance with lifting regulations
- Optional Shipyard Hook are blunt tip hooks, designed for point loading and virtually eliminate stretched hooks, reducing downtime for maintenance and repair
- Grade 80 black oxide coated load chain for added durability
- Needle bearings support the load sheave to increase efficiency and promote smooth operation
- Impact resistant all steel construction for added durability and protection
- Standards
- This product complies with ANSI / ASME B30.21 and HST-3 Standards
- Load tested to 125% of capacity with certificate





STAND BEHIND YOUR WORK



287602

SPECIFICATIONS

Load Capacity (Tons)	6
Lift (Ft.)	15
Overload Protection	No
Ship Yard Hooks	No
Headroom (In.)	24-2/5
Handle Length (In.)	16-1/7
Lever Pull Force (LBF)	77
Lift per Turn (In.)	1/3
Number of Falls	2
Load Chain Dimensions (Mm.)	10 x 30
Hook Throat Opening (In.)	3
Overall Width (In.)	7-7/8
Weight (Lbs.)	84



STAND BEHIND YOUR WORK



287602

FULL SERIES

STOCK NO	MODEL NO	LOAD CAPACITY (TONS)	LIFT (FT.)	OVERLOAD PROTECTION	SHIP YARD HOOKS	HEADROOM (IN.)
287100	JLP-025A-5	1/4	5	No	No	8-1/4
287101	JLP-025A-10	1/4	10	No	No	8-1/4
287102	JLP-025A-15	1/4	15	No	Νο	8-1/4
287200	JLP-050A-5	1/2	5	No	No	10
287201	JLP-050A-10	1/2	10	No	No	10
287202	JLP-050A-15	1/2	15	No	No	10
287300	JLP-075A-5	3/4	5	No	No	12-4/5
287301	JLP-075A-10	3/4	10	No	No	12-4/5
287302	JLP-075A-15	3/4	15	No	No	12-4/5
287303	JLP-075A-20	3/4	20	No	No	12-4/5
287400	JLP-150A-5	1-1/2	5	No	No	15
287401	JLP-150A-10	1-1/2	10	No	No	15
287402	JLP-150A-15	1-1/2	15	No	No	15
287403	JLP-150A-20	1-1/2	20	No	No	15
287700	JLP-150A-5SH	1-1/2	5	No	Yes	15
287701	JLP-150A-10SH	1-1/2	10	No	Yes	15
287702	JLP-150A-15SH	1-1/2	15	No	Yes	15
287703	JLP-150A-20SH	1-1/2	20	No	Yes	15
287500	JLP-300A-5	3	5	No	No	18-8/9
287501	JLP-300A-10	3	10	No	No	18-8/9
287502	JLP-300A-15	3	15	No	No	18-8/9
287503	JLP-300A-20	3	20	No	No	18-8/9

STAND BEHIND YOUR WORK

)+ SERVICE CENTERS NATIONWIDE | INDUSTRY-LEADING WARRANTIES | EXPERT TECHNICAL SERV

287602

FULL SERIES

STOCK NO	MODEL NO	LOAD CAPACITY (TONS)	LIFT (FT.)	OVERLOAD PROTECTION	SHIP YARD HOOKS	HEADROOM (IN.)
287801	JLP-300A-10SH	3	10	No	Yes	18-8/9
287802	JLP-300A-15SH	3	15	No	Yes	18-8/9
287803	JLP-300A-20SH	3	20	No	Yes	18-8/9
287600	JLP-600A-5	6	5	No	No	24-2/5
287601	JLP-600A-10	6	10	Νο	Νο	24-2/5
287602	JLP-600A-15	6	15	No	No	24-2/5
287603	JLP-600A-20	6	20			24-2/5