




**PRODUCT INFORMATION**

<b>Description</b>	12-24V LED Work Light with Trapezoid Beam Pattern
<b>Height</b>	137.16 (mm) / 5.4 (in)
<b>Width</b>	144.27 (mm) / 5.68 (in)
<b>Depth</b>	66.04 (mm) / 2.6 (in)
<b>Shape</b>	Oval
<b>Outer Lens Material</b>	Polycarbonate
<b>Outer Lens Color</b>	Clear
<b>Housing Material</b>	Die-Cast Aluminum
<b>Housing Color</b>	Black
<b>Mounting Hardware Description</b>	(x1) 5/16"-18 x 0.58" Mounting Bolt
<b>Mounting Type</b>	Universal Pedestal Mount
<b>Minimum Operating Temperature</b>	-40 (°C) / -40 (°F)
<b>Maximum Operating Temperature</b>	65 (°C) / 149 (°F)
<b>Connector or Wiring</b>	Integrated 2-Pin Deutsch Weather-Proof Socket (DT04-2P)
<b>Mating Connector</b>	2-Pin Deutsch Weather-Proof Plug (DT06-2S)
<b>Product Weight</b>	1.55 (lbs) / 0.7 (kgs)
<b>Spec Sheet Printed</b>	2016-07-07

**PRODUCT DIMENSIONS**



**ELECTRICAL SPECIFICATIONS**

<b>Input Voltage</b>	12-24 V DC
<b>Operating Voltage</b>	10-36 V DC
<b>Red Wire</b>	Positive
<b>Black Wire</b>	Negative
<b>Current Draw</b>	3.50A @ 12V DC 1.75A @ 24V DC

**REGULATORY STANDARDS COMPLIANCE**




Buy America Standards  
IEC IP69K

Eco Friendly

**PHOTOMETRIC SPECIFICATIONS**

<b>Raw Lumen Output</b>	3,900
<b>Effective Lumen Output</b>	2,700
<b>Nominal LED Color Temperature</b>	5700 (K)
<b>Beam Pattern(s)</b>	Forward Lighting - Trapezoid



**APPLICATIONS**



**RELATED PRODUCTS**



[Part Number 1706571](#)

**12-24V LED Work Light  
with Spot Beam Pattern**



[Part Number 1706591](#)

**12-24V LED Work Light  
with Flood Beam Pattern**