

J.W. Speaker Model 735 High Output LEDs

Light Upgrade Package

Included in this kit:

(2) J.W. Speaker Model 735 LED lamps (Trap or Flood Lens)(2) Jumper Wire Harnesses(4) Plastic Spacer Washers



Lamps by position:

- A Flood
- B Flood (If combine outfitted with factor HID option, this is HID)
- C Trap
- C Trap
- B Flood (If combine outfitted with factory HID option, this is HID)
- A Flood

Installation Procedures:

- 1. Disconnect wire harness from bulb.
- 2. Remove lamp from combine by removing (2) 13mm hex head mounting bolts.





3. Remove bracket from lamp with ½" wrench.





4. Reusing bracket, bolt, washer, and nut... reconstruct bracket assembly on new Model 735 LED lamp. Also use 2 additional new plastic spacer washers (included in upgrade kit). Assemble as per picture.



5. Attach jumper wire harness (included in upgrade kit) to vehicle wire harness.





6. Attach LED lamp to combine, use previously installed 13mm hex head mounting bolts.



7. Plug other end of jumper wire harness into back of new LED lamp.



8. Power on your lights to confirm operation.



9. Adjust lamp as necessary.



10. Repeat steps 1-9 for remaining lights you are swapping out. Remember to account for trap and flood position, per the diagram at the start of these instructions.