



SAFETY DATA SHEET

1. Identification

| | |
|-------------------------------|---|
| Product identifier | <u>Trans-X® Posi Trac® Limited Slip Gear Oil Additive</u> |
| Other means of identification | |
| Product code | 402508 |
| Recommended use | Gear oil additive |
| Recommended restrictions | None known. |

2. Hazard(s) identification

| | |
|-----------------------|--|
| Physical hazards | Not classified. |
| Health hazards | Not classified. |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard Category 3 Hazardous to the aquatic environment, long-term hazard Category 3 |
| OSHA defined hazards | Not classified. |

Label elements



| | |
|---|---|
| Signal word | Danger |
| Hazard statement | Harmful to aquatic life. Harmful to aquatic life with long lasting effects. |
| Precautionary statement | |
| Prevention | Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Avoid release to the environment. |
| Response | Wash hands after handling. |
| Storage | Store away from incompatible materials. |
| Disposal | Dispose of contents/container in accordance with local/regional/national regulations. |
| Hazard(s) not otherwise classified (HNOC) | None known. |

Supplemental information

40.5% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 40.5% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|---------|
| Distillates (petroleum), hydrotreated heavy naphthenic | | 64742-52-5 | 70 - 80 |
| Methanol | | 67-56-1 | < 0.2 |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|---|
| Inhalation | If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist. |
| Skin contact | Rinse skin with water/shower. Get medical attention if irritation develops and persists. |
| Eye contact | Rinse with water. Get medical attention if irritation develops and persists. |
| Ingestion | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Most important symptoms/effects, acute and delayed | Direct contact with eyes may cause temporary irritation. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire-fighting equipment/instructions | Move containers from fire area if you can do so without risk. |
| General fire hazards | No unusual fire or explosion hazards noted. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. |
| Environmental precautions | Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. |

7. Handling and storage

| | |
|---|--|
| Precautions for safe handling | Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Use care in handling/storage. For product usage instructions, please see the product label. |
| Conditions for safe storage, including any incompatibilities | Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---|------|-----------------------------------|-------|
| Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) | PEL | 5 mg/m ³ | Mist. |
| | | 2000 mg/m ³ 500 ppm | |
| Methanol (CAS 67-56-1) | PEL | 260 mg/m ³ | |
| | | 200 ppm | |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---|------|---------------------|---------------------|
| Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) | TWA | 5 mg/m ³ | Inhalable fraction. |
| | | | |
| Methanol (CAS 67-56-1) | STEL | 250 ppm | |
| | TWA | 200 ppm | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|---|---------|----------------------------------|-------|
| Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) | Ceiling | 1800 mg/m ³ | |
| | STEL | 10 mg/m ³ | Mist. |
| | TWA | 5 mg/m ³ | Mist. |
| Methanol (CAS 67-56-1) | STEL | 325 mg/m ³ | |
| | | 250 ppm | |
| | TWA | 260 mg/m ³ 200 ppm | |

Biological limit values

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|------------------------|---------|-------------|----------|---------------|
| Methanol (CAS 67-56-1) | 15 mg/l | Methanol | Urine | * |

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Methanol (CAS 67-56-1) Skin designation applies.

US - Tennessee OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile.

| | |
|---------------------------------------|--|
| Other | Wear suitable protective clothing. |
| Respiratory protection | If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

Appearance

| | |
|---|--------------------------------------|
| Physical state | Liquid. |
| Form | Liquid. |
| Color | Dark amber. |
| Odor | Mild petroleum. |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | -40 °F (-40 °C) estimated |
| Initial boiling point and boiling range | 620.6 °F (327 °C) estimated |
| Flash point | > 300 °F (> 148.9 °C) Tag Closed Cup |
| Evaporation rate | Slow. |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | 7.3 % estimated |
| Flammability limit - upper (%) | 36 % estimated |
| Vapor pressure | 3.8 hPa estimated |
| Vapor density | > 1 (air = 1) |
| Relative density | 0.9 |
| Solubility (water) | Negligible. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 500 °F (260 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity (kinematic) | Not available. |
| Percent volatile | 73.3 % estimated |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | Prolonged inhalation may be harmful. |
| Skin contact | Prolonged skin contact may cause temporary irritation. |

| | |
|---|--|
| Eye contact | Direct contact with eyes may cause temporary irritation. |
| Ingestion | May cause stomach ache or discomfort. |
| Symptoms related to the physical, chemical and toxicological characteristics | Not available. |

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

| Product | Species | Test Results |
|--|---------|----------------------|
| Trans-X® Posi Trac® Limited Slip Gear Oil Additive | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 3361 mg/kg estimated |
| Oral | | |
| LD50 | Rat | 5000 mg/kg estimated |

* Estimates for product may be based on additional component data not shown.

| | |
|---|---|
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. |
| Respiratory sensitization | Not a respiratory sensitizer. |
| Skin sensitization | This product is not expected to cause skin sensitization. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Carcinogenicity | This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. |
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. |
| Specific target organ toxicity - single exposure | Not classified. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Based on available data, the classification criteria are not met. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. |

12. Ecological information

| Product | Species | Test Results |
|---|---------|---|
| Ecotoxicity Harmful to aquatic life with long lasting effects. | | |
| Trans-X® Posi Trac® Limited Slip Gear Oil Additive | | |
| Aquatic | | |
| Crustacea | EC50 | Daphnia 3055.3831 mg/l, 48 hours estimated |
| <i>Acute</i> | | |
| Fish | LC50 | Fish 168.0672 mg/l, 96 hours estimated |
| Components | | |
| Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Fish | LC50 | Fathead minnow (Pimephales promelas) > 30000 mg/l |
| Methanol (CAS 67-56-1) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) > 10000 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Methanol

-0.77

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code

Not regulated.

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

Food and Drug Administration (FDA)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Section 311/312****Hazard categories**Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No**SARA 302 Extremely hazardous substance**

No

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
Methanol (CAS 67-56-1)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. New Jersey Worker and Community Right-to-Know Act

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)
Methanol (CAS 67-56-1)

US. Massachusetts RTK - Substance List

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Methanol (CAS 67-56-1)

US. Rhode Island RTK

None.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Cyanide (CAS 57-12-5) Listed: July 5, 2013

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 51.100(s)) < 80 %

Consumer products (40 CFR 59, Subpt. C) Not regulated

State

Consumer products Not regulated

VOC content (CA) < 40 %

VOC content (OTC) < 40 %

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|--------------------|-------------|
| Issue date | 06-01-2015 |
| Prepared by | Allison Cho |
| Version # | 01 |

Further information

CRC # 914A

HMIS® ratings

Health: 1
Flammability: 1
Physical hazard: 1
Personal protection: B

NFPA ratings

Health: 1
Flammability: 1
Instability: 1

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.