

GRAVITY LED DAYLIGHTER



6" GRAVITY LED DAYLIGHTER

LIGITIEN

FEATURES

- Two Models Available:
 - SAE/ECE CERTIFIED STREET LEGAL Gravity LED

Driving Beam - #652-#653:

Each Light Rated at: 20-Watt; 2,104 Lumens;

1,310 LUX @ 10 Meters; 131,000 Candela

• Gravity LED Spot Beam - #650-#651:

Each Light Rated at: 20-Watt; 2,452 Lumens;

2,150 LUX @ 10 Meters; 215,000 Candela

- Patented Gravity Reflective Diode (GRD) technology yields more controlled and farther reaching light beams
- Available in both Black Powder Coated or Stainless Steel housing
- LED Color Temperature: 5,000K
- 9V to 32V, EMI DO 160E Compliant
- Hard Coated Polycarbonate Lens
- IP 68 Rated, fully self contained and sealed LED reflector housing
- Comes with 2 "KC Daylighter" light guards
- Package comes complete with pre-terminated, weatherproof, sealed 2-pin Deutsch connector wiring harness and 30 Amp illuminated switch with switch panel.

PHOTOMETRICS 20M OT BEAM PATTERN 10M o 2,150 lx 10M 20M 10M 50M 100M 150M 20M **DRIVING BEAM PATTERN** 10M o 1,310 lx 10M SAE/ECE STREET LEGAL 20M 10M 100M 150M **50M PERFORMANCE VALUES** 2.150 LX 1.310 LX 2.452 LM 2.104 LM **SPOT DRIVING DIMENSIONS** 5.38" 6.22

KC 6" Gravity LED Daylighter

Pair Pack Part No.	Single Light Part No.	Model / Description	Beam Pattern	Beam Distance (m)	Watts	Volts	Lumens	Width	Height	Depth
650	1650	6" Gravity/Stainless Steel	Spot	927	20	9 - 32	2,452	6.22"	8.42"	5.38"
651	1651	6" Gravity/Blk Powder	Spot	927	20	9 - 32	2,452	6.22"	8.42"	5.38"
652	1652	6" Gravity/Stainless Steel	Driving	724	20	9 - 32	2,104	6.22"	8.42"	5.38"
653	1653	6" Gravity/Blk Powder	Driving	724	20	9 - 32	2,104	6.22"	8.42"	5.38"