## Pro 5 MP Fire Extinguisher

Part number 466112 Multipurpose use

### Rechargeable

### UL Rated 3-A, 40-B:C



### Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Pro 5 MP unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough metal valve assembly.

Also available: 46611201 with Metal Strap Bracket.

### At a Glance

- Model Pro 5 MP
- Multipurpose Dry Chemical
- UL listed
- UL rated 3-A, 40-B:C
- Supplied with wall hanger
- 6 year limited warranty
- Suitable for use on most





- Monoammonium Phosphate

# common fires

### **Features**

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 5.5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection
- U.S.C.G. approved bracket part number 466400



Pt # 466112 - 4 pack UPC: 0-47871-66112-0 I2F - 20047871661125

### Packaging Options



# **Product Specification**

For use on the following

types of fire:

Troduct Specification	
Net agent weight (Average)	5.5 lb.
Unit weight (Average)	9.0 lb.
Diameter	4.5 inches
Height	16.31 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Metal
Strap Bracket	U.S.C.G approved

### Packaging dimensions (inches)

	Depth	Width	Height
Carton	4.75	6.0	17.0
Master Pack	13.0	17.25	9.87

