

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modifications will be required. However, the following procedures MUST be followed to ensure the proper fit and seal of the K&N Filter.

INSTALLATION

- 1. Locate and remove two screws which secure the stock intake tube. Remove stock intake tube. (Fig.1.)
- Locate and unlatch two clips which are located at the top of the vehicle's air box. Remove the factory air box base, then, remove the stock air filter. (Fig.2)
- 3. Place the K&N air filter into the base of the airbox. If properly positioned, the two tabs on the K&N air filter will be at rest inside the two tabs in the air box.
- 4. Verify air filter was placed correctly into the air box. (Fig. 3.)
- 5. Re-install the air box base and secure by relatching the clips that were unlatched in step two.
- 6. Re-install the stock intake tube and secure with the two screws that were removed in step one.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED; OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1








Fig. 3

Learn more about performance air intake systems we have.