



INSTALLATION INSTRUCTIONS

Part Number: VF2049

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

K&N® Cabin Air Filters replace your vehicle's stock cabin filter with a reusable design that cleans and freshens incoming air. They are electrostatically charged to grab and hold dust particles. K&N® cabin air filters help control odors while they help capture most mold, mildew, fungus, spores, bacteria and germs. When they get dirty they can be cleaned and reused and best of all, they come with a 10 year/Million mile limited warranty.

When applicable, refer to owner's manual for manufacturers installation/removal instructions. The following are helpful steps when replacing/servicing cabin air filter with K&N® cabin air filter.

1. Locate the glove box on the passenger side dashboard.
2. Open the glove box and release the shock on the right side. (Fig. 1)
3. To release glove box press tabs inward on each side. These tabs are located on the outside of the glove box. (Fig. 2)
4. Pull tray off the dashboard then remove the two screws located on each side. (Fig. 3, Fig. 4)
5. Carefully unclip housing from dashboard and then unplug pig tail on the left side of the housing. (Fig. 5, Fig. 6)
6. Open cabin filter door and remove dirty cabin filter. (Fig. 7, Fig. 8)

NOTE: Remove any debris that might be present inside the cabin filter housing.

4. Install K&N® cabin filter and close door (Fig. 9)
5. Reverse steps 1-5 to complete cabin filter installation. With the cabin filter installed, clean an area on the housing and apply K&N® Stop Decal. The decal will help notify others that this is a reusable cabin filter.



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9

We recommend refreshing your K&N® Cabin Air Filter every 12 months, or 12,000 miles. Use K&N® Refresher kit pt.# 99-6000 which includes the easy to follow instructions.