



INSTALLATION INSTRUCTIONS

Part Number: VF2050

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

K&N® Cabin Air Filters replace your vehicle's stock cabin filter with a reusable design that cleans and freshens incoming air. They are electrostatically charged to grab and hold dust particles. K&N® cabin air filters help control odors while they help capture most mold, mildew, fungus, spores, bacteria and germs. When they get dirty they can be cleaned and reused and best of all, they come with a 10 year/Million mile limited warranty.

When applicable, refer to owner's manual for manufacturers installation/removal instructions. The following are helpful steps when replacing/servicing cabin air filter with K&N® cabin air filter.

1. Remove the side cover, on the right side of the glove box, by pulling it outward. Fig. 1
2. Remove the vent panel by pulling it towards the seats, starting on the right side. Figs. 2 & 3
3. Remove the 4 glove box screws. Two are behind the vent panel (Fig. 4) and two are below the dash (Figs. 5 & 6).
4. Pull the glove box towards you and disconnect the electrical plug in the back, right corner to remove from dash.
5. Remove the two screws holding the cabin filter door in place. Fig. 7
6. Spread the tabs outwards to allow the cabin filter door to open. Fig. 8
7. Remove dirty cabin filter from housing & clean any debris that might be present in the cabin filter housing.
8. Install K&N® Cabin Filter. **NOTE: Filter can only be installed one way with pull tab facing out.** Fig. 9
9. Reverse steps 1-6 to complete cabin filter installation. With the cabin filter installed, clean an area on the cowl and apply the K&N® Stop Decal. The decal will help notify others that this is a re-usable cabin filter.



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6



Fig. 7



Fig. 8



Fig. 9

We recommend refreshing your K&N® Cabin Air Filter every 12 months, or 12,000 miles. Use K&N® Refresher kit pt.# 99-6000 which includes the easy to follow instructions.