

INSTALLATION INSTRUCTIONS Part Number: 33-5026

This filter fits: See catalog for current applications

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modification will be required. However the following procedures MUST be followed to ensure the proper fit and seal of the K&N® air filter.

INSTALLATION:

- 1. Remove the stock filter.
- 2. Place the K&N® filter in the K&N® frame with the filters logo facing the frames cut outs. (See fig. 1)
- 3. Apply the supplied K&N® grease to the seal to ease installation. (See fig. 2)
- 4. Install the K&N[®] filter by pushing the frame with the filter into the air box. (See fig. 3, 4)

 NOTE: Ensure that the seal is resting inside the air box by pushing the frame in completely. (See fig. 5)
- 5. Install the lid on the air box.

CLEANING:

K&N Engineering, Inc., suggests checking the air filter element periodically for excessive dirt build-up. Depending on your driving conditions, we recommend cleaning your air filter every 50,000 miles. To clean and re-oil, purchase our filter Recharger® service kit, part number 99-5050 or 99-5000 and follow the easy instructions.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



fig. 1



fig. 2



fig. 3



fig. 4



fig. 5