
 2 3/8 - 5 7/8  
inch

 4 7/8 - 7 7/8  
inch


 M10

 max. 5.5 US t


 max. 51.5 ft lb

metric imperial

 60 - 150 mm

 122 - 200 mm

 19 mm

 M10

 max. 5 t

 max. 70 Nm

 2.05 kg

metric imperial

## Spare part

[618175](#) Mechanical pressure spindle.

[18-1-T](#) Cross-beam

[018265](#) Side bolt complete

## Accessories

[18-0-AS](#) Set of screw adapters

[18-003A](#) Threaded adapter

[18-004A](#) Threaded adapter

[18-005A](#) Threaded adapter

[18-006A](#) Threaded adapter

[18-008A](#) Threaded adapter

[18-010A](#) Threaded adapter

[18-012A](#) Threaded adapter

[18-016A](#) Threaded adapter

[19-1-P](#) 2 extensions for pulling devices (pair)

[K-600-018](#) Set of interchangeable pressure pads for KUKKO pressure screws

## part of

[15-A](#) Separating-set

[17-A](#) Separating-set with quick clamping pressure spindle

EVLW-1-KFZ Merchandiser, automotiv pullers

EVLW-1-NFZ Merchandiser, automotiv pullers

EVLW-1-INDUSTRIE Display

[WT-019](#) Puller product range - separating

[EVLW-2-KFZ](#) Merchandiser, automotiv pullers

[EVLW-2-NFZ](#) Merchandiser, automotive pullers / commercial vehicle / agricultural machin

## Spare part of

[15-A](#) Separating-set

[17-A](#) Separating-set with quick clamping pressure spindle

## also included in

[WT-014](#) Puller product range - automotive - chassis suspension

Looking for dependable automotive tools? Rely on Kukko for quality and long-lasting products.