


 120 mm

 100 mm

 70 - 180 mm

 17 mm

 max. 2,5 t

 max. 35 Nm


 1.42 kg

 J^x 2

metric imperial

 4 3/4 inch

 3 7/8 inch

 2 3/4 - 7 1/8 inch

 max. 2.5 US t

 max. 25.5 ft lb

 J^x 2

metric imperial

Spare part

[614160](#) Mechanical pressure spindle.

[1-93-P](#) 2 narrow, quick adjusting jaws (pair)

[20-10-T](#) 2-jaw cross bar

Accessories

[219-1](#) Clamp for 2-jaw pullers

[1-193-P](#) 2 narrow, quick adjusting jaws (pair)

[1-253-P](#) 2 narrow, quick adjusting jaws (pair)

[K-600-014](#) Set of interchangeable pressure pads for KUKKO pressure screws

part of

WT-006 Puller product range - automotive

[WT-003+S](#) Puller product range - exterior pulling - BASIC+

[K-2030-10+S](#) Universal 2-jaw and 3-jaw puller set with narrow, quick-adjusting pulling jaws

[20-ST+S](#) Sales display for 2-jaw puller with narrow jaws

Spare part of

WT-006 Puller product range - automotive

[WT-003+S](#) Puller product range - exterior pulling - BASIC+

[20-ST+S](#) Sales display for 2-jaw puller with narrow jaws

also included in

WT-006 Puller product range - automotive

[WT-014](#) Puller product range - automotive - chassis suspension

[K-2030-10+S](#) Universal 2-jaw and 3-jaw puller set with narrow, quick-adjusting pulling jaws

K-2030-10+S+T Set of universal 2- and 3-jaw pullers