



 7 7/8 inch

 5 7/8 inch

 3 7/8 - 10 1/4  
inch

 max. 5.5 US t

 max. 88.5 ft lb

 J<sup>x</sup> 2

metric imperial

 200 mm

 150 mm

 100 - 260 mm

 22 mm

 max. 5 t

 max. 120 Nm

 3.3 kg

 J<sup>x</sup> 2

metric imperial

## Spare part

[621220](#) Mechanical pressure spindle.

[2-153-P](#) 2 narrow, quick adjusting jaws (pair)

[20-20-T](#) 2-jaw cross bar

## Accessories

[2-303-P](#) 2 narrow, quick adjusting jaws (pair)

[30-20-T3](#) 3-jaw cross bar

[K-600-025](#) Set of interchangeable pressure pads for KUKKO pressure screws

## part of

WT-006 Puller product range - automotive

[WT-003+S](#) Puller product range - exterior pulling - BASIC+

[20-ST+S](#) Sales display for 2-jaw puller with narrow jaws

## Spare part of

WT-006 Puller product range - automotive

[WT-003+S](#) Puller product range - exterior pulling - BASIC+

[20-ST+S](#) Sales display for 2-jaw puller with narrow jaws

## also included in

WT-006 Puller product range - automotive

Looking for dependable automotive tools? [Rely on Kukko for quality and long-lasting products.](#)