







 90 mm	 100 mm	 70 - 140 mm
 17 mm	 max. 3 t	 max. 40 Nm
 1.1 kg	 J <sup>x</sup> 3	

metric  imperial

 3 1/2 inch	 3 7/8 inch	 2 3/4 - 5 1/2 inch
 max. 3 US t	 max. 29.5 ft lb	 J <sup>x</sup> 3

metric  imperial

## Spare part

<a href="#">614135</a>	Mechanical pressure spindle.
<a href="#">1-93-S</a>	3 narrow, quick adjusting jaws (set)
<a href="#">30-1-T</a>	3-jaw cross bar

## Accessories

<a href="#">1-93-S</a>	3 narrow, quick adjusting jaws (set)
<a href="#">1-193-S</a>	3 narrow, quick adjusting jaws (set)
<a href="#">1-253-S</a>	3 narrow, quick adjusting jaws (set)
<a href="#">1-95-S</a>	3 extremely narrow, quick adjusting jaws (set)
<a href="#">1-195-S</a>	3 extremely narrow, quick adjusting jaws (set)
<a href="#">1-255-S</a>	3 extremely narrow, quick adjusting jaws (set)
<a href="#">K-600-014</a>	Set of interchangeable pressure pads for KUKKO pressure screws

## part of

<a href="#">EVLW-1-INDUSTRIE</a>	Display
<a href="#">EVLW-2-INDUSTRIE</a>	Display

## also included in

<a href="#">KS-2030-1+S</a>	Set of two- and three-arm pullers with narrow jaws
-----------------------------	--