

 130 mm


 100 mm

 70 - 180 mm

 17 mm

 max. 3 t


 max. 40 Nm

 1.54 kg

 J^x 3

metric imperial

 5 1/8 inch

 3 7/8 inch

 2 3/4 - 7 1/8 inch

 max. 3 US t

 max. 29.5 ft lb

 J^x 3

metric imperial

Spare part

[614135](#) Mechanical pressure spindle.

[1-93-S](#) 3 narrow, quick adjusting jaws (set)

[30-10-T](#) Cross-beam

Accessories

[1-93-S](#) 3 narrow, quick adjusting jaws (set)

[1-193-S](#) 3 narrow, quick adjusting jaws (set)

[1-253-S](#) 3 narrow, quick adjusting jaws (set)

[1-95-S](#) 3 extremely narrow, quick adjusting jaws (set)

[1-195-S](#) 3 extremely narrow, quick adjusting jaws (set)

[1-255-S](#) 3 extremely narrow, quick adjusting jaws (set)

[K-600-014](#) Set of interchangeable pressure pads for KUKKO pressure screws

also included in

[K-2030-10+S](#) Universal 2-jaw and 3-jaw puller set with narrow, quick-adjusting pulling jaws

K-2030-10+S+T Set of universal 2- and 3-jaw pullers

Looking for dependable automotive tools? Rely on Kukko for quality and long-lasting products.